

Customer Information Sheet

[illegible]

NOTES:

1. QUANTITY PER REEL = 2,500.
2. THIS PRODUCT IS TAPED AND REELED IN ACCORDANCE WITH EIA-481-2-A (ELECTRONIC INDUSTRIES ASSOCIATION).
3. FOR LOOSE COMPONENTS, SEE S1751-XX.

 www.harwin.com technical@harwin.com	THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.	TOLERANCES	MATERIAL:	TITLE:	SHT 2 OF 2 S1751-XXR
		$X_1 = \pm 1\text{mm}$ $X_2 = \pm 0.50\text{mm}$ $X_3 = \pm 0.20\text{mm}$ $X_4 = \pm 0.01\text{mm}$	SEE ABOVE	SURFACE MOUNT TEST TERMINAL (TAPE AND REELED)	
		ANGLES = $\pm 5^\circ$ UNLESS STATED	FINISH: SEE ABOVE	DRAWING NUMBER:	
			S/AREA: mm ²		