


Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	✔ Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	✔ 2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	✔ 2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40

Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Maximum Cable Diameter [mm] :	2.40
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	 0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	 1.00
Maximum Cable Core Cross Section [mm2] :	1.00

Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Maximum Cable Core Cross Section [mm2] :	1.00
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	✔ -40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	✔ Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0

Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
RoHs compliant :	 Yes
ELV compliant :	 Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.