



[Home](#) ▶ [2N3227 \(#76574\)](#)

Products

- ▶ [Product Directory](#)
- ▶ [Applications Directory](#)
- ▶ [Parametric Search](#)

2N3227 (#76574)

Overview

Diagrams

Electrical Rating	Symbol	Min	Typ	Max	Unit
DC Current Gain	HFE	40.00		250.00	
Turn Off Time (nS)	t _{off}			25.00	ns

Maximum Electrical Rating	Symbol	Min	Typ	Max	Unit
Collector Current (dc)	I _C			0.10	A
Collector-Emitter Voltage (Base Open)	V _{CEO}			20.00	V
Junction Temperature (°C)	T _J			200.00	°C

This part can be found in the following product categories:

- ▶ [Non-Radiation Hardened Devices](#) ▶ [Transistors](#) ▶ [BJT\(BiPolar Junction Transistor\)](#) ▶ [NPN Transistor](#)
- ▶ [Discretes](#) ▶ [Transistors](#) ▶ [BJT\(BiPolar Junction Transistor\)](#) ▶ [NPN Transistor](#)

Related Links

- [Technical support](#)
- [Sales Contacts](#)
- [Available Stock](#)
- [Sales Contacts](#)
- [RFQ/Samples](#)