

| • | Connector | Туре | = Con | nector | Assembly |
|---|-----------|------|-------|--------|----------|
|---|-----------|------|-------|--------|----------|

• Housing Material = High Temperature Thermoplastic

| <ul> <li><u>Mount Angle</u> = Vertical</li> <li><u>Termination Style</u> = Press Fit</li> </ul> | Configuration Features:   |  |  |
|---|---|--|--|
|   | <ul> <li>Total Number of DC Power = 0</li> </ul>                                    |  |  |
| <ul> <li><u>Mating Type</u> = Blindmate</li> </ul>  |   |  |  |
| <ul> <li><u>PCB Mount Retention</u> = Without</li> </ul>  | <ul> <li><u>Total Number of AC Power</u> = 7</li> </ul>                             |  |  |
| <ul> <li>Guides = With</li> </ul>   | <ul> <li>Total Number of Coax = 0</li> </ul>  |  |  |
|   | <ul> <li><u>Total Number of Signal</u> = 0</li> </ul>                               |  |  |
| Electrical Characteristics:   | <ul> <li>Connector Contact Configuration (No. of Pos./Type) = 7/AC Power</li> </ul> |  |  |
| <ul> <li>Mating Functionality = Standard</li> </ul>   |   |  |  |
| <ul> <li>Voltage Rating (Power) (VAC) = 300</li> </ul>  | Industry Standards:   |  |  |
| ······································  | <ul> <li><u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant</li> </ul>      |  |  |
| Termination Features:   | <ul> <li>Lead Free Solder Processes = Not relevant for lead free process</li> </ul> |  |  |
| <ul> <li>Termination Post Length (mm [in]) = 3.43 [0.135]</li> </ul>                            | <ul> <li>RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul>         |  |  |
|   |   |  |  |
| Body Features:  | Operation/Application:  |  |  |
| <ul> <li>Sequencing = No</li> </ul>   | <ul> <li>Application Use = Board-to-Board</li> </ul>                                |  |  |
| <ul> <li>Connector Configuration Orientation = Right-to-Left</li> </ul>                         |   |  |  |
| <ul> <li>Centerline, AC Module (mm [in]) = 7.62 [0.300]</li> </ul>                              | Other:  |  |  |
| <ul> <li>Centerline, Matrix (mm [in]) = 2.54 × 2.54 [.100 × .100]</li> </ul>                    | Brand = AMP   |  |  |
| • Centernite, Matrix ( $\min[inj) = 2.54 \times 2.54$ [.100 x .100]                             | <ul> <li>Comment = For additional configurations available, contact Tyco</li> </ul> |  |  |
|   | Electronics.  |  |  |
| Contact Features:   |   |  |  |
| <ul> <li>Contact Type = Socket</li> </ul>   |   |  |  |
| <ul> <li>Contact Material (Power) = High Conductivity Copper</li> </ul>                         |   |  |  |
| <ul> <li>Contact Material (Signal) = Copper Alloy</li> </ul>                                    |   |  |  |
| <ul> <li>Contact Plating, Mating Area, Material = Gold (30)</li> </ul>                          |   |  |  |
|   |   |  |  |
|   |   |  |  |

| Corporate Information | Quick Links                       | Customer Support      | Keep Me Informed  |
|-----------------------|-----------------------------------|-----------------------|---|
| Who We Are            | Check Distributor Inventory       | Email or Chat With Us | Receive TE News, Events &<br>Technology Updates<br>Enter your email address |
| Investors             | Cross Reference                   | Find a Phone Number   |   |
| News Room             | Find Documents & Drawings         | Search Knowledge Base |   |
| Supplier Portal       | Product Compliance Support Center | Manage your Account   |   |
| Careers               | Site Map                          |                       | 🕒 🖬 😐 🛅 🐸   |
|                       |                                   |                       |   |

🥟 Provide Website Feedback