


SMD Power Inductor

CDRH4D28C/LD



Electrical Characteristics

Part No.	Stamp	Inductance (μ H) [within] ※1	D.C.R (m Ω) Max. (Typ.) (20℃)	Saturation Current (A) ※2	Temperature Rise Current (A) ※3
CDRH4D28CLDNP-1R0PC	A	$1.0 \pm 25\%$	17.5(14)	3.0	4.9
CDRH4D28CLDNP-2R2PC	B	$2.2 \pm 25\%$	23.8(19)	2.0	3.6
CDRH4D28CLDNP-3R3PC	C	$3.3 \pm 25\%$	28.9(23)	1.6	3.2
CDRH4D28CLDNP-4R7PC	D	$4.7 \pm 25\%$	36.3(29)	1.5	2.9
CDRH4D28CLDNP-6R8PC	E	$6.8 \pm 25\%$	48.8(39)	1.2	2.4
CDRH4D28CLDNP-100PC	F	$10 \pm 25\%$	67.5(54)	0.90	1.8
CDRH4D28CLDNP-150PC	G	$15 \pm 25\%$	93.4(75)	0.81	1.6
CDRH4D28CLDNP-220PC	H	$22 \pm 25\%$	140(112)	0.65	1.25
CDRH4D28CLDNP-330PC	I	$33 \pm 25\%$	223(179)	0.55	0.92
CDRH4D28CLDNP-470PC	J	$47 \pm 25\%$	272(218)	0.43	0.86
CDRH4D28CLDNP-680PC	K	$68 \pm 25\%$	366(293)	0.36	0.72
CDRH4D28CLDNP-101PC	L	$100 \pm 25\%$	520(416)	0.30	0.61

※1. Inductance measuring condition: at 100kHz.

※2. Saturation current: The value of D.C. current when the inductance decreases to 65% of it's nominal value.

※3. Temperature rise current: The value of D.C. current when the temperature rise is $\Delta t = 40^\circ\text{C}$ ($T_a = 20^\circ\text{C}$).













SMD Power Inductor

CDRH4D28C/LD



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT




SMD Power Inductor CDRH4D28C/LD




Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com