
Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
		Conditions	min	typ	max	Offic
Collector Cutoff Current	ICBO	V _{CB} =5V, I _E =0A			1.0	μΑ
Emitter Cutoff Current	IEBO	V _{EB} =1V, I _C =0A			1.0	μΑ
DC Current Gain	hFE	V _{CE} =5V, I _C =50mA	60		150	
Gain-Bandwidth Product	fT	V _{CE} =5V, I _C =50mA	13	16		GHz
Forward Transfer Gain	S21e ²	VCE=5V, IC=50mA, f=1GHz	10	13.5		dB
Noise Figure	NF	V _{CE} =1V, I _C =10mA, f=1GHz		1.2	1.8	dB


Notre) Pay attention to handling since it is liable to be affected by static electricity due to the high-frequency process adopted.


Ordering Information


Device	Package	Shipping	memo	
CPH6020-TL-E	CPH6	3,000pcs./reel	Pb Free	



IC - VCE








Embossed Taping Specification

CPH6020-TL-E


1. Packing Format


Package Name	Carrier Tape	Maximum Number of devices contained (pcs)			Packing format		
	Туре	Reel	Inner box	Outer box	Inner BOX (C-1)	Outer BOX (A-7)	
СРН6	СРН6	3, 000	15, 000	90, 000		6 inner boxes contained Dimensions:mm(external)	
					, , ,	$440 \times 195 \times 210$	



2. Taping configuration

2-1. Carrier tape size (unit:mm)






Those with pin 1 index on the feed hole side · · · · · TL

Outline Drawing

CPH6020-TL-E

Mass (g) Unit 0.015 mm 0. 15^{+0. 1}_{-0. 05} 2. 9±0. 1 0.6±0.1 A 0. 2±0.1 [*1][*1] 0. 05±0.05 2, 8±0, 15 . 6±0. 1 [*1] - \$ 0.95 PIN#1 0.05 \$ *1:Lot indication

Land Pattern Example



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa