

LOADED CONNECTOR ASSEMBLY
(FOR EXAMPLE)

Technical drawing of a multi-pin connector. The drawing includes the following dimensions and callouts:

- Pin 1:** 15.40 ± 0.50
- Pin 2:** 11.70 ± 0.10
- Pin 3:** 11.70 ± 0.10
- Pin 4:** 13.45 ± 0.15
- Pin 5:** 3.00 ± 0.10
- Pin 6:** 2.00 ± 0.05 (10X)
- Pin 7:** 2.00 ± 0.05 (10X)
- Pin 8:** 2.00 ± 0.05 (10X)
- Pin 9:** 2.00 ± 0.05 (10X)
- Pin 10:** 2.00 ± 0.05 (10X)
- Pin 11:** 2.00 ± 0.05 (10X)
- Pin 12:** 2.00 ± 0.05 (10X)
- Pin 13:** 2.00 ± 0.05 (10X)
- Pin 14:** 2.00 ± 0.05 (10X)
- Pin 15:** 2.00 ± 0.05 (10X)
- Pin 16:** 2.00 ± 0.05 (10X)
- Pin 17:** 2.00 ± 0.05 (10X)
- Pin 18:** 2.00 ± 0.05 (10X)
- Pin 19:** 2.00 ± 0.05 (10X)
- Pin 20:** 2.00 ± 0.05 (10X)
- Pin 21:** 2.00 ± 0.05 (10X)
- Pin 22:** 2.00 ± 0.05 (10X)
- Pin 23:** 2.00 ± 0.05 (10X)
- Pin 24:** 2.00 ± 0.05 (10X)
- Pin 25:** 2.00 ± 0.05 (10X)
- Pin 26:** 2.00 ± 0.05 (10X)
- Pin 27:** 2.00 ± 0.05 (10X)
- Pin 28:** 2.00 ± 0.05 (10X)
- Pin 29:** 2.00 ± 0.05 (10X)
- Pin 30:** 2.00 ± 0.05 (10X)
- Pin 31:** 2.00 ± 0.05 (10X)
- Pin 32:** 2.00 ± 0.05 (10X)
- Pin 33:** 2.00 ± 0.05 (10X)
- Pin 34:** 2.00 ± 0.05 (10X)
- Pin 35:** 2.00 ± 0.05 (10X)
- Pin 36:** 2.00 ± 0.05 (10X)
- Pin 37:** 2.00 ± 0.05 (10X)
- Pin 38:** 2.00 ± 0.05 (10X)
- Pin 39:** 2.00 ± 0.05 (10X)
- Pin 40:** 2.00 ± 0.05 (10X)
- Pin 41:** 2.00 ± 0.05 (10X)
- Pin 42:** 2.00 ± 0.05 (10X)
- Pin 43:** 2.00 ± 0.05 (10X)
- Pin 44:** 2.00 ± 0.05 (10X)
- Pin 45:** 2.00 ± 0.05 (10X)
- Pin 46:** 2.00 ± 0.05 (10X)
- Pin 47:** 2.00 ± 0.05 (10X)
- Pin 48:** 2.00 ± 0.05 (10X)
- Pin 49:** 2.00 ± 0.05 (10X)
- Pin 50:** 2.00 ± 0.05 (10X)
- Pin 51:** 2.00 ± 0.05 (10X)
- Pin 52:** 2.00 ± 0.05 (10X)
- Pin 53:** 2.00 ± 0.05 (10X)
- Pin 54:** 2.00 ± 0.05 (10X)
- Pin 55:** 2.00 ± 0.05 (10X)
- Pin 56:** 2.00 ± 0.05 (10X)
- Pin 57:** 2.00 ± 0.05 (10X)
- Pin 58:** 2.00 ± 0.05 (10X)
- Pin 59:** 2.00 ± 0.05 (10X)
- Pin 60:** 2.00 ± 0.05 (10X)
- Pin 61:** 2.00 ± 0.05 (10X)
- Pin 62:** 2.00 ± 0.05 (10X)
- Pin 63:** 2.00 ± 0.05 (10X)
- Pin 64:** 2.00 ± 0.05 (10X)
- Pin 65:** 2.00 ± 0.05 (10X)
- Pin 66:** 2.00 ± 0.05 (10X)
- Pin 67:** 2.00 ± 0.05 (10X)
- Pin 68:** 2.00 ± 0.05 (10X)
- Pin 69:** 2.00 ± 0.05 (10X)
- Pin 70:** 2.00 ± 0.05 (10X)
- Pin 71:** 2.00 ± 0.05 (10X)
- Pin 72:** 2.00 ± 0.05 (10X)
- Pin 73:** 2.00 ± 0.05 (10X)
- Pin 74:** 2.00 ± 0.05 (10X)
- Pin 75:** 2.00 ± 0.05 (10X)
- Pin 76:** 2.00 ± 0.05 (10X)
- Pin 77:** 2.00 ± 0.05 (10X)
- Pin 78:** 2.00 ± 0.05 (10X)
- Pin 79:** 2.00 ± 0.05 (10X)
- Pin 80:** 2.00 ± 0.05 (10X)
- Pin 81:** 2.00 ± 0.05 (10X)
- Pin 82:** 2.00 ± 0.05 (10X)
- Pin 83:** 2.00 ± 0.05 (10X)
- Pin 84:** 2.00 ± 0.05 (10X)
- Pin 85:** 2.00 ± 0.05 (10X)
- Pin 86:** 2.00 ± 0.05 (10X)
- Pin 87:** 2.00 ± 0.05 (10X)
- Pin 88:** 2.00 ± 0.05 (10X)
- Pin 89:** 2.00 ± 0.05 (10X)
- Pin 90:** 2.00 ± 0.05 (10X)
- Pin 91:** 2.00 ± 0.05 (10X)
- Pin 92:** 2.00 ± 0.05 (10X)
- Pin 93:** 2.00 ± 0.05 (10X)
- Pin 94:** 2.00 ± 0.05 (10X)
- Pin 95:** 2.00 ± 0.05 (10X)
- Pin 96:** 2.00 ± 0.05 (10X)
- Pin 97:** 2.00 ± 0.05 (10X)
- Pin 98:** 2.00 ± 0.05 (10X)
- Pin 99:** 2.00 ± 0.05 (10X)
- Pin 100:** 2.00 ± 0.05 (10X)
- Pin 101:** 2.00 ± 0.05 (10X)
- Pin 102:** 2.00 ± 0.05 (10X)
- Pin 103:** 2.00 ± 0.05 (10X)
- Pin 104:** 2.00 ± 0.05 (10X)
- Pin 105:** 2.00 ± 0.05 (10X)
- Pin 106:** 2.00 ± 0.05 (10X)
- Pin 107:** 2.00 ± 0.05 (10X)
- Pin 108:** 2.00 ± 0.05 (10X)
- Pin 109:** 2.00 ± 0.05 (10X)
- Pin 110:** 2.00 ± 0.05 (10X)
- Pin 111:** 2.00 ± 0.05 (10X)
- Pin 112:** 2.00 ± 0.05 (10X)
- Pin 113:** 2.00 ± 0.05 (10X)

PLATING CODE (DIGIT 13 AND 14)
(REF DWG No BS.C 201844.003)

NOTES:

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT : PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASSFILLED
POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN
MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER
DEPENDING ON PRODUCTION LOCATION.
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A :201572.001

1DEC ± 0.2	APPR.	DATE	SIGN.	MPACS 5R STR HDR CONN TYPE C
2DEC ± 0.1				
ANGLES ± 1°	DRAFT	2001-07-20	M.Fre!	CAT. No. HM2P09PD5110----
	CHECKED			
	PROD. MGR.			
	PR. ENG. MGR.			
	PR. MGT. MGR.			
	PR. DIMENSIONS.			
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS WITHOUT PRIOR NOTICE				SCALE
				www.fciconnect.com

REFERENCES



THIS IS OUR EXCLUSIVE PROPERTY. IT IS NOT TO BE COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY, NOR USED FOR MANUFACTURING WITHOUT OUR WRITTEN CONSENT AND HAS TO BE RETURNED TO US IN CASE OF NO USAGE

DIT IS ONZE EIGENDOM EN MAG NOCH NAGEMAAKT, HERDUKT, OVERGEMAAKT AAN DERDEN, NOCH VOOR FABRIKATIE GEBRUIKT WORDEN, ZONDER ONZE SCHRIFTELIJKE TOELATING. RIJ NIET GEBRUIK IS TERUGZENDING VERPLICHT.

BS, C, 202788, 154

Revised

STATISTICS DRAWING No. **Revised** CUSTOMER DRAWING REVISION