



## PIN CONFIGURATIONS

### 48-Pin mini BGA (6mm x 8mm)




### 44-Pin TSOP-II



## PIN DESCRIPTIONS

|                 |                                 |
|-----------------|---------------------------------|
| A0-A15          | Address Inputs                  |
| I/O0-I/O15      | Data Inputs/Outputs             |
| CE              | Chip Enable Input               |
| OE              | Output Enable Input             |
| WE              | Write Enable Input              |
| LB              | Lower-byte Control (I/O0-I/O7)  |
| UB              | Upper-byte Control (I/O8-I/O15) |
| NC              | No Connection                   |
| V <sub>DD</sub> | Power                           |
| GND             | Ground                          |

### 44-Pin SOJ (K)



## TRUTH TABLE

| Mode            | $\overline{WE}$ | $\overline{OE}$ | $\overline{OE}$ | $\overline{LB}$ | $\overline{UB}$ | I/O PIN          |                  | V <sub>DD</sub> Current             |
|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|------------------|-------------------------------------|
|                 |                 |                 |                 |                 |                 | I/O0-I/O7        | I/O8-I/O15       |                                     |
| Not Selected    | X               | H               | X               | X               | X               | High-Z           | High-Z           | I <sub>SB1</sub> , I <sub>SB2</sub> |
| Output Disabled | H               | L               | H               | X               | X               | High-Z           | High-Z           | I <sub>CC</sub>                     |
|                 | X               | L               | X               | H               | H               | High-Z           | High-Z           |                                     |
| Read            | H               | L               | L               | L               | H               | D <sub>OUT</sub> | High-Z           | I <sub>CC</sub>                     |
|                 | H               | L               | L               | H               | L               | High-Z           | D <sub>OUT</sub> |                                     |
|                 | H               | L               | L               | L               | L               | D <sub>OUT</sub> | D <sub>OUT</sub> |                                     |
| Write           | L               | L               | X               | L               | H               | D <sub>IN</sub>  | High-Z           | I <sub>CC</sub>                     |
|                 | L               | L               | X               | H               | L               | High-Z           | D <sub>IN</sub>  |                                     |
|                 | L               | L               | X               | L               | L               | D <sub>IN</sub>  | D <sub>IN</sub>  |                                     |

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

| Symbol            | Parameter                            | Value                        | Unit |
|-------------------|--------------------------------------|------------------------------|------|
| V <sub>TERM</sub> | Terminal Voltage with Respect to GND | -0.5 to V <sub>DD</sub> +0.5 | V    |
| T <sub>STG</sub>  | Storage Temperature                  | -65 to +150                  | °C   |
| P <sub>T</sub>    | Power Dissipation                    | 1.5                          | W    |
| V <sub>DD</sub>   | V <sub>DD</sub> Related to GND       | -0.2 to +3.9                 | V    |

### Note:

1. Stress greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

## OPERATING RANGE (V<sub>DD</sub>)

| Range      | Ambient Temperature | V <sub>DD</sub> (15 ns) | V <sub>DD</sub> (12 ns) |
|------------|---------------------|-------------------------|-------------------------|
| Commercial | 0°C to +70°C        | 2.5V-3.6V               | 3.3V ± 10%              |
| Industrial | -40°C to +85°C      | 2.5V-3.6V               | 3.3V ± 10%              |
| Automotive | -40°C to +125°C     | 2.5V-3.6V               | 3.3V ± 10%              |

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

**V<sub>DD</sub> = 2.5V-3.6V**

| Symbol          | Parameter                        | Test Conditions                                             | Min. | Max.                  | Unit |
|-----------------|----------------------------------|-------------------------------------------------------------|------|-----------------------|------|
| V <sub>OH</sub> | Output HIGH Voltage              | V <sub>DD</sub> = Min., I <sub>OH</sub> = -1.0 mA           | 2.3  | —                     | V    |
| V <sub>OL</sub> | Output LOW Voltage               | V <sub>DD</sub> = Min., I <sub>OL</sub> = 1.0 mA            | —    | 0.4                   | V    |
| V <sub>IH</sub> | Input HIGH Voltage               |                                                             | 2.0  | V <sub>DD</sub> + 0.3 | V    |
| V <sub>IL</sub> | Input LOW Voltage <sup>(1)</sup> |                                                             | -0.3 | 0.8                   | V    |
| I <sub>LI</sub> | Input Leakage                    | GND ≤ V <sub>IN</sub> ≤ V <sub>DD</sub>                     | -2   | 2                     | μA   |
| I <sub>LO</sub> | Output Leakage                   | GND ≤ V <sub>OUT</sub> ≤ V <sub>DD</sub> , Outputs Disabled | -2   | 2                     | μA   |

### Note:

- V<sub>IL</sub> (min.) = -0.3V DC; V<sub>IL</sub> (min.) = -2.0V AC (pulse width 2.0 ns). Not 100% tested.  
V<sub>IH</sub> (max.) = V<sub>DD</sub> + 0.3V DC; V<sub>IH</sub> (max.) = V<sub>DD</sub> + 2.0V AC (pulse width 2.0 ns). Not 100% tested.

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

**V<sub>DD</sub> = 3.3V ± 10%**

| Symbol          | Parameter                        | Test Conditions                                             | Min. | Max.                  | Unit |
|-----------------|----------------------------------|-------------------------------------------------------------|------|-----------------------|------|
| V <sub>OH</sub> | Output HIGH Voltage              | V <sub>DD</sub> = Min., I <sub>OH</sub> = -4.0 mA           | 2.4  | —                     | V    |
| V <sub>OL</sub> | Output LOW Voltage               | V <sub>DD</sub> = Min., I <sub>OL</sub> = 8.0 mA            | —    | 0.4                   | V    |
| V <sub>IH</sub> | Input HIGH Voltage               |                                                             | 2    | V <sub>DD</sub> + 0.3 | V    |
| V <sub>IL</sub> | Input LOW Voltage <sup>(1)</sup> |                                                             | -0.3 | 0.8                   | V    |
| I <sub>LI</sub> | Input Leakage                    | GND ≤ V <sub>IN</sub> ≤ V <sub>DD</sub>                     | -2   | 2                     | μA   |
| I <sub>LO</sub> | Output Leakage                   | GND ≤ V <sub>OUT</sub> ≤ V <sub>DD</sub> , Outputs Disabled | -2   | 2                     | μA   |

### Note:

- V<sub>IL</sub> (min.) = -0.3V DC; V<sub>IL</sub> (min.) = -2.0V AC (pulse width 2.0 ns). Not 100% tested.  
V<sub>IH</sub> (max.) = V<sub>DD</sub> + 0.3V DC; V<sub>IH</sub> (max.) = V<sub>DD</sub> + 2.0V AC (pulse width 2.0 ns). Not 100% tested.

**POWER SUPPLY CHARACTERISTICS<sup>(1)</sup>** (Over Operating Range)

| Symbol           | Parameter                                        | Test Conditions                                                                                                                          | Options             | -12 ns |      | -15 ns |      | Unit |
|------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------|--------|------|--------|------|------|
|                  |                                                  |                                                                                                                                          |                     | Min.   | Max. | Min.   | Max. |      |
| I <sub>CC</sub>  | V <sub>DD</sub> Dynamic Operating Supply Current | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0 mA, f = f <sub>MAX</sub>                                                                 | COM.                | —      | 35   | —      | 30   | mA   |
|                  |                                                  |                                                                                                                                          | IND.                | —      | 45   | —      | 40   |      |
|                  |                                                  |                                                                                                                                          | AUTO                | —      | 60   | —      | 50   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —      | 20   | —      | 20   |      |
| I <sub>CC1</sub> | Operating Supply Current                         | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0mA, f = 0                                                                                 | COM.                | —      | 5    | —      | 5    | mA   |
|                  |                                                  |                                                                                                                                          | IND.                | —      | 5    | —      | 5    |      |
|                  |                                                  |                                                                                                                                          | AUTO                | —      | 5    | —      | 5    |      |
| I <sub>SB2</sub> | CMOS Standby Current (CMOS Inputs)               | V <sub>DD</sub> = Max.,<br>CE ≥ V <sub>DD</sub> – 0.2V,<br>V <sub>IN</sub> ≥ V <sub>DD</sub> – 0.2V, or<br>V <sub>IN</sub> ≤ 0.2V, f = 0 | COM.                | —      | 20   | —      | 20   | uA   |
|                  |                                                  |                                                                                                                                          | IND.                | —      | 50   | —      | 50   |      |
|                  |                                                  |                                                                                                                                          | AUTO                | —      | 75   | —      | 75   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —      | 6    | —      | 6    |      |

**Note:**

- At f = f<sub>MAX</sub>, address and data inputs are cycling at the maximum frequency, f = 0 means no input lines change.
- Typical values are measured at V<sub>DD</sub>=2.5V, T<sub>A</sub>=25°C. Not 100% tested.

**CAPACITANCE<sup>(1)</sup>**

| Symbol           | Parameter                | Conditions            | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|
| C <sub>IN</sub>  | Input Capacitance        | V <sub>IN</sub> = 0V  | 6    | pF   |
| C <sub>OUT</sub> | Input/Output Capacitance | V <sub>OUT</sub> = 0V | 8    | pF   |

**Note:**

- Tested initially and after any design or process changes that may affect these parameters.

AC TEST CONDITIONS

| Parameter                                                          | Unit<br>(2.5V-3.6V)     | Unit<br>(3.3V ± 10%)      |
|--------------------------------------------------------------------|-------------------------|---------------------------|
| Input Pulse Level                                                  | 0V to V <sub>DD</sub> V | 0V to V <sub>DD</sub> V   |
| Input Rise and Fall Times                                          | 1.5ns                   | 1.5ns                     |
| Input and Output Timing<br>and Reference Level (V <sub>Ref</sub> ) | V <sub>DD</sub> /2      | V <sub>DD</sub> /2 + 0.05 |
| Output Load                                                        | See Figures 1a and 1b   | See Figures 1a and 1b     |

AC TEST LOADS




Figure 1a.




Figure 1b.

**READ CYCLE SWITCHING CHARACTERISTICS<sup>(1)</sup>** (Over Operating Range)


| Symbol                           | Parameter                                          | -12 ns |      |      |      | -15 ns | Unit |
|----------------------------------|----------------------------------------------------|--------|------|------|------|--------|------|
|                                  |                                                    | Min.   | Max. | Min. | Max. |        |      |
| t <sub>RC</sub>                  | Read Cycle Time                                    | 12     | —    | 15   | —    | ns     |      |
| t <sub>AA</sub>                  | Address Access Time                                | —      | 12   | —    | 15   | ns     |      |
| t <sub>OHA</sub>                 | Output Hold Time                                   | 3      | —    | 3    | —    | ns     |      |
| t <sub>ACE</sub>                 | $\overline{CE}$ Access Time                        | —      | 12   | —    | 15   | ns     |      |
| t <sub>DOE</sub>                 | $\overline{OE}$ Access Time                        | —      | 6    | —    | 7    | ns     |      |
| t <sub>HZOE</sub> <sup>(2)</sup> | $\overline{OE}$ to High-Z Output                   | —      | 6    | 0    | 6    | ns     |      |
| t <sub>LZOE</sub> <sup>(2)</sup> | $\overline{OE}$ to Low-Z Output                    | 0      | —    | 0    | —    | ns     |      |
| t <sub>HZCE</sub> <sup>(2)</sup> | $\overline{CE}$ to High-Z Output                   | 0      | 6    | 0    | 6    | ns     |      |
| t <sub>LZCE</sub> <sup>(2)</sup> | $\overline{CE}$ to Low-Z Output                    |        | 3    | —    | 3    | —      | ns   |
| t <sub>BA</sub>                  | $\overline{LB}$ , $\overline{UB}$ Access Time      | —      | 6    | —    | 7    | ns     |      |
| t <sub>HZB</sub>                 | $\overline{LB}$ , $\overline{UB}$ to High-Z Output | 0      | 6    | 0    | 6    | ns     |      |
| t <sub>LZB</sub>                 | $\overline{LB}$ , $\overline{UB}$ to Low-Z Output  | 0      | —    | 0    | —    | ns     |      |

**Notes:**


1. Test conditions assume signal transition times of 1.5 ns or less, timing reference levels of 1.25V, input pulse levels of 0V to V<sub>DD</sub> V and output loading specified in Figure 1a.
2. Tested with the load in Figure 1b. Transition is measured ±500 mV from steady-state voltage. Not 100% tested.
3. Not 100% tested.

## AC WAVEFORMS

### READ CYCLE NO. 1<sup>(1,2)</sup> (Address Controlled) ( $\overline{CS} = \overline{OE} = V_{IL}$ , $\overline{UB}$ or $\overline{LB} = V_{IL}$ )



### READ CYCLE NO. 2<sup>(1,3)</sup>



#### Notes:

1.  $\overline{WE}$  is HIGH for a Read Cycle.
2. The device is continuously selected.  $\overline{OE}$ ,  $\overline{CE}$ ,  $\overline{UB}$ , or  $\overline{LB} = V_{IL}$ .
3. Address is valid prior to or coincident with  $\overline{CE}$  LOW transition.


**WRITE CYCLE SWITCHING CHARACTERISTICS<sup>(1,2)</sup>** (Over Operating Range)

| Symbol                           | Parameter                                               | -12 ns |      | -15 ns |      | Unit |
|----------------------------------|---------------------------------------------------------|--------|------|--------|------|------|
|                                  |                                                         | Min.   | Max. | Min.   | Max. |      |
| t <sub>WC</sub>                  | Write Cycle Time                                        | 12     | —    | 15     | —    | ns   |
| t <sub>SCE</sub>                 | $\overline{CE}$ to Write End                            | 9      | —    | 10     | —    | ns   |
| t <sub>AW</sub>                  | Address Setup Time to Write End                         | 9      | —    | 10     | —    | ns   |
| t <sub>HA</sub>                  | Address Hold from Write End                             | 0      | —    | 0      | —    | ns   |
| t <sub>SA</sub>                  | Address Setup Time                                      | 0      | —    | 0      | —    | ns   |
| t <sub>PWB</sub>                 | $\overline{LB}$ , $\overline{UB}$ Valid to End of Write | 9      | —    | 10     | —    | ns   |
| t <sub>PWE1</sub>                | $\overline{WE}$ Pulse Width ( $\overline{OE}$ = HIGH)   | 9      | —    | 10     | —    | ns   |
| t <sub>PWE2</sub>                | $\overline{WE}$ Pulse Width ( $\overline{OE}$ = LOW)    | 11     | —    | 12     | —    | ns   |
| t <sub>SD</sub>                  | Data Setup to Write End                                 | 9      | —    | 9      | —    | ns   |
| t <sub>HD</sub>                  | Data Hold from Write End                                | 0      | —    | 0      | —    | ns   |
| t <sub>HZWE</sub> <sup>(3)</sup> | $\overline{WE}$ LOW to High-Z Output                    | —      | 6    | —      | 7    | ns   |
| t <sub>LZWE</sub> <sup>(3)</sup> | $\overline{WE}$ HIGH to Low-Z Output                    | 3      | —    | 3      | —    | ns   |


**Notes:**

1. Test conditions for IS61WV6416BLL assume signal transition times of 1.5ns or less, timing reference levels of 1.25V, input pulse levels of 0V to V<sub>DD</sub> V and output loading specified in Figure 1a.
2. Tested with the load in Figure 1b. Transition is measured  $\pm 500$  mV from steady-state voltage. Not 100% tested.
3. The internal write time is defined by the overlap of  $\overline{CE}$  LOW and  $\overline{UB}$  or  $\overline{LB}$ , and  $\overline{WE}$  LOW. All signals must be in valid states to initiate a Write, but any one can go inactive to terminate the Write. The Data Input Setup and Hold timing are referenced to the rising or falling edge of the signal that terminates the write.


**WRITE CYCLE NO. 1<sup>(1,2)</sup>** ( $\overline{CE}$  Controlled,  $\overline{OE}$  = HIGH or LOW)




**WRITE CYCLE NO. 2<sup>(1)</sup>** ( $\overline{WE}$  Controlled,  $\overline{OE}$  = HIGH during Write Cycle)



**WRITE CYCLE NO. 3** ( $\overline{WE}$  Controlled:  $\overline{OE}$  is LOW During Write Cycle)



**WRITE CYCLE NO. 4** ( $\overline{\text{LB}}$ ,  $\overline{\text{UB}}$  Controlled, Back-to-Back Write) <sup>(1,3)</sup>



**Notes:**

1. The internal Write time is defined by the overlap of  $\overline{\text{CE}} = \text{LOW}$ ,  $\overline{\text{UB}}$  and/or  $\overline{\text{LB}} = \text{LOW}$ , and  $\overline{\text{WE}} = \text{LOW}$ . All signals must be in valid states to initiate a Write, but any can be deasserted to terminate the Write. The  $t_{SA}$ ,  $t_{HA}$ ,  $t_{SD}$ , and  $t_{HD}$  timing is referenced to the rising or falling edge of the signal that terminates the Write.
2. Tested with  $\overline{\text{OE}}$  HIGH for a minimum of 4 ns before  $\overline{\text{WE}} = \text{LOW}$  to place the I/O in a HIGH-Z state.
3.  $\overline{\text{WE}}$  may be held LOW across many address cycles and the  $\overline{\text{LB}}$ ,  $\overline{\text{UB}}$  pins can be used to control the Write function.


DATA RETENTION SWITCHING CHARACTERISTICS

| Symbol           | Parameter                          | Test Condition                                             | Operations           | Min.            | Typ. <sup>(1)</sup> | Max.           | Unit |
|------------------|------------------------------------|------------------------------------------------------------|----------------------|-----------------|---------------------|----------------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                                |                      | 1.8             | —                   | 3.6            | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 1.8V, $\overline{CE} \geq V_{DD} - 0.2V$ | COM.<br>IND.<br>AUTO | —<br>—<br>—     | 6<br>6<br>6         | 20<br>50<br>75 | μA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                                |                      | 0               | —                   | —              | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                                |                      | t <sub>RC</sub> | —                   | —              | ns   |

Note:

1. Typical values are measured at V<sub>DD</sub> = 2.5V, T<sub>A</sub> = 25°C. Not 100% tested.

DATA RETENTION WAVEFORM ( $\overline{CE}$  Controlled)



## ORDERING INFORMATION

### Commercial Temperature Range: 0°C to +70°C

| Speed (ns) | Order Part No.     | Package                        |
|------------|--------------------|--------------------------------|
| 12         | IS61WV6416BLL-12KL | 400-mil Plastic SOJ, Lead-free |

### Industrial Temperature Range: -40°C to +85°C



| Speed (ns) | Order Part No.      | Package                         |
|------------|---------------------|---------------------------------|
| 12         | IS61WV6416BLL-12TI  | Plastic TSOP                    |
| 12         | IS61WV6416BLL-12TLI | Plastic TSOP, Lead-free         |
| 12         | IS61WV6416BLL-12KLI | 400-mil Plastic SOJ, Lead-free  |
| 12         | IS61WV6416BLL-12BI  | mini BGA (6mm x 8mm)            |
| 12         | IS61WV6416BLL-12BLI | mini BGA (6mm x 8mm), Lead-free |
| 15         | IS61WV6416BLL-15TLI | Plastic TSOP, Lead-free         |
| 15         | IS61WV6416BLL-15BI  | mini BGA (6mm x 8mm)            |
| 15         | IS61WV6416BLL-15BLI | mini BGA (6mm x 8mm), Lead-free |

### Temperature Range (A3): -40°C to +125°C


| Speed (ns)            | Order Part No.       | Package                         |
|-----------------------|----------------------|---------------------------------|
| 15 (12 <sup>1</sup> ) | IS64WV6416BLL-15TA3  | Plastic TSOP                    |
| 15 (12 <sup>1</sup> ) | IS64WV6416BLL-15TLA3 | Plastic TSOP, Lead-free         |
| 15 (12 <sup>1</sup> ) | IS64WV6416BLL-15BA3  | mini BGA (6mm x 8mm)            |
| 15 (12 <sup>1</sup> ) | IS64WV6416BLL-15BLA3 | mini BGA (6mm x 8mm), Lead-free |

**Note:**

1. Speed = 12ns for V<sub>DD</sub> = 3.3V ± 10%. Speed = 15ns for V<sub>DD</sub> = 2.5V- 3.6V.




| SYMBOL | DIMENSION IN MM |       |       | DIMENSION IN INCH |       |       |
|--------|-----------------|-------|-------|-------------------|-------|-------|
|        | MIN.            | NOM.  | MAX.  | MIN.              | NOM.  | MAX.  |
| A      | 3.25            |       | 3.76  | 0.128             |       | 0.148 |
| A1     | 2.08            |       |       | 0.082             |       |       |
| A3     | 0.635           |       |       | 0.025             |       |       |
| b      | 0.38            |       | 0.51  | 0.015             |       | 0.020 |
| b2     | 0.66            | 0.71  | 0.81  | 0.026             | 0.028 | 0.032 |
| D      | 20.82           | 20.95 | 21.08 | 0.820             | 0.825 | 0.830 |
| E      | 11.05           | 11.18 | 11.30 | 0.435             | 0.440 | 0.445 |
| E1     | 10.03           | 10.16 | 10.29 | 0.395             | 0.400 | 0.405 |
| E2     | 9.40            | BSC.  |       | 0.370             | BSC.  |       |
| e      | 1.27            | BSC.  |       | 0.050             | BSC.  |       |
| ZD     | 0.95            | REF   |       | 0.037             | REF   |       |



NOTE :

1. Controlling dimension : mm
2. Dimension D and E1 do not include mold protrusion .
3. Dimension b2 does not include dambar protrusion/intrusion.
4. Formed leads shall be planar with respect to one another within 0.1mm at the seating plane after final test.
5. Reference document : JEDEC SPEC MS-027.

|      |       |                                   |      |   |      |            |
|------|-------|-----------------------------------|------|---|------|------------|
| ISSI | TITLE | 32L 400mil SOJ<br>Package Outline | REV. | E | DATE | 12/19/2007 |
|------|-------|-----------------------------------|------|---|------|------------|




| SYMBOL | DIMENSION IN MM |      |      | DIMENSION IN INCH |       |       |
|--------|-----------------|------|------|-------------------|-------|-------|
|        | MIN.            | NOM. | MAX. | MIN.              | NOM.  | MAX.  |
| A      |                 |      | 1.20 |                   |       | 0.047 |
| A1     | 0.20            |      | 0.30 | 0.008             |       | 0.012 |
| Øb     | 0.30            | 0.35 | 0.40 | 0.012             | 0.014 | 0.016 |
| D      | 7.90            | 8.00 | 8.10 | 0.311             | 0.315 | 0.319 |
| D1     | 5.25            | BSC  |      | 0.207             | BSC   |       |
| E      | 5.90            | 6.00 | 6.10 | 0.232             | 0.236 | 0.240 |
| E1     | 3.75            | BSC  |      | 0.148             | BSC   |       |
| e      | 0.75            | BSC. |      | 0.030             | BSC.  |       |
| ZD     | 1.375           | REF. |      | 0.054             | REF.  |       |
| ZE     | 1.125           | REF. |      | 0.044             | REF.  |       |

NOTE :

1. CONTROLLING DIMENSION : MM.
2. Reference document : JEDEC MO-207

|      |       |                                     |      |   |      |            |
|------|-------|-------------------------------------|------|---|------|------------|
| ISSI | TITLE | 48L 6x8mm TF-BGA<br>Package Outline | REV. | C | DATE | 08/12/2008 |
|------|-------|-------------------------------------|------|---|------|------------|



|      |                 |                   |      |   |      |            |
|------|-----------------|-------------------|------|---|------|------------|
| ISSI | TITLE           | 44L 400mil TSOP-2 | REV. | F | DATE | 06/04/2008 |
|      | Package Outline |                   |      |   |      |            |