


## CONTACTS


| Wire Range |                 | Wire Insulation Dia. mm <sup>2</sup> | Tab        |             | Receptacle |             | Applicator Part Number |               |          |           |  | Extraction Tool |            |
|------------|-----------------|--------------------------------------|------------|-------------|------------|-------------|------------------------|---------------|----------|-----------|--|-----------------|------------|
| AWG        | mm <sup>2</sup> |                                      | Strip Form | Loose Piece | Strip Form | Loose Piece | Automatic              | Semiautomatic |          | Hand Tool |  | Tab             | Receptacle |
| 26-22      | 0.14-0.34       | 1.30-2.00                            | 177916-1   | 179594-1    | 177914-1   | 179592-1    | 680283-1               | 680283-2      | 680283-3 | 91567-1   |  | 234914-1        | 234912-1   |
|            |                 |                                      |            |             | 177914-2*  | 179592-2*   |                        |               |          |           |  |                 |            |
| 20-16      | 0.51-1.38       | 2.00-3.10                            | 177917-1   | 179595-1    | 177915-1   | 179593-1    | 680286-1               | 680286-2      | 680286-3 | 91569-1   |  |                 |            |
|            |                 |                                      |            |             | 177915-2*  | 179593-2*   |                        |               |          |           |  |                 |            |

See Application Specification 114-5175 &amp; Instruction Sheet 411-5638

\* Part Number suffix -2 represents high contact pressure type



Tab



Receptacle

The PDL contacts are phosphor bronze with pre-tin plating and designed without lances to prevent entanglement of contacts with one another. The receptacle contact gets loaded into the plug housings and the tab contact gets loaded into cap housings.



The semi-inner locking system of the PDL design helps eliminate unmating by external force and the audible click helps indicate the connector system is fully latched. The smooth compact design prevents snagging when mated.

## PLUG HOUSINGS

## 3.96 mm Centerline Spacing

| No. of Pos. | No. of Rows | Base Part No.       | Available Color Options (Part No. Suffix) <sup>4</sup> |    |    |    |    | Double Lock Plate Part No. <sup>1</sup> |
|-------------|-------------|---------------------|--|----|----|----|----|---|
| 1           | 1           | 316768              | -1   | -2 | -4 | -6 | -9 | 316770-1                                |
| 2           | 1           | 177898 <sup>2</sup> | -1   | -2 | -4 | -6 | -9 | 177918-1                                |
| 3           | 1           | 177899 <sup>2</sup> | -1   | -2 | -4 | -6 | -9 | 177919-1                                |
| 4           | 1           | 316501 <sup>2</sup> | -1   |    | -4 | -6 |    | 177920-1                                |
| 4           | 2           | 177900 <sup>2</sup> | -1   |    | -4 | -6 |    | 177918-1                                |
| 6           | 2           | 177901 <sup>2</sup> | -1   |    | -4 | -6 |    | 177919-1                                |
| 8           | 2           | 177902 <sup>2</sup> | -1   |    | -4 | -6 |    | 177920-1                                |
| 9           | 3           | 177903 <sup>2</sup> | -1   |    | -4 | -6 |    | 177919-1                                |
| 10          | 2           | 177904              | -1   |    | -4 | -6 |    | 177921-1                                |
| 12          | 3           | 177905              | -1   |    | -4 | -6 |    | 177920-1                                |

## 6.5 mm Centerline Spacing

|    |   |                     |    |    |    |    |    |          |
|----|---|---------------------|----|----|----|----|----|----------|
| 2  | 1 | 1939344             | -1 |    |    |    |    | 316061-1 |
| 3  | 1 | 179938              | -1 | -2 | -4 | -6 | -9 | 316062-1 |
| 4  | 1 | 179939              | -1 |    | -4 | -6 | -9 | 316063-1 |
| 4  | 2 | 179861 <sup>3</sup> | -1 |    | -4 | -6 |    | 316061-1 |
| 6  | 2 | 179862 <sup>3</sup> | -1 |    | -4 | -6 |    | 316062-1 |
| 12 | 2 | 917354 <sup>3</sup> | -1 |    |    |    |    | 353891-1 |

## 7.92 mm Centerline Spacing

|   |   |                     |    |    |    |    |    |          |
|---|---|---------------------|----|----|----|----|----|----------|
| 2 | 1 | 177899 <sup>2</sup> | -1 | -2 | -4 | -6 | -9 | 177919-1 |
|---|---|---------------------|----|----|----|----|----|----------|

## 13.0 mm Centerline Spacing

|   |   |        |    |    |    |    |    |          |
|---|---|--------|----|----|----|----|----|----------|
| 2 | 1 | 179938 | -1 | -2 | -4 | -6 | -9 | 316062-1 |
|---|---|--------|----|----|----|----|----|----------|

## Notes:

1. Refer to No. of Rows to specify the number of double lock plates required.
2. Available in Type II lock, see catalog 82181 for details.
3. Available in Type B, see catalog 82181 for details.
4. Color Key Code: -1 Natural, -2 Red, -4 Yellow, -6 Blue, -9 Black

## CAP HOUSINGS

## 3.96 mm Centerline Spacing

| No. of Pos. | No. of Rows | Free-Hanging | Panel Mount | Available Color Options (Part No. Suffix) <sup>4</sup> |    |    |    |    | Double Lock Plate Part No <sup>1</sup> |
|-------------|-------------|--------------|-------------|--|----|----|----|----|--|
| 1           | 1           | 316769       | —           | -1   | -2 | -4 | -6 | -9 | 316770-1                               |
| 2           | 1           | 179463       | 177906      | -1   | -2 | -4 | -6 | -9 | 177918-1                               |
| 3           | 1           | 179464       | 177907      | -1   | -2 | -4 | -6 | -9 | 177919-1                               |
| 4           | 1           | —            | 316502      | -1   |    | -4 | -6 |    | 177920-1                               |
| 4           | 2           | 179465       | 177908      | -1   |    | -4 | -6 |    | 177918-1                               |
| 6           | 2           | 179466       | 177909      | -1   |    | -4 | -6 |    | 177919-1                               |
| 8           | 2           | 179467       | —           | -1   |    | -4 | -6 |    | 177920-1                               |
| 9           | 3           | —            | 177911      | -1   |    | -4 | -6 |    | 177919-1                               |
| 10          | 2           | —            | 177912      | -1   |    | -4 | -6 |    | 177921-1                               |
| 12          | 3           | 1903720      | 177913      | -1   |    | -4 | -6 |    | 177920-1                               |



A double lock plate is available for both plug and cap housings to ensure positive loading and to help prevent contact back-out.

## HEADERS

| No. of Pos.               | Rows | Base Part No. | Available Color Options (Part No. Suffix) <sup>4</sup> |    |    |    |    |
|---------------------------|------|---------------|--|----|----|----|----|
| 3.96 mm Centerline        |      |               |  |    |    |    |    |
| 2                         | 1    | 179838        | -1   | -2 | -4 | -6 | -9 |
| 3                         | 1    | 179839        | -1   | -2 | -4 | -6 | -9 |
| 4                         | 2    | 179840        | -1   |    | -4 | -6 |    |
| 6                         | 2    | 179841        | -1   |    | -4 | -6 |    |
| 8                         | 2    | 917845        | -1   |    | -4 | -6 |    |
| 12                        | 3    | 179843        | -1   |    | -4 | -6 |    |
| 6.5 mm Centerline Spacing |      |               |  |    |    |    |    |
| 3                         | 1    | 179846        | -1   |    | -4 | -6 |    |
| 4                         | 2    | 179848        | -1   |    | -4 | -6 |    |
| 6                         | 2    | 179849        | -1   |    | -4 | -6 |    |
| 12                        | 2    | 917353*       | -1   |    |    |    |    |
| 13 mm Centerline Spacing  |      |               |  |    |    |    |    |
| 2                         | 1    | 917745        | -1   |    | -4 | -6 |    |

\*Available without kink, see catalog # 82181 for details.



The PDL headers offer a kink in the solder tail along with the kink in the mounting boss which secures the header on the board firmly while soldering. Board-mounted headers are compatible with resin or conformal coatings (no drain holes).

## CONNECTOR KITS PROVIDED BY WALDOM ELECTRONICS

| Kit Part Number | Description  |
|-----------------|--|
| 2110837-1       | Power Double Lock Panel Mount Plug, Receptacle and Double Lock Plate Connector Kit |
| 2110837-2       | Power Double Lock Vertical Header Wire-to-Board Connector Kit                      |
| 2110837-3       | Power Double Lock Free-Hanging Wire-to-Wire Connector Kit                          |
| 2110837-4       | Power Double Lock Wire-to-Wire and Wire-to-Board Connector Kit                     |
| 2110837-5       | 6.5 mm Power Double Lock Wire-to-Wire and Wire-to-Board Connector Kit              |

**Note:** Design kits are designed and assembled by Waldom Electronics and are available for purchase through your local distributor.

Positive mounting achieved with Double Lock mechanism.



1) Contact is partially-mounted.



2) Double Lock Plate is set.



3) Contact is fully pushed in as Double Lock Plate is pressed.

## Questions that will help you better select the product that you need:

### What are the current and voltage requirements for your application?


The power double lock connector system has a maximum current rating of 14 Amps per line and is rated for 300 Volts AC/DC wire-to-wire and 50 Volts AC/DC wire-to-board.

### What are the wire type and size requirements?

The power double lock connector system is approved for use with 26-16 AWG wire with an insulation range between 1.3 mm and 3.1 mm.

### What are the number of positions and available space?

The power double lock connector system is available in select positions (1-12) on four contact centerline spacings; 3.9 mm, 6.5 mm, 7.92 mm and 13.0 mm. The overall mated length of the free-hanging system is 38.7 mm and the maximum height of the wire-to-board system is 25.5 mm.



### What are the operating temperature requirements?

The power double lock connector system has a maximum operating temperature of 105°C. For more information regarding operating temperatures refer to Product Specification 108-5410.

### Is contact back-out a concern? Do you need confirmation that the contacts are seated?

The power double lock connector system offers an optional double lock

plate. The purpose of the double lock plate is two-fold: 1) allows contacts to be fully seated in the housing and 2) it helps prevent the possibility of contact disengagement when wires are exposed to external pressure.

### Do you need to differentiate this connector from other connectors in the application?

The power double lock connector system offers multiple options of colored housings for ease of connector identification during manufacturing and assembly.

### What is the benefit of choosing a header with a polarization peg (boss)?

The power double lock connector system offers headers with or without polarization pegs. The purpose of this feature is to polarize the headers to the PCB so the header can not be placed on the PCB in the wrong orientation. For more information regarding PCB layout please refer to the header product drawing.

### What is the benefit of choosing a high force contact?

The power double lock connector system offers high force contacts for use in applications where vibration is prominent. It is important to note that the high force contacts increase the amount of mating force. Refer to Product Specification 108-5410 for more information.

### What is the benefit of choosing Lock Type II or Lock Type B (non-standard) latch?

- Lock Type II is offered on the 3.96 mm plugs allowing for easier unmating (more finger room to depress the latch).
- Lock Type B is offered on the 6.5 mm plugs providing a slightly lower profile and can be used when the application will not have to be unmated often.

## FOR MORE INFORMATION

### TE Technical Support Center

|                   |                       |
|-------------------|-----------------------|
| USA:              | +1 (800) 522-6752     |
| Canada:           | +1 (905) 475-6222     |
| Mexico:           | +52 (0) 55-1106-0800  |
| Latin/S. America: | +54 (0) 11-4733-2200  |
| Germany:          | +49 (0) 6251-133-1999 |
| UK:               | +44 (0) 800-267666    |
| France:           | +33 (0) 1-3420-8686   |
| Netherlands:      | +31 (0) 73-6246-999   |
| China:            | +86 (0) 400-820-6015  |

Part numbers in this brochure are RoHS Compliant\*, unless marked otherwise.

\*as defined [www.te.com/leadfree](http://www.te.com/leadfree)

## te.com

© 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company. All Rights Reserved.

1773458-5 CIS LUG FP 1M 03/2011

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

