Data Sheet



Coaxial PCB Connector 82_MMCX-S50-0-55/119_O

Description

Straight PCB jack

Interface Standards
SUHNER-MMCX



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 6 \ \text{GHz} \end{array}$

Mechanical Data

Board mounting type surface mount Weight 0.0002 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -40 °C to 90 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Gold Plating
Outer contact	Brass	Gold Plating
Body	LCP (Liquid crystal polymer)	

Related Documents

Outline drawing DOU-00080629

Mounting hole DOU-00012840

Ordering Information

Tape and Reel package 82_MMCX-S50-0-55/119_OM

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.