

CPH6424


Continued from preceding page.

Parameter	Symbol	Conditions	Ratings			Unit
	Symbol		min	typ	max] UIIII
Input Capacitance	Ciss	V _{DS} =20V, f=1MHz		266		pF
Output Capacitance	Coss	V _{DS} =20V, f=1MHz		54		pF
Reverse Transfer Capacitance	Crss	V _{DS} =20V, f=1MHz		34		pF
Turn-ON Delay Time	t _d (on)	See specified Test Circuit.		8		ns
Rise Time	t _r	See specified Test Circuit.		8		ns
Turn-OFF Delay Time	t _d (off)	See specified Test Circuit.		33		ns
Fall Time	tf	See specified Test Circuit.		30		ns
Total Gate Charge	Qg	V _{DS} =30V, V _{GS} =10V, I _D =3A		7.8		nC
Gate-to-Source Charge	Qgs	V _{DS} =30V, V _{GS} =10V, I _D =3A		2.4		nC
Gate-to-Drain "Miller" Charge	Qgd	V _{DS} =30V, V _{GS} =10V, I _D =3A		1.7		nC
Diode Forward Voltage	V _{SD}	I _S =3A, V _{GS} =0		0.84	1.2	V

Switching Time Test Circuit







CPH6424

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. SCILLC strives to supply high-quality high-reliability products and recommends adopting safety measures when designing equipment to avoid accidents or malfunctions. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals," must be validated for each customer application by customer's technical experts. SCILLC shall not be held liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affil liates, and distributors harmless against all claims, costs, dam

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email: orderlit@onsemi.com

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA **Phone**: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada N. American Technical Support: 800-282-9855 Toll Free USA/Canada.

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910

Japan Customer Focus Center Phone: 81-3-5773-3850 ON Semiconductor Website:www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative