- 1. T(*)F and T(*)FM Cord Plug With On-Off Switch
- 2. D(*)M, D(*)F and D(*)FD Receptacles

click here to download a schematic drawing

(you will need to have Adobe Acrobat installed on your system to do this)



T(*)F and T(*)FM Cord Plug With On-Off Switch

T(*)**F** Straight female cord plug with DPDT (2-C) locking on-off switch; standard latchlock.

T(*)FM Straight female cord plug with SPDT (1-C) momentary on-off switch; standard latchlock.

Slide switches rated 500 mA, 125V (AC or DC). Mounting screws are supplied.

Part Number *	Part Number	Insert Contacts	
T3F	¤T3FL	3	
¤T3FM	¤T3FLM	3	
¤T4F	¤T4FL	4	
¤T4FM	¤T4FLM	4	
¤T5F	¤T5FL	5	
¤T5FM	¤T5FLM	5	
¤T6F	¤T6FL	6	
¤T6FM	¤T6FLM	6	
¤T7F	-	7	
¤T7FM	-	7	

^{*} Number of insert contact or pins must be specified to complete Part Number. ¤Available on special order only; contact Switchcraft for price and delivery.

D(*)M, D(*)F and D(*)FD Receptacles

Studio quality black and gold Q-G ® receptacle with black housing and gold contacts is

designed for low/stable contact resistance and withstands corrosion where highest quality is required for recording and broadcast studio equipment, consoles, and other applications.

D(*)M SERIES - Male receptacle for panel or chassis mounting. Special rectangular flange permits close spacing on crowded panels, has two .136 inch (3.45mm) diameter countersunk holes for #5-40 flat head mounting screws (not supplied). Mounts from front of panel or chassis in .766 inch (19.45) diameter hole. Satin nickel finish (Series D*M) or black finish (Series D*MB, or D*MBAU).

D(*)F SERIES - Female receptacle for panel or chassis mounting. Flange has two .136-inch (3.45 mm) diameter countersunk holes for #5-40 flat head mounting screws (not supplied). Mounts from front of panel or chassis in .953-inch (24.21 mm) diameter hole. Series D(*)F has standard latchlock; Series D(*)FD has FAS-DISCONNECT detent. Satin nickel finish (Series D*F and D*FD) and "Black-Velvet" finish (Series D*FBAU).

Nickel Finish	Black Finish		Detent	QGP Series1	Pins
	Silver	Gold	Detent	QGI Sellesi	1 1115
D3M	D3MB	D3MBAU	-	QGP363	3
D4M	D4MB	D4MBAU	-	-	4
D5M	D5MB	D5MBAU	-	-	5
D6M	D6MB	D6MBAU	-	-	6
D7M	D7MB	D7MBAU	-	-	7
D3F	D3FB	D3FBAU	D3FD	QGP362	3
D4F	D4FB	D4FBAU	¤D3FDB	-	4
D5F	D5FB	D5FBAU	-	-	5
D6F	D6FB	D6FBAU	¤D6FDB	-	6
D7F	D7FB	D7FBAU	-	-	7

^{*} Number of insert contact or pins must be specified to complete Part Number. ¤Available on special order only; contact Switchcraft for price and delivery. 1 Non-reflective gray finish, gold-plated pins.

Previous Page | Return to Index | Next Page

To search a category please click on the corresponding icon:



| Connectors | Jacks and Plugs | | Patch Panels, Patch Kits & Jackfields | Cable Assemblies and Patch Cords | Switches |

All products shown are covered by Switchcraft's limited lifetime warranty.

| <u>Switchcraft home</u> |

<u>About Us</u> | <u>Products</u> | <u>What's New</u> | <u>Search</u> | <u>Contact Us</u>