

5555165-2 Product Details

 Share Print Email



5555165-2

TE Internal Number: 5555165-2

 Active

 View 3D PDF

PCB Mounted Jacks - Single Port, Multi-port and Stacked

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ14

[View all Features](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information	
Product Drawings: MODULAR JACK ASSEMBLY, 6 POSITION, LOW PROFILE, RIGH... (PDF, English) Catalog Pages/Data Sheets: 1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT (PDF, English) Product Specifications: Modular Plugs, Thru-Hole and Surface Mount Jacks, Da... (PDF, English) Application Specifications: Modular Jacks (PDF, English) Instruction Sheets: - None Available CAD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version E) 3D Model (IGES, Version E) 3D Model (STEP, Version E)	Additional Information: Product Line Information Related Products: Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Product Type = Connector - Jack Type = RJ14 - PCB Mounting Orientation = Side Entry (Right Angle) - PCB Mount Style = Through Hole - Termination Method to PC Board = Solder - Performance Category = Cat 3 - LED = Without - Grounding Options = Without - Panel Stops = Without - Keyed = No - Profile = Low - Color = Black - Latch Style = Standard Mechanical Attachment: Panel Mount Retention = With - Flanged = No Electrical Characteristics: Shielded = No Termination Features: Solder Tail Contact Plating = Tin over Nickel Dimensions: Height (mm [in]) = 12.70 [0.500] PCB Tail Length (mm [in]) = 3.80 [0.150] PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]	Body Features: Inverted Jack Face = No Contact Features: Contact Plating, Mating Area, Material = Gold (50) - Contact Base Material = Phosphor Bronze Housing Features: - Housing Material = PBT - GF - UL Flammability Rating = UL 94V-0 Configuration Features: - Preloaded = Yes - Port Configuration = Single Jack Configuration = 1 x 1 Number of Positions = 6 - Number of Contacts Loaded = 4 Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C - RoHS/ELV Compliance History = Always was RoHS compliant Packaging Features: - Packaging Method = Tray Product Availability: - Region = Asia, North America Other: - Brand = AMP

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed



© 2013 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved |  Provide Website Feedback

Downloaded from [Arrow.com](#)