



Maxim > Products > Automotive > MAX2170, MAX2171
Maxim > Products > Wireless and RF > MAX2170, MAX2171

MAX2170, MAX2171

Direct-Conversion to Low-IF Tuners for Digital Audio Broadcast

Highest Performance, Most Integrated Triple-Band Receivers for T-DMB/DAB/FM Digital Radios

Overview

Technical Documents

Ordering Info

Related Products

User Comments (0)

All

Status

Active: Data sheet on request only

Data Sheet

[Request Full Data Sheet](#)

Description

The MAX2170/MAX2171 direct-conversion to low-IF tuners are designed for Digital Audio Broadcast (DAB) and Terrestrial Digital Multimedia Broadcast (T-DMB) applications, covering an input frequency range of 168MHz to 240MHz (VHF-III), 1452MHz to 1492MHz (L-Band), and also 87MHz to 108MHz (FM). The MAX2170/MAX2171 achieve a high level of component integration, allowing low-power, tuner-on-board designs. The direct-conversion to low-IF architecture eliminates the need for an IF-SAW filter while providing a balanced 2.048MHz center frequency baseband output to the demodulator.

The MAX2170 provides a buffered reference clock at the crystal frequency, while the MAX2171 outputs a reference at 1/3rd of the crystal frequency. A sigma-delta fractional-N synthesizer is incorporated to optimize both close-in and wideband phase noise performances for OFDM applications where sensitivity to both 1kHz phase noise and wideband phase noise related to strong adjacents can be a problem.

The MAX2170/MAX2171 are available in a 40-pin thin QFN package (6mm x 6mm) with an exposed paddle. Electrical performance is guaranteed over the extended -40°C to +85°C temperature range.

An evaluation kit is available: [MAX2170EVKIT](#)

Key Features

- +2.7V to +3.5V Supply Voltage Range
- Low-IF Output Eliminates IF-SAW Filter
- Integrated Low-IF Bandpass Filter
- Sigma-Delta Fractional-N Synthesizer
- +45dB Digital ACPR
- 3.5dB Typical Noise Figure for VHF-III (Includes On-Chip Tracking Filter)
- 3.1dB Typical Noise Figure for L-Band
- VHF-III Sensitivity of -100dBm
- L-Band Sensitivity of -99dBm
- Baseband Overload Detector Controls RF AGC

Applications/Uses

- Fixed and Mobile Digital Audio Broadcast (DAB)
- Terrestrial Digital Multimedia Broadcast (T-DMB)

Key Specifications:

Digital Radio Receivers													
Part Number	Ref. Clock Freq. (MHz)	IF f _{OUT} (MHz)	Noise Figure (dB)	V _{SUPPLY} (V)	I _{SUPPLY} (mA)	Applications	Solutions	Band/ Freq. (MHz)	Features	Footprint (mm x mm)	Package/Pins	Smallest Available Pckg. (mm ²)	Industry Qualified
			typ									max w/pins	
MAX2170	24.576	2.048	2.9	2.7 to 3.5	62	DAB and T-DMB Home and Automotive Radios	Automotive Consumer	168 to 240 and 1452 to 1492	3.1dB NF in L-band 45dB ACPR On-Chip VHF Tracking Filter	6.0 x 6.0	TQFN/40	37.2	Automotive - AECQ100 Automotive - General
MAX2171			3					87 to 108, 168 to 240 and 1452 to 1492			TQFN/40		Automotive - General

[See All Digital Radio Receivers \(5\)](#)

Pricing Notes:

This pricing is BUDGETARY, for comparing similar parts. Prices are in U.S. dollars and subject to change. Quantity pricing may vary substantially and international prices may differ due to local duties, taxes, fees, and exchange rates. For volume-specific prices and delivery, please see the [price and availability](#) page or contact an authorized distributor.

Application Notes

Application Note 3908
Reference Design 4154
Application Note 4271
Tutorial 5100

[MAX2170/MAX2171 DAB/T-DMB Digital Radio Tuner](#)
[MAX2170/MAX2171 DAB/T-DMB Reference Design](#)
[Automotive Infotainment Goes Mainstream: High-Integration Solutions Enable Value-Added Features](#)
[General Layout Guidelines for RF and Mixed-Signal PCBs](#)

Product Guides

[Wireless \(PDF\)](#)

Reliability Reports

Reliability Report:
Show FIT data for: [MAX2170](#) [Go](#)

Request Reliability Report for: [MAX2171](#) [Go](#)

Software/Models

none

Ordering Information

Filters: Part Number: Package: [Any](#) Temperature: [Any](#) ☐ Tape and Reel ☐ Sample [Go](#)

Part Number	Free Sample	Buy	Status	Package: TYPE PINS FOOTPRINT DRAWING CODE/VAR *	Temp	RoHS/Lead-Free? Materials Analysis
MAX2170E/WGB1		Buy	Active: Data sheet on request only	WAFER; Land Pattern: Not Available	-40°C to +85°C	See data sheet
MAX2170ETL+	Sample	Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2170ETL+B4B		Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2170ETL+T		Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2170ETL/V+	Sample	Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2170ETL/V+T		Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2171ETL+	Sample	Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2171ETL+T		Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2171ETL/V+		Buy	Active: Data sheet on request only	TQFN;40 pin;37.2 mm ² Outline Drawing:21-0141 (PDF) Land Pattern: 90-0053 (PDF) Use pkgcode/variation: T4066+2*	-40°C to +85°C	RoHS/Lead-Free: Lead Free Materials Analysis
MAX2171ETL/V+T		Buy	Active: Data sheet on request only	QFN; Land Pattern: Not Available	-40°C to +85°C	See data sheet

Notes:

- Other options and links for purchasing parts are listed at: <http://www.maxim-ic.com/sales>.
- Didn't Find What You Need? Ask our applications engineers. Expert assistance in finding parts, usually within one business day.
- Part number suffixes: T or T&R = tape and reel; + = RoHS/lead-free; # = RoHS/lead-exempt; -D = drypack; -U/+U on DS parts = cut tape. More: See Full Data Sheet or Maxim Product Naming Conventions.
- * Some packages have variations, listed on the drawing. "PkgCode/Variation" tells which variation the product uses. Note that "+", "#", "-" in the part number suffix describes RoHS status. Package drawings may show a different suffix character.

Similar Products by Function

[See All Digital Radio Receivers \(5 Products\)](#)

Similar Products by Application

[Automotive: Head Unit > Digital Audio Broadcast \(DAB\)](#)
[Automotive: TV-Tuner Systems > Tuner](#)
[Broadcast TV and Radio > Digital Terrestrial Radio](#)
[Broadcast TV and Radio > Mobile TV](#)
[Broadcast TV and Radio > Receive System ICs](#)

Evaluation Kits

[MAX2170EVKIT](#) [MAX2170 Evaluation Kit](#)

Products with Similar Part Numbers

[MAX2170EVKIT](#) [MAX2170 Evaluation Kit](#)

More Information

New Product Press Release [2008-06-04] [2007-05-10]

Your Comments

Login or register to post a comment.

Didn't Find What You Need?

[Next Day Product Selection Assistance from Applications Engineers](#)
[Parametric Search](#)
[Applications Help](#)

Information Index

Overview	Technical Documents	Ordering Info	Related Products
Description Key Features Applications/Uses Key Specifications Diagram Notes and Comments	Data Sheet Application Notes Evaluation Kits Product Guides Reliability Reports Software/Models	Price and Availability Samples Buy Online Package Information Lead-Free Information	Similar Products by Function Similar Products by Application Evaluation Kits Products with Similar Part Numbers Products Used With This

Document Ref.: 19-0699 Rev 3; 2010-03-26
This page last modified: 2010-03-26