

NOT RECOMMENDED FOR NEW DESIGNS USE PDS3100



Ordering Information (Note 8)

Device	Packaging	Shipping
MBRM3100-13-F	POWERMITE 3	5000/Tape & Reel

Notes: 3. TA = TSOLDERING POINT, R JS = 3.5 C/W, R SA = 0 C/W.

- Device mounted on GETEK substrate, 2"x2", 2 oz. copper, double-sided, cathode pad dimensions 0.75" x 1.0", anode pad dimensions 0.25" x 1.0". R JA in range of 30-35°C/W.
- Device mounted on FR-4 substrate, 2"x2", 2 oz. copper, single-sided, pad layout as per Diodes Inc. suggested pad layout document AP02001 which can be found on our website at http://www.diodes.com/datasheets/ap02001.pdf. R JA in range of 115-125°C/W.
- 6. Maximum power dissipation when the device is mounted in accordance to the conditions described in Note 4.
- 7. Maximum power dissipation when the device is mounted in accordance to the conditions described in Note 3.
- 8. For Packaging Details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



MBRM3100 = Product type marking code D11 = Manufacturers' code marking YYWW = Date code marking YY = Last digit of year ex: 02 for 2002 WW = Week code 01 to 52 (K) = Factory Designator

NOT RECOMMENDED FOR NEW DESIGNS USE PDS3100

POWERMITE is a registered trademark of Microsemi Corporation.



IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.