

Quick Links

Cross reference

RoHS/LF P/N Search

Industry Standards

Alphabetical List

Documentation

3D model search

Customer drawing search



Multi Selection Search

Search by category

Start > Search=10127815-04LF* > 10127815-04LF

10127815-04LF

10127815-04LF - Minitex® Pwr4.2 : Minitex® Pwr4.2
Receptacle Housing, Dual row, 4 positions, Glow Wire
Compatible



Customer
drawing



Product Environmental
Compliance Report

ACTIVE 48

RoHS
Compliant

Distributor Stock

CORE
RANGE

Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Specifications	
Download document	
General Dimensional Electrical Mechanical Physical Approvals / Certifications Other Features	
General	
Number of contacts	4
Series	10127815
Dimensional	
Pitch	4.2
Electrical	
Withstanding Voltage	1500 Vac, No breakdown. Current leakage < 5mA
Current rating	UP to 9 Amps
Resistance (Contact)	10 milliohm max.
Resistance (Insulation)	1000M ΩMin
Voltage rating	600V
Mechanical	
Durability (Mating cycles)	30 Cycles
Insertion force	14.7N max.
Withdrawal Force	1 N min.
Glow Wire Compatible	Yes
Physical	
Color (Housing)	Natural
Material (Housing)	Nylon 66
Temperature (Range)	-40°C to +105°C
Approvals / Certifications	
Approvals / Certifications	UL Approved
UL File Number	ML E467317
Other Features	
Packaging (Type)	PE Bag

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.