




	 JPN_SS_108-60025-1_B.tif Japanese  JPN_SS_108-60018-1_D.pdf Japanese  JPN_SS_108-60018-1_D.tif Japanese Product Specification  ENG_SS_108-60018_G_108-60018_G.pdf English
Product Environmental Compliance	MD_292231-3_012320171017_dmtec  ENG_PC_MD_292231-3_F(493828).xlsx English MD_292231-3_012320171017_dmtec  ENG_PC_MD_292231-3_F(710831).xml English
Agency Approvals	UL  ENG_AAD_UL_E28476_19990118_D.pdf English
Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.	
Product Type Features	PCB Connector Assembly Type : PCB Mount Header Connector System : Wire-to-Board Header Type : Shrouded Sealable : No Connector & Contact Terminates To : Printed Circuit Board
Configuration Features	PCB Mount Orientation : Vertical Number of Positions : 3 Number of Rows : 1
Electrical Characteristics	Operating Voltage (VDC): 50 Operating Voltage (VAC): 50
Contact Features	Contact Base Material : Brass PCB Contact Termination Area Plating Material : Tin Contact Shape & Form : Square Contact Retention Within Housing : Without Contact Mating Area Plating Material : Tin Contact Mating Area Plating Material Finish : Matte Contact Mating Area Plating Material Thickness : 1 μm [39.37 μin] Contact Type : Pin Contact Current Rating (Max) (A): 2 PCB Contact Termination Area Plating Material Thickness : 1 μm [39.37 μin] Mating Post Length : 2.4 mm [.095 in] Contact Layout : Staggered Contact Design : Square
Termination Features	Termination Method to Printed Circuit Board : Surface Mount

Mechanical Attachment	PCB Mount Alignment : Without Mating Retention : With PCB Mount Retention : Without Connector Mounting Type : Board Mount
Housing Features	Centerline (Pitch) : 1.5 mm [.059 in] Housing Color : Natural Housing Material : Nylon
Dimensions	Wire Size (AWG): 28 – 24 PCB Thickness (Recommended) : .8 mm [.031 in] Connector Width : 4.7 mm [.185 in] Connector Height : 6.9 mm [.272 in] Connector Length : 7 mm [.2756 in]
Usage Conditions	Operating Temperature Range : -22 – 221 °C [-30 – 105 °F]
Operation/Application	Assembly Process Feature : Pick and Place Cover Circuit Application : Signal
Industry Standards	UL Flammability Rating : UL 94V-0 Agency/Standard : UL Agency/Standard Number : CSA, UL UL File Number : E28476 CSA File Number : LR 7189-133
Packaging Features	Packaging Quantity : 500 Packaging Method : Tape, Box
	



Wire-to-Board
Connector Contacts
(4)



Wire-to-Board
Connector Housings
(182)



Wire-to-Board
Headers &
Receptacles (387)

[ABOUT TE CONNECTIVITY](#)

[FOR PARTNERS](#)

[SUPPORT](#)

[CALL US](#)

[LIVE CHAT](#)

[UNITED STATES \(EN\)](#)