

CMOS Analog Switches

ABSOLUTE MAXIMUM RATINGS

Voltages Referenced to V^-
 V^+ (DG304-DG307) 36V
 V^+ (DG304A-DG307A) 44V
GND 25V
Digital Inputs, V_S , V_D (Note 1) -4V to ($V^+ + 4V$) or
30mA, whichever occurs first.
Current, Any Terminal Except S or D 30mA
Continuous Current, S or D 30mA
(Pulsed at 1msec, 10% duty cycle max) 100mA
Storage Temperature (A & B Suffix) -65°C to 150°C
(C Suffix) -65°C to 125°C

Operating Temperature (A Suffix) -55°C to 125°C
(B Suffix) -25°C to 85°C
(C Suffix) 0°C to 70°C
Lead Temperature (Soldering 10 sec.) +300°C
Power Dissipation*
Cerdip (K) (Derate 11mW/°C above 75°C) 825mW
Plastic DIP (J) (Derate 6.5mW/°C above 25°C) .. 470mW
Metal Can (A) (Derate 6mW/°C above 75°C) 450mW

* Device mounted with all leads soldered or welded to PC board.

Stresses listed under "Absolute Maximum Ratings" may be applied (one at a time) to devices without resulting in permanent damage. These are stress ratings only, and functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum ratings conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS ($V^+ = +15V$, $V^- = -15V$, GND = 0V, $T_A = 25^\circ C$, unless otherwise indicated)

	PARAMETER	SYMBOL	TEST CONDITIONS	DG304-DG307A DG304A-DG307AA			DG304-DG307B/C DG304A-DG307AB/C			UNITS
				MIN	TYP	MAX	MIN	TYP	MAX	
				(Note 2)	(Note 3)		(Note 2)	(Note 3)		
SWITCH	Analog Signal Range	V_{ANALOG}	$I_S = 10mA$, $V_{in} = 3.5V$ or $11.0V$	-15		15	-15		15	V
	Drain-Source ON Resistance	$r_{DS(on)}$	$I_S = -10mA$, $V_D = 10V$		30	50		30	50	Ω
			$I_S = 10mA$, $V_D = -10V$		30	50		30	50	
	Source OFF Leakage Current	$I_{S(off)}$	$V_{in} = 3.5V$ or $V_{in} = 11.0V$		0.1	1		0.1	5	nA
			$V_S = 14V$, $V_D = -14V$	-1	-0.1		-5	-0.1		
	Drain OFF Leakage Current	$I_{D(off)}$	$V_S = -14V$, $V_D = 14V$		0.1	1		0.1	5	
			$V_S = 14V$, $V_D = -14V$	-1	-0.1		-5	-0.1		
INPUT	Drain ON Leakage Current	$I_{D(on)}$	$V_D = V_S = 14V$		0.1	1		0.1	5	
			$V_D = V_S = -14V$	-2	-0.1		-5	-0.1		
	Input Current/Voltage High	I_{INH}	$V_{in} = 5.0V$	-1	-0.001		-1	-0.001		μA
			$V_{in} = 15V$		0.001	1		0.001	1	
DYNAMIC	Input Current/Voltage Low	I_{INL}	$V_{in} = 0V$	-1	-0.001		-1	-0.001		μA
	Turn-ON Time	t_{on}	See Switching Time Test Circuit		110	250		110	250	ns
	Turn-OFF Time	t_{off}			70	150		70	150	
	Break-Before-Make Interval	$t_{on}-t_{off}$	See Break-Before-Make Time Test Circuit DG305(A)/DG307(A) Only		50			50		
	Charge Injection	Q	$C_L = 10nF$, $R_{gen} = 0\Omega$, $V_{gen} = 0V$		12			12		pC
	Source OFF Capacitance	$C_{S(off)}$	$f = 1MHz$, $V_{in} = 3.5V$ or $V_{in} = 11.0V$		14			14		pF
	Drain OFF Capacitance	$C_{D(off)}$	$V_S = 0V$							
			$V_D = 0V$		14			14		
	Channel-ON Capacitance	$C_{D(on)} + C_{S(on)}$	$V_S = V_D = 0V$		40			40		
	Input Capacitance	C_{in}	$f = 1MHz$		6			6		
			$V_{in} = 0V$		7			7		
			$V_{in} = 15V$							
	Off Isolation (Note 4)		$V_{in} = 0V$, $R_L = 1k\Omega$		62			62		dB
	Crosstalk (Channel to Channel)		$V_S = 1 V_{RMS}$, $f = 500kHz$		74			74		

(See Notes next page).

CMOS Analog Switches

ELECTRICAL CHARACTERISTICS (Continued)

(V⁺ = +15V, V⁻ = -15V, GND = 0V, T_A = 25°C, unless otherwise indicated)

	PARAMETER	SYMBOL	TEST CONDITIONS	DG304-DG307A DG304A-DG307AA			DG304-DG307B/C DG304A-DG307AB/C			UNITS
				MIN	TYP	MAX	MIN	TYP	MAX	
SUPPLY	Positive Supply Current	I ⁺	V _{in} = 15.0V (All Inputs)	0.001 10			0.001 10			μA
	Negative Supply Current	I ⁻		-10 -0.001			-10 -0.001			
	Positive Supply Current	I ⁺	V _{in} = 0V (All Inputs)	0.001 10			0.001 10			
	Negative Supply Current	I ⁻		-10 -0.001			-10 -0.001			

ELECTRICAL CHARACTERISTICS (Over Temperature)

(V⁺ = +15V, GND = 0V, T_A = Over Temperature Range, unless otherwise noted)

	PARAMETER	SYMBOL	TEST CONDITIONS		DG304-DG307A DG304A-DG307AA		DG304-DG307B/C DG304A-DG307AB/C		UNITS	
					MIN (Note 2)	TYP (Note 3)	MAX (Note 2)	TYP (Note 3)		MAX (Note 3)
SWITCH	Analog Signal Range	V _{ANALOG}	I _S = 10mA, V _{in} = 3.5V or 11.0V		-15		15	-15		V
	Drain-Source ON Resistance	r _{DS(on)}	V _{in} = 3.5V or V _{in} = 11.0V	I _S = -10mA, V _D = 10V			75		75	Ω
		I _S = 10mA, V _D = -10V				75		75		
	Source OFF Leakage Current	I _{S(off)}		V _S = 14V, V _D = -14V			100		100	nA
		V _S = -14V, V _D = 14V		-100		-100				
	Drain OFF Leakage Current	I _{D(off)}		V _S = -14V, V _D = 14V			100		100	
		V _S = 14V, V _D = -14V		-100		-100				
		V _D = V _S = 14V				100		100		
Drain ON Leakage Current	I _{D(on)}	V _D = V _S = -14V	-200		-200					
INPUT	Input Current/ Voltage High	I _{INH}	V _{in} = 5.0V		-1		-10		μA	
			V _{in} = 15V				1			10
	Input Current/ Voltage Low	I _{INL}	V _{in} = 0V		-1		-10			
SUPPLY	Positive Supply Current	I ⁺	V _{in} = 15.0V (All Inputs)				100			μA
	Negative Supply Current	I ⁻					-100			
	Positive Supply Current	I ⁺	V _{in} = 0V (All Inputs)				100			
	Negative Supply Current	I ⁻					-100			

Note 1: Signals on S_X, D_X, or I_{NX} exceeding V⁺ or V⁻ will be clamped by internal diodes. Limit diode forward current to maximum current ratings.

Note 2: The algebraic convention whereby the most negative value is a minimum, and the most positive value is a maximum is used in this data sheet.


Note 3: Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.

Note 4: OFF isolation = $20 \log \frac{V_S}{V_D}$, V_S = input to OFF switch, V_D = Output.

MAXIM

CMOS Analog Switches

Typical Operating Characteristics



Test Circuits




Figure 1. Charge Injection Test Circuit.

CMOS Analog Switches

Test Circuits (Continued)




Figure 2. Break-Before-Make Time Test Circuit SPDT DG305(A), DG307(A).




Figure 3. Switching Time Test Circuit.

Application Information

All DG304 family switches will operate with ± 15 V power supplies. They can also be used with single ended power supplies ranging from +10V to +30V where the V^- terminal is connected to ground. In either case analog signals ranging from V^+ to V^- can be switched.

The on resistance variation with analog signal and supply voltage is shown in the Typical Operating Characteristics graphs. The temperature coefficient of R_{ON} is typically 0.5%/°C. Typical on resistance matching from channel to channel is 10%. In addition, Table 1 outlines some typical parameters for single supply operation.

Table 1. Typical Single Supply Parameters

	V* SUPPLY VOLTAGE (V* = 0V)			
	+10V	+15V	+20V	+30V
Switching Time ($R_L = 1k\Omega$)				
t_{ON}	220ns	180ns	165ns	110ns
t_{OFF}	60ns	40ns	30ns	20ns
On Resistance				
$V_{SIGNAL} = +1V$	71 Ω	51 Ω	42 Ω	31 Ω
$V_{SIGNAL} = V^*/2$	77 Ω	54 Ω	43 Ω	30 Ω
$V_{SIGNAL} = V^+$	84 Ω	63 Ω	54 Ω	43 Ω
Input Logic Levels	3.5V, 11.0V	3.5V, 11.0V	3.5V, 12.5V	3.5V, 22.0V

The charge injection test circuit is shown in Figure 1. Table 2 lists the typical injected charge for DG304 series switches with various input voltages.

Table 2. Charge Injection (± 15 V Supplies)

ANALOG INPUT	INJECTED Q
+10V	4pC
+5V	8pC
0V	12pC
-5V	8pC
-10V	5pC

CMOS Analog Switches

Ordering Information (continued)

DG304(A)/DG305(A)/DG306(A)/DG307(A)

PART	TEMP. RANGE	PACKAGE
DG304AC/D	0°C to +70°C	Dice
DG304ACJ	0°C to +70°C	14 Lead Plastic DIP
DG304ACWE	0°C to +70°C	16 Lead Wide SO
DG304ACK	0°C to +70°C	14 Lead Cerdip
DG304ABWE	-25°C to +85°C	16 Lead Wide SO
DG304ABK	-25°C to +85°C	14 Lead Cerdip
DG304ABA	-25°C to +85°C	10 Lead Metal Can
DG305C/D	0°C to +70°C	Dice
DG305CJ	0°C to +70°C	14 Lead Plastic DIP
DG305CWE	0°C to +70°C	16 Lead Wide SO
DG305CK	0°C to +70°C	14 Lead Cerdip
DG305BWE	-25°C to +85°C	16 Lead Wide SO
DG305BK	-25°C to +85°C	14 Lead Cerdip
DG305BA	-25°C to +85°C	10 Lead Metal Can
DG305AK	-55°C to +125°C	14 Lead Cerdip
DG305AA	-55°C to +125°C	10 Lead Metal Can
DG305AC/D	0°C to +70°C	Dice
DG305ACJ	0°C to +70°C	14 Lead Plastic DIP
DG305ACWE	0°C to +70°C	16 Lead Wide SO
DG305ACK	0°C to +70°C	14 Lead Cerdip
DG305ABWE	-25°C to +85°C	16 Lead Wide SO
DG305ABK	-25°C to +85°C	14 Lead Cerdip
DG305ABA	-25°C to +85°C	10 Lead Metal Can


PART	TEMP. RANGE	PACKAGE
DG306C/D	0°C to +70°C	Dice
DG306CJ	0°C to +70°C	14 Lead Plastic DIP
DG306CWE	0°C to +70°C	16 Lead Wide SO
DG306CK	0°C to +70°C	14 Lead Cerdip
DG306BWE	-25°C to +85°C	16 Lead Wide SO
DG306BK	-25°C to +85°C	14 Lead Cerdip
DG306AK	-55°C to +125°C	14 Lead Cerdip
DG306AC/D	0°C to +70°C	Dice
DG306ACJ	0°C to +70°C	14 Lead Plastic DIP
DG306ACWE	0°C to +70°C	16 Lead Wide SO
DG306ACK	0°C to +70°C	14 Lead Cerdip
DG306ABWE	-25°C to +85°C	16 Lead Wide SO
DG306ABK	-25°C to +85°C	14 Lead Cerdip
DG307C/D	0°C to +70°C	Dice
DG307CJ	0°C to +70°C	14 Lead Plastic DIP
DG307CWE	0°C to +70°C	16 Lead Wide SO
DG307CK	0°C to +70°C	14 Lead Cerdip
DG307BWE	-25°C to +85°C	16 Lead Wide SO
DG307BK	-25°C to +85°C	14 Lead Cerdip
DG307AK	-55°C to +125°C	14 Lead Cerdip
DG307AC/D	0°C to +70°C	Dice
DG307ACJ	0°C to +70°C	14 Lead Plastic DIP
DG307ACWE	0°C to +70°C	16 Lead Wide SO
DG307ACK	0°C to +70°C	14 Lead Cerdip
DG307ABWE	-25°C to +85°C	16 Lead Wide SO
DG307ABK	-25°C to +85°C	14 Lead Cerdip

CMOS Analog Switches

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to www.maxim-ic.com/packages.)


MAX304(A)/DG305(A)/DG306(A)/DG307(A)



CMOS Analog Switches

Package Information (continued)


(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to www.maxim-ic.com/packages.)



CMOS Analog Switches

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to www.maxim-ic.com/packages.)



MAX304(A)/DG305(A)/DG306(A)/DG307(A)

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 9

© 2004 Maxim Integrated Products Printed USA **MAXIM** is a registered trademark of Maxim Integrated Products.