

## Absolute Maximum Ratings [1]


Parameter	AlGaAs Red HLCF-J100	HER HDSP-4830	Yellow HDSP-4840	Green HDSP-4850
Average Power Dissipation per LED ( $T_A = 25^\circ\text{C}$ )	37 mW	87 mW	50 mW	105 mW
Peak Forward Current per LED	45 mA <sup>[3]</sup>	90 mA <sup>[4]</sup>	60 mA <sup>[4]</sup>	90 mA <sup>[4]</sup>
DC Forward Current per LED	15 mA <sup>[5]</sup>	30 mA <sup>[6]</sup>	20 mA <sup>[6]</sup>	30 mA <sup>[6]</sup>
Operating Temperature Range	-20°C to +100°C	-40°C to +85°C	-40°C to +85°C	-20°C to +85°C
Storage Temperature Range	-55°C to +100°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Reverse Voltage* per LED	5.0 V	3.0 V	3.0 V	3.0 V
Lead Solder Dipping Temperature (1.59 mm (1/16 inch) below seating plane) [7]	260°C for 5 seconds [8]			
Wave Soldering Temperature (at 2 mm distance from the body)	250°C for 3 seconds			

\* reverse voltage is for LED testing purposes and is not recommended to be used as an application condition.

Notes:

1. Absolute maximum ratings for HER, Yellow, and Green elements of the multicolor arrays are identical to the HDSP-4830/4840/4850 maximum ratings.
2. See Figure 1 to establish pulsed operating conditions. Maximum pulse width is 1.5 ms.
3. See Figure 2 to establish pulsed operating conditions. Maximum pulse width is 1.5 ms.
4. See Figure 8 to establish pulsed operating conditions. Maximum pulse width is 2 ms.
5. Derate maximum DC current for Red above  $T_A = 62^\circ\text{C}$  at 0.79 mA/°C, and AlGaAs Red above  $T_A = 91^\circ\text{C}$  at 0.8 mA/°C. See Figure 3.
6. Derate maximum DC current for HER above  $T_A = 48^\circ\text{C}$  at 0.58 mA/°C, Yellow above  $T_A = 70^\circ\text{C}$  at 0.66 mA/°C, and Green above  $T_A = 37^\circ\text{C}$  at 0.48 mA/°C. See Figure 9.
7. Clean only in water, isopropanol, ethanol, Freon TF or TE (or equivalent), or Genesolve DI-15 (or equivalent).
8. Maximum tolerable component side temperature is 134°C during solder process.

## Internal Circuit Diagram



Pin	Function	Pin	Function
1	Anode a	11	Cathode j
2	Anode b	12	Cathode i
3	Anode c	13	Cathode h
4	Anode d	14	Cathode g
5	Anode e	15	Cathode f
6	Anode f	16	Cathode e
7	Anode g	17	Cathode d
8	Anode h	18	Cathode c
9	Anode i	19	Cathode b
10	Anode j	20	Cathode a

## Multicolor Array Segment Colors

Segment	HDSP-4832 Segment Color	HDSP-4836 Segment Color
a	HER	HER
b	HER	HER
c	HER	Yellow
d	Yellow	Yellow
e	Yellow	Green
f	Yellow	Green
g	Yellow	Yellow
h	Green	Yellow
i	Green	HER
j	Green	HER

## Electrical/Optical Characteristics at $T_A = 25^\circ\text{C}$ <sup>[4]</sup>

### AlGaAs Red HLCP-J100

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity per LED (Unit Average) <sup>[1]</sup>	$I_V$	600	1000		$\mu\text{cd}$	$I_F = 1 \text{ mA}$
			5200			$I_F = 20 \text{ mA Pk};$ 1 of 4 Duty Factor
Peak Wavelength	$\lambda_{\text{PEAK}}$		645		nm	
Dominant Wavelength <sup>[2]</sup>	$\lambda_d$		637		nm	
Forward Voltage per LED	$V_F$		1.6		V	$I_F = 1 \text{ mA}$
			1.8	2.2		$I_F = 20 \text{ mA}$
Reverse Voltage per LED <sup>[5]</sup>	$V_R$	5	1.5		V	$I_R = 100 \mu\text{A}$
Temperature Coefficient $V_F$ per LED	$\Delta V_F / ^\circ\text{C}$		-2.0		mV/ $^\circ\text{C}$	
Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		300		$^\circ\text{C/W/LED}$	

### High Efficiency Red HDSP-4830

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity per LED (Unit Average) <sup>[1,4]</sup>	$I_V$	900	3500		$\mu\text{cd}$	$I_F = 10 \text{ mA}$
Peak Wavelength	$\lambda_{\text{PEAK}}$		635		nm	
Dominant Wavelength <sup>[2]</sup>	$\lambda_d$		626		nm	
Forward Voltage per LED	$V_F$		2.1	2.5	V	$I_F = 20 \text{ mA}$
Reverse Voltage per LED <sup>[5]</sup>	$V_R$	3	30		V	$I_R = 100 \mu\text{A}$
Temperature Coefficient $V_F$ per LED	$\Delta V_F / ^\circ\text{C}$		-2.0		mV/ $^\circ\text{C}$	
Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		300		$^\circ\text{C/W/LED}$	

### Yellow HDSP-4840

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity per LED (Unit Average) <sup>[1,4]</sup>	$I_V$	600	1900		$\mu\text{cd}$	$I_F = 10 \text{ mA}$
Peak Wavelength	$\lambda_{\text{PEAK}}$		583		nm	
Dominant Wavelength <sup>[2,3]</sup>	$\lambda_d$	581	585	592	nm	
Forward Voltage per LED	$V_F$		2.2	2.5	V	$I_F = 20 \text{ mA}$
Reverse Voltage per LED <sup>[5]</sup>	$V_R$	3	40		V	$I_R = 100 \mu\text{A}$
Temperature Coefficient $V_F$ per LED	$\Delta V_F / ^\circ\text{C}$		-2.0		mV/ $^\circ\text{C}$	
Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		300		$^\circ\text{C/W/LED}$	

### Green HDSP-4850

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity per LED (Unit Average) <sup>[1,4]</sup>	$I_V$	600	1900		$\mu\text{cd}$	$I_F = 10 \text{ mA}$
Peak Wavelength	$\lambda_{\text{PEAK}}$		566		nm	
Dominant Wavelength <sup>[2,3]</sup>	$\lambda_d$		571	577	nm	
Forward Voltage per LED	$V_F$		2.1	2.5	V	$I_F = 20 \text{ mA}$
Reverse Voltage per LED <sup>[5]</sup>	$V_R$	3	50		V	$I_R = 100 \mu\text{A}$
Temperature Coefficient $V_F$ per LED	$\Delta V_F / ^\circ\text{C}$		-2.0		mV/ $^\circ\text{C}$	
Thermal Resistance LED Junction-to-Pin	$R\theta_{J-PIN}$		300		$^\circ\text{C/W/LED}$	

Notes:

1. The bar graph arrays are categorized for luminous intensity. The category is designated by a letter located on the side of the package.
2. The dominant wavelength,  $\lambda_d$ , is derived from the CIE chromaticity diagram and is that single wavelength which defines the color of the device.
3. The HDSP-4832/-4836/-4840/-4850 bar graph arrays are categorized by dominant wavelength with the category designated by a number adjacent to the intensity category letter. Only the yellow elements of the HDSP-4832/-4836 are categorized for color.
4. Electrical/optical characteristics of the High-Efficiency Red elements of the HDSP-4832/-4836 are identical to the HDSP-4830 characteristics. Characteristics of Yellow elements of the HDSP-4832/-4836 are identical to the HDSP-4840. Characteristics of Green elements of the HDSP-4832/-4836 are identical to the HDSP-4850.
5. Reverse voltage per LED should be limited to 3.0 V max. for the HDSP-4830/-4840/-4850/-4832/-4836 and 5.0 V max. for the HLCP-J100.

## Red, AlGaAs Red




Figure 1. Maximum Tolerable Peak Current vs. Pulse Duration – Red.




Figure 2. Maximum Tolerable Peak Current vs. Pulse Duration – AlGaAs Red.




Figure 3. Maximum Allowable DC Current vs. Ambient Temperature.  
 $T_{JMAX} = 100^{\circ}\text{C}$  for Red and  $T_{JMAX} = 110^{\circ}\text{C}$  for AlGaAs Red.




Figure 4. Relative Efficiency (Luminous Intensity per Unit Current) vs. Peak Current.




Figure 5. Forward Current vs. Forward Voltage.




Figure 6. Relative Luminous Intensity vs. DC Forward Current – Red.




Figure 7. Relative Luminous Intensity vs. DC Forward Current – AlGaAs.

For a Detailed Explanation on the Use of Data Sheet Information and Recommended Soldering Procedures, See Application Note 1005.

## HER, Yellow, Green




Figure 8. Maximum Tolerable Peak Current vs. Pulse Duration –

## HER/Yellow/Green.




Figure 9. Maximum Allowable DC Current vs. Ambient Temperature.  $T_{JMAX} = 100^{\circ}$ C.




Figure 10. Relative Efficiency (Luminous Intensity per Unit Current) vs. Peak Current.




Figure 11. Forward Current vs. Forward Voltage.




Figure 12. Relative Luminous Intensity vs. DC Forward Current.

For a Detailed Explanation on the Use of Data Sheet Information and Recommended Soldering Procedures, See Application Note 1005.

## Electrical/Optical

These versatile bar graph arrays are composed of ten light emitting diodes. The light from each LED is optically stretched to form individual elements. The AlGaAs Red (HLCP-J100) bar graph array LEDs use double heterojunction AlGaAs on a GaAs substrate. HER (HDSP-4830) and Yellow (HDSP-4840) bar graph array LEDs use a GaAsP epitaxial layer on a GaP substrate. Green (HDSP-4850) bar graph array LEDs use liquid phase GaP epitaxial layer on a GaP substrate. The multicolor bar graph arrays (HDSP-4832/4836) have HER, Yellow, and Green LEDs in one package. These displays are designed for strobed operation. The typical forward voltage values can be scaled from Figures 5 and 11. These values should be used to calculate the current limiting resistor value and typical power consumption. Expected maximum  $V_F$  values for driver circuit design and maximum power dissipation may be calculated using the  $V_{FMAX}$  models:

AlGaAs Red HLCP-J100 series

$$V_{FMAX} = 1.8 \text{ V} + I_{Peak} (20 \Omega)$$

For:  $I_{Peak} \leq 20 \text{ mA}$

$$V_{FMAX} = 2.0 \text{ V} + I_{Peak} (10 \Omega)$$

For:  $I_{Peak} \geq 20 \text{ mA}$

HER (HDSP-4830) and Yellow (HDSP-4840) series

$$V_{FMAX} = 1.6 + I_{Peak} (45 \Omega)$$

For:  $5 \text{ mA} \leq I_{Peak} \leq 20 \text{ mA}$

$$V_{FMAX} = 1.75 + I_{Peak} (38 \Omega)$$

For:  $I_{Peak} \geq 20 \text{ mA}$

Green (HDSP-4850) series

$$V_{FMAX} = 2.0 + I_{Peak} (50 \Omega)$$

For:  $I_{Peak} > 5 \text{ mA}$

Figures 4 and 10 allow the designer to calculate the luminous intensity at different peak and average currents. The following equation calculates intensity at different peak and average currents:

$$I_VAVG = (I_FAVG/I_FAVG \text{ DATA SHEET})\eta_{peak}(I_V \text{ DATA SHEET})$$

Where:

$I_VAVG$  is the calculated time averaged luminous intensity resulting from  $I_FAVG$ .

$I_FAVG$  is the desired time averaged LED current.

$I_FAVG \text{ DATA SHEET}$  is the data sheet test current for  $I_V \text{ DATA SHEET}$ .

$\eta_{peak}$  is the relative efficiency at the peak current, scaled from Figure 4 or 10.

$I_V \text{ DATA SHEET}$  is the data sheet luminous intensity, resulting from  $I_FAVG \text{ DATA SHEET}$ .

For example, what is the luminous intensity of an HDSP-4830 driven at 50 mA peak 1/5 duty factor?

$$I_FAVG = (50 \text{ mA}) (0.2) = 10 \text{ mA}$$

$$I_FAVG \text{ DATA SHEET} = 10 \text{ mA}$$

$$\eta_{peak} = 1.3$$

$$I_V \text{ DATA SHEET} = 3500 \mu\text{cd}$$

Therefore

$$I_VAVG = (10 \text{ mA}/10 \text{ mA}) (1.3) (3500 \text{ mcd}) = 4550 \text{ mcd}$$

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries.

Data subject to change. Copyright © 2005-2015 Avago Technologies. All rights reserved. Obsoletes AV01-0277EN

AV02-1798EN - October 9, 2015

