


CH1 Markers

2:55.604 n -2.3867 n 1.57662 OHz

3: 4.6333 Ω 8.2705 Ω 1.52500 GHz

SM2520-4 Case

4-Terminal Ceramic Surface-Mount Case 2.5 X 2.0 mm Nominal Footprint



Case Dimensions


Dimension	mm						
	Min	Nom	Max				
Α	1.88	2.0	2.12				
В	2.38	2.5	2.62				
С			1.00				
D	0.67	0.80	0.83				
E	0.80	0.95	1.10				
F	0.55	0.70	0.85				
G	0.50	0.60	0.70				

Electrical Connections

	Connection	Terminals			
Port 1	Single-ended Input	1			
Port 2	Single-ended Output	3			
	Ground	All others			
Single-ended Operation Only					


Materials					
Solder Pad Plating	0.3 to 1.0 μm Gold over 1.27 to 8.89 μm Nickel				
Lid Plating	2.0 to 3.0 µm Nickel				
Body	Al ₂ O ₃ Ceramic				
Pb Free					

TOP VIEW




← C →

BOTTOM VIEW



PCB Foot Print








Table 4: SM2520-4

YEAR	CODE	WEEK CODE				_			
		ALPHA	REPRESENTS	ALPHA	REPRESENTS	ALPHA	REPRESENTS	ALPHA	REPRESENTS
NUMBER	REPRESENTS	CHARACTER	WEEK NO.						
3	2013	Α	01	N	14	а	27	n	40
4	2014	В	02	0	15	b	28	0	41
5	2015	C	03	Р	16	С	29	р	42
6	2016	D	04	Q	17	d	30	q	43
7	2017	E	05	R	18	е	31	r	44
8	2018	F	06	S	19	f	32	S	45
9	2019	G	07	T	20	g	33	t	46
0	2020	Н	08	U	21	h	34	u	47
N. Control of the con		ı	09	٧	22	i	35	V	48
		J	10	W	23	j	36	w	49
		K	11	X	24	k	37	Х	50
		L	12	Y	25	I	38	у	51
		М	13	Z	26	m	39	Z	52

Reflow Profile



Reel Dimension



Tape Dimension

