Allowable Operating Range at $Ta = 25^{\circ}C$

Parameter	Symbol	Conditions	Ratings	Unit
Supply voltage V _{CC}			2.5 to 9.5	V
	VS		2.5 to 9.5	
High-level input voltage	VIH		2.0 to 7.5	V
Low-level input voltage	v_{IL}		-0.3 to 0.7	V


Electrical Characteristics at $Ta = 25^{\circ}C$, $V_{CC} = VS = 5V$


Devenueter	Querra ha a l			11.2			
Parameter	Symbol	Conditions	min	typ	max	Unit	
V _{CC} system power supply	ICC0	IN1 = IN2 = IN3 = IN4 = 0V		0.1	1	μA	
current	ICC1	IN1 = IN3 = 3V, IN2 = IN4 = 0V		10	16	mA	
VS system power supply current	IS0	IN1 = IN2 = IN3 = IN4 = 0V		0.1	1	μA	
	IS1	IN1 = IN3 = 3V, IN2 = IN4 = 0V		12	19	mA	
Output saturation voltage	V _{OUT} 1	V_{CC} = VS = 3V to 7.5V, V_{IN} = 3V or 0V, I_{OUT} = 200mA (High and low side)	-	0.25	0.4	V	
	V _{OUT} 2	V_{CC} = VS = 4V to 7.5V, V_{IN} = 3V or 0V, I_{OUT} = 400mA (High and low side)	-	0.5	0.8	V	
Input current	IIN	V _{IN} = 5V		150	200	μA	
Spark killer diode			-				
Reverse current	IS(leak)				30	μA	
Forward voltage	VSF	I _{OUT} = 400mA			1.7	V	

Package Dimensions


unit:mm (typ)

3178B






Pin Assignment









IN1	IN2	IN3	IN4	OUT1	OUT2	OUT3	OUT4	Output mode
L	L			off	off			(1)
L	н	-		L	н			(2)
н	L			н	L			(3)
				off	н			(4)
H(*)	H(*) H(*)			Н	off			(4)'
		L	L			off	off	(5)
		L	Н			L	н	(6)
-		н	L	-		- H L		(7)
						off	Н	(8)
		H(*) H(*)				н	off	(8)'

L : low, H : high

*: The output logic mode when IN1/IN2 = H/H is determined by the immediately preceding IN1/IN2 mode.

The post-switching output modes will be as follows.

When switching from (2): (4)

When switching from (3): (4)'


When switching from (1): Undefined (Either (4) or (4)')


The modes when IN3/IN4 = H/H operate similarly as described below.


When switching from (6): (8)

When switching from (7): (8)'

When switching from (5): Undefined (Either (8) or (8)')







ORDERING INFORMATION

Device	Package	Shipping (Qty / Packing)		
LB1936V-MPB-E	SSOP16 (225mil) (Pb-Free)	90 / Fan-Fold		
LB1936V-TLM-E	SSOP16 (225mil) (Pb-Free)	2000 / Tape & Reel		

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affimative Action Employer. This literature is subject to all applicable copyright may and is not for resele in any manner.