Contents

1	Electrical ratings 3
2	Electrical characteristics4
	2.1 Electrical characteristics (curve) 5
3	Package mechanical data 6
4	Revision history8



1 Absolute maximim ratings

Table 1.	Absolute maximim ratings
	Absolute maximum ratings

Symbol	Parameter	Value	Unit
V _{CBO}	Collector-base voltage (I _E = 0)	60	V
V _{CEO}	Collector-emitter voltage (I _B = 0)	60	V
V _{EBO}	Emitter-base voltage ($I_C = 0$)	5	V
Ι _C	Collector current	3	А
I _{CM}	Collector peak current	5	А
۱ _B	Base current	1	А
P _{TOT}	Total dissipation at $T_{case} = 25^{\circ}C$ Total dissipation at $T_{amb} = 25^{\circ}C$	40 2	W W
T _{stg}	Storage temperature	-65 to 150	°C
TJ	Max. operating junction temperature	150	°C



2 Electrical characteristics

 $(T_{case} = 25^{\circ}C \text{ unless otherwise specified})$

Table 2.	Electrical	characteristics

Symbol	Parameter Test conditions		Min.	Тур.	Max.	Unit
I _{CEO}	Collector cut-off current (I _B = 0)	V _{CE} = 30 V			0.3	mA
I _{EBO}	Emitter cut-off current ($I_C = 0$)	V _{EB} = 5V			1	mA
I _{CES}	Collector cut-off current (V _{BE} = 0)	V _{CE} = 60V			0.2	mA
V _{CEO(sus)} ⁽¹⁾	Collector-emitter sustaining voltage (I _B = 0)	I _C = 30mA	60			V
V _{CE(sat)} ⁽¹⁾	Collector-emitter saturation voltage	I _C = 3A I _B = 375mA			1.2	V
V _{BE(on)} ⁽¹⁾	Base-emitter voltage	$I_{C} = 3A$ $V_{CE} = 4V$			1.8	V
h _{FE} ⁽¹⁾			25 10		50	

1. Pulsed duration = 300 ms, duty cycle $\ge 1.5\%$



2.1 Electrical characteristics (curve)

Figure 1. Safe Operating area

Figure 2. Derating curves




Figure 3. DC-current gain






Figure 4. DC-current gain








Figure 7. Base-emitter on voltage




3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com



	TO-220 MECHANICAL DATA					
DIM.		mm.		inch		
DINI.	MIN.	TYP	MAX.	MIN.	TYP.	MAX
Α	4.40		4.60	0.173		0.181
b	0.61		0.88	0.024		0.034
b1	1.15		1.70	0.045		0.066
С	0.49		0.70	0.019		0.027
D	15.25		15.75	0.60		0.620
E	10		10.40	0.393		0.409
е	2.40		2.70	0.094		0.106
e1	4.95		5.15	0.194		0.202
F	1.23		1.32	0.048		0.052
H1	6.20		6.60	0.244		0.256
J1	2.40		2.72	0.094		0.107
L	13		14	0.511		0.551
L1	3.50		3.93	0.137		0.154
L20		16.40			0.645	
L30		28.90			1.137	
øP	3.75		3.85	0.147		0.151
Q	2.65		2.95	0.104		0.116







TIP31A

4 Revision history

Table 3. Revision history

Date	Revision	Changes
20-Apr-2006	1	New release



Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZE REPRESENTATIVE OF ST, ST PRODUCTS ARE NOT DESIGNED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS, WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2006 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

10/10

