



.040 MULTILOCK Connectors


Tab Contact (To be used with cap housing for wire to wire connections.)

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)
				S.T.	L.P.	
.040 Tab  Crimp Specifications: 114-5108	0.3~0.5mm ² (AWG#22-20)	Ø1.8-2.0mm	Brass/Pre-tin	173682-1	175063-1	91577-1 (411-5417)

Receptacle Contact (To be used with plug.)

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)
				S.T.	L.P.	
.040 Receptacle  Crimp Specifications: 114-5094	0.3~0.5mm ² (AWG#22-20)	Ø1.8-2.0mm	Copper Alloy/Pre-tin	173681-1	175062-1	91577-1 (411-5417)
			Copper Alloy/Sel. Gold	173681-2	175062-2	
.040 Receptacle For an extra-thin jacketed cable Crimp Specifications: 114-5162	0.3~0.5mm ² (AWG#22-20)	Ø1.1-1.6mm	Copper Alloy/Pre-tin	175180-1	—	—
			Copper Alloy/Sel. Gold	175180-2	—	

Receptacle Contact (To be used with power plug, 16 pos)

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)
				S.T.	L.P.	
.070 Receptacle  Crimp Specifications: 114-5109	0.5~2.0mm ² (AWG#20-14)	Ø2.0-2.9mm	Copper Alloy/Pre-tin	173708-1	175081-1	91177-1 (411-5422)
			Copper Alloy/Sel. Gold	173708-2	175081-2	
.070 Receptacle For an extra-thin jacketed cable Crimp Specifications: 114-5156	0.5~1.25mm ² (AWG#20-16)	Ø1.3-2.1mm	Copper Alloy/Pre-tin	175221-1	—	—