

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

ON CHARACTERISTICS ⁽³⁾

Forward-Current Transfer Ratio $I_C = 50 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$ $I_C = 1.0 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$	h_{FE}	30 15	120	
Collector-Emitter Saturation Voltage $I_C = 50 \text{ mAdc}$, $I_B = 5.0 \text{ mAdc}$	$V_{CE(sat)}$		2.0	Vdc
Base-Emitter Voltage $I_C = 50 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$	V_{BE}		1.5	Vdc

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short Circuit Forward Current Transfer Ratio $I_C = 10 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$, $f = 5.0 \text{ MHz}$	$ h_{fe} $	3.0	15	
Forward Current Transfer Ratio $I_C = 5.0 \text{ mAdc}$, $V_{CE} = 10 \text{ Vdc}$, $f = 1.0 \text{ kHz}$	h_{fe}	25		
Output Capacitance $V_{CB} = 10 \text{ Vdc}$, $I_E = 0$, $100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{obo}		15	pF
Input Capacitance $V_{EB} = 5.0 \text{ Vdc}$, $I_C = 0$, $100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$	C_{ibo}		75	pF

SWITCHING CHARACTERISTICS

Turn-On Time $V_{CC} = 200 \text{ Vdc}$, $I_C = 50 \text{ mAdc}$, $I_{B1} = 5.0 \text{ mAdc}$	t_{on}		1.0	μs
Turn-Off Time $V_{CC} = 200 \text{ Vdc}$, $I_C = 50 \text{ mAdc}$, $I_{B1} = I_{B2} = 5.0 \text{ mAdc}$	t_{off}		10	μs

SAFE OPERATING AREA

DC Tests $T_C = +25^\circ\text{C}$; 1 Cycle; $t = 0.4 \text{ s}$ Test 1 $V_{CE} = 10 \text{ Vdc}$, $I_C = 1.0 \text{ Adc}$ Test 2 $V_{CE} = 100 \text{ Vdc}$, $I_C = 100 \text{ mAdc}$ Test 3 $V_{CE} = 200 \text{ Vdc}$, $I_C = 24 \text{ mAdc}$ 2N5415 Test 4 $V_{CE} = 300 \text{ Vdc}$, $I_C = 10 \text{ mAdc}$ 2N5416				
---	--	--	--	--

(3) Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.