


ELECTRICAL CHARACTERISTICS ($T_{amb} = 25^{\circ}\text{C}$)


Symbol	Parameter
V_{RM}	Stand-off voltage
V_{BR}	Breakdown voltage
V_{CL}	Clamping voltage
I_{RM}	Leakage current @ V_{RM}
I_{PP}	Peak pulse current
αT	Voltage temperature coefficient
V_F	Forward voltage drop



Types		$I_{RM} @ V_{RM}$		$V_{BR} @ I_R$		$V_{CL} @ I_{PP}$		$V_{CL} @ I_{PP}$		αT	C
		max		min		max		max		max	typ
				note2		10/1000 μs		8/20 μs		note3	note4
Unidirectional	Bidirectional	μA	V	V	mA	V	A	V	A	$10^{-4}/^{\circ}\text{C}$	pF
BZW06-5V8	BZW06-5V8B	1000	5.8	6.45	10	10.5	57.0	13.4	298	5.7	4000
BZW06-6V4	BZW06-6V4B	500	6.4	7.13	10	11.3	53.0	14.5	276	6.1	3700
BZW06-8V5	BZW06-8V5B	10	8.5	9.5	1	14.5	41	18.6	215	7.3	2800
BZW06-10	BZW06-10B	5	10.2	11.4	1	16.7	36.0	21.7	184	7.8	2300
BZW06-13	BZW06-13B	5	12.8	14.3	1	21.2	28.0	27.2	147	8.4	1900
BZW06-15	BZW06-15B	1	15.3	17.1	1	25.2	24.0	32.5	123	8.8	1600
BZW06-19	BZW06-19B	1	18.8	20.9	1	30.6	19.6	39.3	102	9.2	1350
BZW06-20	BZW06-20B	1	20.5	22.8	1	33.2	18.0	42.8	93	9.4	1250
BZW06-23	BZW06-23B	1	23.1	25.7	1	37.5	16.0	48.3	83	9.6	1150
BZW06-26	BZW06-26B	1	25.6	28.5	1	41.5	14.5	53.5	75	9.7	1075
BZW06-28	BZW06-28B	1	28.2	31.4	1	45.7	13.1	59.0	68	9.8	1000
BZW06-31	BZW06-31B	1	30.8	34.2	1	49.9	12.0	64.3	62	9.6	950
BZW06-33	BZW06-33B	1	33.3	37.1	1	53.9	11.1	69.7	57	10.0	900
BZW06-40	BZW06-40B	1	40.2	44.7	1	64.8	9.3	84	48	10.1	800
BZW06-48	BZW06-48B	1	47.8	53.2	1	77.0	7.8	100	40	10.3	700
BZW06-58	BZW06-58B	1	58.1	64.6	1	92.0	6.5	121	33	10.4	625
BZW06-70	BZW06-70B	1	70.1	77.9	1	113	5.3	146	27.0	10.5	550
BZW06-85	BZW06-85B	1	85.5	95.0	1	137	4.4	178	22.5	10.6	500
BZW06-102	BZW06-102B	1	102	114	1	165	3.6	212	19.0	10.7	450
BZW06-128	BZW06-128B	1	128	143	1	207	2.9	265	15.0	10.8	400
BZW06-154	BZW06-154B	1	154	171	1	246	2.4	317	12.6	10.8	360
BZW06-171	BZW06-171B	1	171	190	1	274	2.2	353	11.3	10.8	350

Types		I_{RM} @ V_{RM}		V_{BR} @ I_R		V_{CL} @ I_{PP}		V_{CL} @ I_{PP}		αT	C
				min		max		max		max	typ
				note2		10/1000 μs		8/20 μs		note3	note4
Unidirectional	Bidirectional	μA	V	V	mA	V	A	V	A	$10^{-4}/^{\circ}C$	pF
BZW06-188	BZW06-188B	1	188	209	1	328	2.0	388	10.3	10.8	330
BZW06-213	BZW06-213B	1	231	237	1	344	2.0	442	9.0	11.0	310
BZW06-256	BZW06-256B	1	256	285	1	414	1.6	529	7.6	11.0	290
BZW06-273	BZW06-273B	1	273	304	1	438	1.6	564	7.1	11.0	280
BZW06-299	BZW06-299B	1	299	332	1	482	1.6	618	6.5	11.0	270
BZW06-342	BZW06-342B	1	342	380	1	548	1.3	706	5.7	11.0	360
BZW06-376	BZW06-376B	1	376	418	1	603	1.3	776	5.7	11.0	350

Fig. 1: Peak pulse power dissipation versus initial junction temperature (printed circuit board).



Note 2 : Pulse test: $t_p < 50$ ms.

Note 3 : $\Delta V_{BR} = \alpha T * (T_{amb} - 25) * V_{BR}(25^{\circ}C)$

Note 4 : $V_R = 0$ V, $F = 1$ MHz. For bidirectional types, capacitance value is divided by 2




Fig. 2 : Peak pulse power versus exponential pulse duration.





Fig. 3 : Clamping voltage versus peak pulse current.

Exponential waveform $t_p = 20 \mu\text{s}$ _____
 $t_p = 1 \text{ ms}$ _____
 $t_p = 10 \text{ ms}$



Note : The curves of the figure 3 are specified for a junction temperature of 25°C before surge.
 The given results may be extrapolated for other junction temperatures by using the following formula :
 $\Delta V_{BR} = \alpha T * (T_{amb} - 25) * V_{BR}(25^\circ\text{C})$.
 For intermediate voltages, extrapolate the given results.

Fig. 4a : Capacitance versus reverse applied voltage for unidirectional types (typical values).




Fig. 4b : Capacitance versus reverse applied voltage for bidirectional types (typical values).




Fig. 5 : Peak forward voltage drop versus peak forward current (typical values for unidirectional types).




Fig. 6 : Transient thermal impedance junction ambient versus pulse duration (For FR4 PC Board with L lead = 10mm).






Fig. 7 : Relative variation of leakage current versus junction temperature.



BZW06-xx


ORDER



MARKING : Logo, Date Code, Type Code, Cathode Band (for unidirectional types only).

PACKAGE MECHANICAL DATA

DO-15 (Plastic)



Packaging : standard packaging is in tape and reel.

Weight = 0.4 g.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany
Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>