


SMD Power Inductor

CDRH8D43



Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※1	D.C.R. (m Ω) Max. (Typ.) (at 20℃)	Saturation Current (A) ※2 (Typ.)	Temperature Rise Current (A) ※3
CDRH8D43NP-R68NC	R68	0.68 $\pm$ 35%	9.5(7.0)	9.0(10.80)	7.60
CDRH8D43NP-1R2NC	1R2	1.2 $\pm$ 35%	12.2(9.0)	8.0(10.50)	7.00
CDRH8D43NP-2R0NC	2R0	2.0 $\pm$ 30%	14(11)	7.0(9.00)	6.30
CDRH8D43NP-3R9NC	3R9	3.9 $\pm$ 30%	19(15)	5.9(7.50)	4.90
CDRH8D43NP-4R7NC	4R7	4.7 $\pm$ 30%	22(17)	5.6(7.20)	4.60
CDRH8D43NP-6R8NC	6R8	6.8 $\pm$ 30%	25(20)	4.4(5.80)	4.30
CDRH8D43NP-100NC	100	10 $\pm$ 30%	36(29)	4.0(5.50)	3.50
CDRH8D43NP-150NC	150	15 $\pm$ 30%	53(42)	2.9(3.60)	2.55
CDRH8D43NP-220NC	220	22 $\pm$ 30%	75(60)	2.6(3.25)	2.10
CDRH8D43NP-330NC	330	33 $\pm$ 30%	125(100)	2.2(2.60)	1.55
CDRH8D43NP-470NC	470	47 $\pm$ 30%	150(120)	1.8(2.25)	1.42
CDRH8D43NP-680NC	680	68 $\pm$ 30%	240(190)	1.5(1.76)	1.15
CDRH8D43NP-101NC	101	100 $\pm$ 30%	360(290)	1.3(1.55)	0.88

- ※1. Inductance measuring conditions at 100kHz.
- ※2. Saturation current: The DC current at which the inductance decreases to 65% of its nominal value.
- ※3. Temperature rise current: The actual DC current at which the temperature rise is $\Delta t=40^{\circ}\text{C}$.(Ta=20℃)


SMD Power Inductor

CDRH8D43



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT




SMD Power Inductor



CDRH8D43



Saturation Current & Temperature Rise Graph



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com