

Material :	✓ CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	✓ 1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	✓ Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11

Minimum Cable Diameter [mm] :	 3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Minimum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	 3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Maximum Cable Diameter [mm] :	3.11
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	 0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50

Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Minimum Cable Core Cross Section [mm2] :	0.50
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	 0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Maximum Cable Core Cross Section [mm2] :	0.80
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	 -40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125

Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	✔ Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
Voltage Drop :	Less than 3.0
RoHs compliant :	✔ Yes
ELV compliant :	✔ Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.

