



Press image to zoom

## 50FT PRO-AUDIO XLR MALE TO XLR FEMALE CABLE

Connect line or mic level outputs from mixing consoles to recorders and amplifiers with balanced inputs

Product # : 40062

Connector 1 : (1) XLR 3-pin Male

Connector 2 : (1) XLR 3-pin Female

Lengths : 50ft 1.5ft 3ft 6ft 12ft

**Add**

120 In Stock & ready to ship!

### NEED IT SHIPPED TODAY?

Place your order before the timer runs out!

**3: 42: 36**

print share chat

[Product Info](#) [Customer Reviews](#) [Questions & Answers](#) [Distributors](#) [More Choices](#)

[Product Features](#) [Product Description](#) [Product Specifications](#)

### Product Features

- 22 AWG conductor construction
- Foil and braided shield to protect from interference
- Highly flexible jacket
- Nickel-plated connectors

### Product Description

Use this XLR to XLR cable to connect unbalanced sources to balanced XLR inputs. This pro-audio cable is made from 22 AWG twisted pair audio cable under an aluminum foil shield and 60% copper braid for maximum shielding from noise. The highly flexible 7mm PVC jacket reduces the risk of the cable kinking and damaging the conductors.

Bright nickel plating on solid brass connectors resists wear from reconfiguring and moving equipment from one venue to another. Spring strain relief on the 1/4in plug and a chuck strain relief inside the XLR reduce the effects of age on the solder joints and contacts.

Tap an icon to learn more:



**WARNING:** Cancer and Reproductive Harm [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Product Specifications

<b>Color :</b>	Black
<b>Length :</b>	50.00 Foot
<b>UPC :</b>	757120400622
<b>Warranty :</b>	Lifetime
<b>Vendor :</b>	C2G
<b>Weight :</b>	1.850 LB

#### Info

[About Us](#)  
[Order History](#)  
[Where To Buy](#)  
[More ▾](#)

#### Service

[Contact Us](#)  
[OEM Solutions](#)  
[Tech Support](#)  
[More ▾](#)

#### Resources

[Connector Guides](#)  
[ConnectXpress](#)  
[Drivers & Manuals](#)  
[More ▾](#)

#### Have A Question?

Get help with [Chat](#)  
Call C2G **800.506.9607**