

PIN PLATING CODES:

XXXXX-1YY	30u"/0.76u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-2YY	15u"/0.38u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-3YY	50u"/1.27u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-4YY	100u"/2.54u MIN Sn OVER 50u"/1.27u MIN NI (SEE NOTE 10)
XXXXX-4YYHLF	
XXXXX-5YY	15u"/0.38u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-6YY	30u"/0.76u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-7YY	50u"/0.76u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-8YY	15u"/0.38u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-9YY	15u"/0.38u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI
XXXXX-0YY	30u"/0.76u MIN (SEE NOTE 9) OVER 50u"/1.27u MIN NI

NOTES

① PART NUMBER OPTIONS:

PIN PLATING CODES (SEE ABOVE)

HIGH TEMP. MATERIAL:

PART NUMBERS WITH AND WITHOUT 'H' WILL BE SUPPLIED WITH HIGH TEMPERATURE PLASTIC

NUMBER OF POSITION:

EVEN NUMBER OF POSITIONS FROM 2 (2X1) THRU 72 (2X36).

PACKAGING:

PACKAGED IN POLY BAGS.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A 'T' ARE PACKAGED IN TUBES. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

LEAD FREE:

ADD 'HLF' SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION, NOT AVAILABLE FOR -5YY, -5YYH, -6YY & -6YYH.

② BODY MATERIAL:

MANUFACTURER'S OPTION OF NYLON, PCT GLASS FIBER REINFORCED, OR MINERAL FILLED LCP FLAME RETARDANT PER UL-94V-0. COLOR: BLACK.

PART NUMBERS WITH AND WITHOUT 'H' SUFFIX WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRARED OR VAPOR PHASE SOLDER PROCESS.

③ PIN MATERIAL: PHOS-BRONZE.

④ MEASURED WITH PART IN RESTRAINED CONDITION.

⑤ TWO SIDES OF PIN TIPS NOT PLATED. TYPICAL BOTH ENDS.

⑥ 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION.

⑦ MILITARY BERGSTIK HEADER
P/N XXXXX-XY-MIL
NOT AVAILABLE.

⑧ THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.

⑨ PLATING OPTIONS:

PERFORMANCE PLATING WILL BE EITHER GOLD OR GXT ON POST OR TAIL, OPTIONALLY (78-295u"/2-7.5u) TIN ON TAIL.

⑩ THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS.

⑪ THE DAL DON'T EXCEED 31mm


DAL = MATTING DIM + TAIL DIM + 4.0mm ≤ 31mm *WHERE THE SUM OF TAIL LEGTH DON'T EXCEED 27mm *TAIL TAIL LENGTH MIN 2.00mm TAIL LENGTH MAX 10.4mm MATTING LENGTH MIN 1.5mm MATTING LENGTH MAX 25.4mm

⑫ INCREMENTS BY 0.1mm IN LENGTH ONLY

⑬ FOR ESPECIAL PACKAGING REQUEST PLEASE CONTACT PRODUCT MANAGER FOR AVAILABILITY

⑭ BEND DIMENSION AT 1.5mm ONLY

⑮ TO DETERMINE DIMENSIONS:

N=NUMBER OF POSITION PER ROW
EXAMPLE: 10 PDS. N X 100/2.54

RECOMMENDED HOLE PATTERN

www.fciconnect.com				surface		tolerance std		projection		INCH/MM	
Dr	DIWHITING	03/08/93	ANGULAR	ISD 1302	✓	ISD 406	ISD 1101	⊕	⊕	Scale	
Eng	THANNA	03/08/93	LINEAR	TOLERANCES UNLESS OTHERWISE SPECIFIED				size	A4	1.000	
Chr	T.BREVINKER	03/08/93	0° ±2°	0XX	0XX	±0.05	±0.05	ECN			
Appr	THANNA	03/08/93	Product family	BERGSTIK	Spec ref						
FCI BERGSTIK® II HEADER				100/2.54cc DR R/A		2		68020		Rev.	
catalog no						Product-Customer Drw		Sheet 2 of 5		BM	



Copyright FCI.

D

C

B

A

1

2

3

4

PRODUCT NUMBER	MATING	LENGTH	TAIL LENGTH		BEND DIM.		PIN TO SIDE		BODY WIDTH		PACKAGING	LF OPTION
	DIM F	DIM F	DIM G	DIM G	DIM H	DIM H	DIM J	DIM J	DIM K	DIM K		
	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC		
68020-XYX	0.230	5.84	0.095	2.41	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS/TUBES	NOTE 1,8
68021-XYX	0.230	5.84	0.120	3.05	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68022-XYX	0.318	8.08	0.110	2.79	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
68025-XYX	0.230	5.84	0.195	4.95	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68405-XYX	0.230	5.84	0.095	2.41	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	NOTE 1,8
68452-XYX	0.380	9.65	0.110	2.79	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
68459-XYX	0.318	8.08	0.150	3.81	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS/TUBES	
68462-XYX	0.400	10.16	0.120	3.05	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68463-XYX	0.230	5.84	0.110	2.79	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	NOTE 1,8
68480-XYX	0.318	8.08	0.110	2.79	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68492-XYX	0.230	5.84	0.150	3.81	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
68493-XYX												
68695-XYX	0.230	5.84	0.090	2.29	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	NOTE 1,8
68696-XYX	0.318	8.08	0.125	3.18	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68697-XYX	0.230	5.84	0.125	3.18	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68715-XYX	0.138	3.51	0.138	3.51	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68728-XYX												NOTE 1,8
68740-XYX	0.345	8.76	0.110	2.79	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
68759-XYX	0.275	6.99	0.120	3.05	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
68780-XYX	0.230	5.84	0.039	0.99	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
69147-XYX	0.540	13.72	0.260	6.60	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	NOTE 1,8
69186-XYX												
72240-XYX	0.550	13.97	0.120	3.05	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
72261-XYX	0.100	2.54	0.100	2.54	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
72324-XYX	0.550	13.97	0.260	6.60	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	NOTE 1,8
72410-XYX	0.120	3.05	0.350	8.89	0.120	3.05	0.070	1.78	0.240	6.10	POLY BAGS	
74430-XYX	0.000	0.00	0.233	5.92	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	



Copyright FCI.

www.fciconnect.com		Surface ISD 1302		tolerance std ISD 406 ISD 1101		projection		INCH/MM	
TOLERANCES UNLESS OTHERWISE SPECIFIED		ANGULAR		LINEAR		size		Scale	
Dw DIVIDING		03/08/93		0.0X		±0.3		A4	
Eng THAWNA		03/08/93		0.0X		±0.15		1:1000	
Chr TBREUNAKER		03/08/93		0.0X		±0.05		ECN	
Appr THAWNA		03/08/93		Product family		BERGSTIK		Spec ref	
FCI logo		BERGSTIK II HEADER		100/254cc DR R/A		68020		Rev. BM	
catalog no		Product-Customer Dtw		Sheet 3 of 5					

D

C

B

A

1

2

3

4

1

2

3

4

PRODUCT NUMBER	MATING	LENGTH	TAIL LENGTH	BEND DIM.	PIN TO SIDE	BODY WIDTH	PACKAGING	LF OPTION				
	DIM F	DIM F	DIM G	DIM G	DIM H	DIM H	DIM J	DIM J	DIM K	DIM K		
	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC		
78576-XXX	0.120	3.05	0.120	3.05	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
78923-XXX	0.240	6.10	0.095	2.41	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
78951-XXX	0.500	12.70	0.120	3.05	-0.060	1.52	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
79200-XXX	0.155	3.94	0.280	7.11	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79201-XXX	0.225	5.72	0.280	7.11	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79202-XXX	0.245	6.22	0.280	7.11	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79203-XXX	0.315	8.00	0.280	7.11	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79204-XXX	0.177	4.50	0.410	10.41	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79205-XXX	-0.25	-6.35	0.410	10.41	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79206-XXX	0.315	8.00	0.410	10.41	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
79248-XXX												NOTE 1,8
79257-XXX	0.230	5.84	0.120	3.05	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS/TUBES	
79258-XXX	0.318	8.08	0.120	3.05	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS/TUBES	
79807-XXX												
79841-XXX	0.060	1.52	0.230	5.84	-0.060	1.52	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
86385-XXX	0.260	-6.6	0.120	3.05	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
86840-XXX	0.318	8.08	0.230	5.84	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
86867-XXX												
88822-XXX	0.318	8.08	0.080	2.03	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
89292-XXX	0.120	3.05	0.300	7.62	-0.120	3.05	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
90234-XXX	0.130	3.30	0.195	4.95	-0.060	1.52	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
92634-XXX	0.318	8.08	0.318	8.08	0.060	1.52	0.045	1.14	0.190	4.83	POLY BAGS	
93162-XXX	0.230	5.84	0.400	10.16	-0.150	3.81	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
93932-XXX	0.200	5.08	0.120	3.05	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB
93939-XXX	0.160	4.06	0.120	3.05	0.060	1.52	0.070	1.78	0.240	6.10	POLY BAGS	
94687-XXX	0.430	10.92	0.230	5.84	-0.060	1.52	0.045	1.14	0.190	-4.83	-POLY BAGS	OB
94688-XXX	0.385	9.78	0.280	7.11	-0.060	1.52	0.070	1.78	0.240	-6.10	-POLY BAGS	OB



Copyright FCI.

www.fciconnect.com				Surface ISO 1302		tolerance std ISO 406 ISO 1101		projection		INCH/MM	
TOLERANCES UNLESS OTHERWISE SPECIFIED				ANGULAR		LINEAR		size		Scale	
Dr DIVIDING				03/08/93		0.0X		±0.3		A4	
Eng THAWNA				03/08/93		0.0XX		±0.15		1,000	
Chr TBREVNAKER				03/08/93		0.1XX		±0.05		ECN	
Appr THAWNA				03/08/93		Product family		BERGSTIK		Spec ref	
FCI BERGSTIK® II HEADER				100/254cc DR R/A		Rev.		68020		BM	
catalog no				Product-Customer Drw		Sheet 4 of 5					

D

C

B

A

1

2

3

4

1													2		3	
PRODUCT NUMBER	MATING		LENGTH		TAIL LENGTH		BEND DIM.		PIN TO SIDE		BODY WIDTH					
	DIM F	DIM F	DIM F	DIM G	DIM G	DIM H	DIM H	DIM J	DIM J	DIM K	DIM K		LF			
	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	OPTION			
95035-XXXX	0.230	5.84	0.400	10.16	0.060	1.52	0.045	1.14	0.190	4.83	—	—	POLY BAGS	OB		
95182-XXXX	0.400	10.16	0.110	2.79	0.060	1.52	0.070	1.78	0.240	6.10	—	—	POLY BAGS	OB		
98358-XXXX	0.205	5.21	0.410	10.44	0.060	1.52	0.070	1.78	0.240	6.10	—	—	POLY BAGS	OB		
98359-XXXX	0.275	6.99	0.410	10.44	0.060	1.52	0.070	1.78	0.240	6.10	—	—	POLY BAGS	OB		
68020-144-095030LF	.374	9.50	0.118	3.00	0.060	1.52	0.070	1.78	0.240	6.10			POLY BAGS			

B

A



C

Copyright FCI.

D

www.fciconnect.com		surface		tolerance std		projection		INCH/MM	
ISD 1302		ISD 406		ISD 1101		ISD 1302		ISD 406	
TOLERANCES UNLESS OTHERWISE SPECIFIED		ANGULAR		LINEAR		size		A4	
Dr DIVIDING		03/08/93		0.0X		±0.3		Scale	
Eng THANNA		03/08/93		0.0X		±0.15		1,000	
Chr TBREVNAKER		03/08/93		0" ±2"		ECN			
Appr THANNA		03/08/93		Product family		BERGSTIK		Spec ref	
FCI logo		BERGSTIK® II HEADER		100/254cc DR R/A		Product-Customer Drw		68020	
catalog no		68020		Rev.		Product-Customer Drw		Sheet 5 of 5	

D

C

B

A