

SEMICONDUCTOR

BCV71

NPN General Purpose Amplifier

- This device is designed for general purpose applications at collector currents to 300mA.
- Sourced from process 10.



BCV71

1. Base 2. Emitter 3. Collector

Absolute Maximum Ratings * T_a=25°C unless otherwise noted

Symbol	Parameter	Value	Units	
/ _{CEO}	Collector-Emitter Voltage	60	V	
V _{CBO}	Collector-Base Voltage	80	V	
V _{EBO}	Emitter-Base Voltage	5.0	V	
с	Collector current (DC) 500		mA	
T _J , T _{sta}	Operating and Storage Junction Temperature Range	-55 ~ +150	°C	

NOTES:

1) These ratings are based on a maximum junction temperature of 150 degrees C.
2) These are state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Electrical Characteristics T_a=25°C unless otherwise noted


Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units
Off Charact	eristics					
V _{(BR)CBO}	Collector-Base Breakdown Voltage	$I_{\rm C} = 10 \mu {\rm A}, \ I_{\rm E} = 0$	80			V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	$I_{\rm C} = 2{\rm mA}, I_{\rm B} = 0$	60			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	$I_{\rm E} = 10 \mu A, I_{\rm C} = 0$	5.0			V
I _{CBO}	Collector Cutoff Current	$V_{CB} = 20V, I_E = 0$			100	nA
		$V_{CB} = 20V, I_E = 0, T_a = 100^{\circ}C$			10	μΑ
On Charact	eristics					
h _{FE}	DC Current Gain	$I_{C} = 2.0 \text{mA}, V_{CE} = 5.0 \text{V}$	110		220	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 10mA, I _B = 0.5mA			0.25	V
V _{BE(on)}	Base-Emitter On Voltage	$I_{C} = 2.0 \text{mA}, V_{CE} = 5.0 \text{V}$	0.55		0.7	V

Thermal Characteristics T_a=25°C unless otherwise noted

Symbol	Parameter	Max.	Units
PD	Total Device Dissipation	350	mW
-	Derate above 25°C	2.8	mW/°C
$R_{ extsf{ heta}JA}$	Thermal Resistance, Junction to Ambient	357	°C/W

Device mounted on FR-4PCB 40mm × 40mm × 1.5mm

©2004 Fairchild Semiconductor Corporation



©2004 Fairchild Semiconductor Corporation

Rev. A, April 2004

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

The Power France	chise [®]	$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	POP [™] Power247 [™] PowerSaver [™] PowerTrench [®] QFET [®] QS [™] QT Optoelectronics [™] Quiet Series [™] RapidConfigure [™] RapidConnect [™] SILENT SWITCHER [®]	SPM TM Stealth TM SuperFET TM SuperSOT TM -3 SuperSOT TM -6 SuperSOT TM -8 SyncFET TM TinyLogic [®] TINYOPTO TM TruTranslation TM UHC TM UltraFET [®]
		OPTOLOGIC [®] OPTOPLANAR™	SILENT SWITCHER® SMART START™	UltraFE1 [©] VCX™
Programmable A	ctive Droop™	OF TOF LANAIX	SMART START	VOX

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user. 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Formative or	
In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.
	Full Production

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor haves against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death a

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81–3–5817–1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

© Semiconductor Components Industries, LLC

Downloaded from Arrow.com.