

GL865-QUAD

Product features

- LCC Castellation form factor
- Quad-band GSM | GPRS 850 / 900 / 1800 / 1900 MHz
- GSM | GPRS protocol stack 3GPP Release 4 compliant
- Control via AT commands according to 3GPP TS 27.005, 27.007 and Telit custom AT commands
- Serial port multiplexer 3GPP TS 27.010
- SIM access profile
- SIM application toolkit 3GPP TS 51.014
- DARP/SAIC support
- SMS Support
- SMS over GPRS
- Telephony, emergency call
- Half rate, full rate, enhanced full rate and adaptive multi rate voice codecs (HR, FR, EFR, AMR)
- Superior echo cancellation & noise reduction
- Multiple audio profiles pre-programmed and fully configurable by mean AT commands
- DTMF
- SIM phonebook
- Fixed dialing number (FDN)
- Real-time clock
- Alarm management
- Network LED support
- IRA, GSM, 8859-1 and UCS2 character set
- Jamming detection
- Embedded TCP/IP stack, including TCP, IP, UDP, SMTP, ICMP and FTP protocols
- PFM (Premium FOTA Management) Over-The-Air Update service
- Remote AT commands
- Event monitor
- Telit's EASY features EASY SCAN[®] automatic scan over GSM frequencies (also without SIM card)

Data

GPRS

- GPRS class 10
- Mobile station class B
- Coding scheme 1 to 4
- PBCCH support
- GERAN Feature Package 1 support (NACC, Extended TBF)

CSD

Environmental

- Dimensions: 24.4 x 24.4 x 2.7 mm
- Weight: 2.8 grams
- Extended temperature range
- -40°C to +85°C (operational)
- -40°C to +85°C (storage temperature)

Interfaces

- 8 I/O ports maximum
- Analog audio (balanced), digital audio
- 2 A/D plus 1 D/A converter
- Buzzer output
- ITU-T V.24 serial link through CMOS UART:
 - Baud rate from 300 to 115,200 bps
 - Autobauding up to 115,200 bps

Approvals

- Fully type approved conforming R&TTE directive
- CE, GCF
- FCC, IC, PTCRB (North America)
- ANATEL (Brazil)

Electrical & Sensitivity

- Output power
 - Class 4 (2W) @ 850/900 MHz
 - Class 1 (1W) @ 1800/1900 MHz
- Supply voltage range: 3.22 - 4.5 VDC (3.8 V DC recommended)
- Power consumption (typical values)
 - Power off: < 5 uA
 - Idle (registered, power saving): 1.5 mA @ DRX=9
 - Dedicated mode: 230 mA @ max power level
 - GPRS cl.10: 360 mA @ max power level

- Sensitivity:
 - 108 dBm (typ.) @ 850/900 MHz
 - 107 dBm (typ.) @ 1800/1900 MHz

Software

- Python* application resources
- Python* script interpreter (module takes the application code directly in the Python* language)
- Memory: 800 kB of NV memory for the user scripts and 1 MB RAM for the Python* engine usage



Join the Telit Technical Forum

For a quicker and more rewarding integration experience join the Telit Technical Forum. There you can browse the first open forum covering all m2m topics, get direct support by region (EMEA, North America, Latin America, APAC), take part in this quickly growing m2m community and exchange experiences.