

Applications

- Security and Surveillance Cameras

Product Features

- support for image sizes:
 - 1080p @ 30 fps
 - cropped 720p @ 60 fps
 - VGA @ 120 fps
- programmable controls: gain, exposure, frame rate, image size, horizontal mirror, vertical flip, cropping, windowing, and panning
- automatic image control functions:
 - automatic exposure (AEC)
 - automatic gain control (AGC)
 - automatic white balance (AWB)
 - automatic black level calibration (ABLC)
- serial camera control bus (SCCB)
- lens correction (LENC)
- defect pixel correction (DPC)
- support for digital video port (DVP) parallel output interface
- integrated auto focus filter
- support for 10-bit RAW RGB output format
- support for black sun cancellation
- embedded one-time programmable (OTP) memory
- on-chip phase lock loop (PLL)
- built-in 1.5 V regulator for core

OV2715




Ordering Information

- **OV02715-A68A**
(color, lead-free, 68-pin CSP3)
- **OV02715-A68A-PC**
(color, lead-free, 68-pin CSP3 with protective film)
- **OV02715-A68A-RC**
(color, lead-free, 68-pin CSP3 with protective film, packed in tape and reel)

Product Specifications

- **active array size:** 1920 x 1080
- **power supply:**
 - analog: 3.0 - 3.6 V (3.3 V typical)
 - core: 1.425 - 1.575 V (1.5 V typical)
 - I/O: 1.7 - 3.6 V (1.8 V typical)
- **power requirements:**
 - active: 350 mW
 - power down: 70 μ A
- **temperature range:**
 - operating: -30°C to 85°C junction temperature
 - stable image: 0°C to 65°C junction temperature
- **output interfaces:** 10-bit parallel/one lane MIPI
- **output formats:** 10-bit RAW RGB data
- **lens size:** 1/2.7"
- **lens chief ray angle:** 0°
- **input clock frequency:** 6 - 27 MHz
- **scan mode:** progressive
- **maximum image transfer rate:**
 - 1080p: 30 fps
 - cropped 720p: 60 fps
 - VGA: 120 fps
 - QVGA: 240 fps
- **sensitivity:** 3300 mV/lux-sec
- **shutter:** rolling shutter
- **max S/N ratio:** 39 dB
- **dynamic range:** 69 dB @ 8x gain
- **maximum exposure interval:** 1096 tline
- **pixel size:** 3 μ m x 3 μ m
- **image area:** 5856 μ m x 3276 μ m
- **package dimensions:** 7465 μ m x 5865 μ m

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: +1 408 567 3000
Fax: +1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniPixel3-HS is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.

OmniVision

Version 1.4, October, 2011