

Power PCB Relay RT2 DC and AC (for Asia/Pacific markets) (Continued)

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter


Resistance to heat and fire	
WG version	according EN60335, par30
Ambient temperature -40 to 85°C	
Category of environmental protection	
IEC 61810	RTII - flux proof, RTIII - wash tight
Vibration resistance (functional)	
form A/form B contact, 30 to 300Hz	20g/5g
Shock resistance (destructive)	
	100g
Terminal type PCB-THT, plug-in	
Weight 13g	
Resistance to soldering heat THT, IEC 60068-2-20	
RTII	270°C/10s
RTIII	260°C/5s
Packaging/unit tube/20pcs., box/500pcs.	

Accessories

For details see datasheet [Accessories Industrial Power Relay RT](#)


NOTE: indicated contact ratings and electrical endurance data for direct wiring of relays (according IEC 61810-1); for relays mounted on sockets deratings may apply.

Dimensions




PCB layout / terminal assignment

Bottom view on solder pins




*) With the recommended PCB hole sizes a grid pattern from 2.5mm to 2.54mm can be used.

2 form C (CO) contacts



2 form A (NO) contacts



Power PCB Relay RT2 DC and AC (for Asia/Pacific markets) (Continued)

Product code structure	Typical product code	RT	4	2	4	024
Type	RT Power PCB Relay RT2					
Version	4 8A, pinning 5mm, flux proof E 8A, pinning 5mm, wash tight (not for Reflow version)					
Contact arrangement	2 2 form C (CO) contacts 4 2 form A (NO) contacts					
Contact material	3 AgSnO 4 AgNi 90/10 5 AgNi 90/10 gold plated					
Coil	Coil code: please refer to coil versions table					
Version	Blank Standard version WG Product in accordance with IEC 60335-1 (domestic appliances) R Reflow solderable					

Product code	Version	Contact	Contact Material	Coil	Version	Part number
RT424005	8A,	2 form C (CO)	AgNi 90/10	5VDC	standard	1-1649329-0
RT424006	pinning 5 mm,	contacts		6VDC		1-1649329-1
RT424009	flux proof			9VDC		1-1649329-2
RT424012				12VDC		1-1649329-3
RT424012WG				12VDC	IEC 60335-1 compliant	8-1833003-5
RT424024				24VDC	standard	1-1649329-5
RT424048				48VDC		1-1649329-6
RT424060				60VDC		1-1649329-7
RT424110				110VDC		1-1649329-8
RT425005			AgNi 90/10	5VDC		4-1649329-6
RT425012			gold plated	12VDC		4-1649329-9
RT425024				24VDC		5-1649329-1
RT444012		2 form A (NO)	AgNi 90/10	12VDC		3-1649329-1
RT444024		contacts		24VDC		3-1649329-3
RTE24005	8A,	2 form C (CO)		5VDC		1649329-1
RTE24006	pinning 5 mm,	contacts		6VDC		1649329-2
RTE24012	wash tight			12VDC		1649329-4
RTE24024				24VDC		1649329-6
RTE24048				48VDC		1649329-7
RTE24060				60VDC		1649329-8
RTE24110				110VDC		1649329-9
RTE25005			AgNi 90/10	5VDC		3-1649329-7
RTE25012			gold plated	12VDC		4-1649329-0
RTE25024				24VDC		4-1649329-2
RTE44009		2 form A (NO)	AgNi 90/10	9VDC		2-1649329-1
RTE44012		contacts		12VDC		2-1649329-2
RTE44024				24VDC		2-1649329-4
RTE44048				48VDC		2-1649329-5