
Contents

1	Electrical ratings.....	3
2	Electrical characteristics	4
2.1	Electrical characteristics (curves)	6
3	Test circuits	9
4	Package information	10
4.1	TO-247 package information	10
5	Revision history.....	12

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V _{CES}	Collector-emitter voltage (V _{GE} = 0)	600	V
I _C ⁽¹⁾	Continuous collector current at T _C = 25 °C	42	A
I _C ⁽¹⁾	Continuous collector current at T _C = 100 °C	23	A
I _{CL} ⁽²⁾	Turn-off latching current	30	A
V _{GE}	Gate-emitter voltage	±20	V
P _{TOT}	Total dissipation at T _C = 25 °C	140	W
T _{stg}	Storage temperature range	- 55 to 150	°C
T _J	Operating junction temperature range		

Notes:

⁽¹⁾Calculated according to the iterative formula:

$$I_C(T_C) = \frac{T_{JMAX} - T_C}{R_{THJ-C} \times V_{CESAT(MAX)}(T_{J(max)} \times I_C(T_C))}$$

⁽²⁾V_{CLAMP} = 80% (V_{CES}), V_{GE} = 15 V, R_G = 10 Ω, T_J = 150 °C

Table 3: Thermal data

Symbol	Parameter	Value	Unit
R _{thj-case}	Thermal resistance junction-case max	0.9	°C/W
R _{thj-amb}	Thermal resistance junction-ambient max	50	°C/W

2 Electrical characteristics

$T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise specified

Table 4: Static

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CES}$	Collector-emitter breakdown voltage	$V_{GE} = 0\text{ V}$, $I_C = 1\text{ mA}$	600			V
$V_{CE(sat)}$	Collector-emitter saturation voltage	$V_{GE} = 15\text{ V}$, $I_C = 12\text{ A}$		2.1	2.5	V
		$V_{GE} = 15\text{ V}$, $I_C = 12\text{ A}$, $T_J = 125\text{ }^{\circ}\text{C}$		1.8		
$V_{GE(th)}$	Gate threshold voltage	$V_{CE} = V_{GE}$, $I_C = 250\text{ }\mu\text{A}$	3.75		5.75	V
I_{CES}	Collector cut-off current	$V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$			150	μA
		$V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$, $T_C = 125\text{ }^{\circ}\text{C}$ ⁽¹⁾			1	mA
I_{GES}	Gate-emitter leakage current	$V_{CE} = 0\text{ V}$, $V_{GE} = \pm 20\text{ V}$			± 100	nA
g_{fs}	Forward transconductance	$V_{CE} = 15\text{ V}$, $I_C = 12\text{ A}$		10		S

Notes:

⁽¹⁾Defined by design, not subject to production test.

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{ies}	Input capacitance	$V_{CE} = 25\text{ V}$, $f = 1\text{ MHz}$, $V_{GE} = 0\text{ V}$	-	1180	-	pF
C_{oes}	Output capacitance		-	130	-	
C_{res}	Reverse transfer capacitance		-	26	-	
Q_g	Total gate charge	$V_{CE} = 390\text{ V}$, $I_C = 12\text{ A}$, $V_{GE} = 15\text{ V}$ (see Figure 16: "Gate charge test circuit")	-	53	-	nC
Q_{ge}	Gate-emitter charge		-	10	-	
Q_{gc}	Gate-collector charge		-	21	-	

Table 6: Switching on/off (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 10\ \Omega$ (see Figure 17: "Switching waveform")	-	25	-	ns
t_r	Current rise time		-	7	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1600	-	A/ μ s
$t_{d(on)}$	Turn-on delay time	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 10\ \Omega$, $T_C = 125^\circ\text{C}$ (see Figure 17: "Switching waveform")	-	25	-	ns
t_r	Current rise time		-	8	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1400	-	A/ μ s
$t_r(V_{off})$	Off voltage rise time	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 10\ \Omega$ (see Figure 17: "Switching waveform")	-	22	-	ns
$t_{d(off)}$	Turn-off delay time		-	90	-	ns
t_f	Current fall time		-	43	-	ns
$t_r(V_{off})$	Off voltage rise time	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 10\ \Omega$, $T_C = 125^\circ\text{C}$ (see Figure 17: "Switching waveform")	-	47	-	ns
$t_{d(off)}$	Turn-off delay time		-	127	-	ns
t_f	Current fall time		-	77	-	ns

Table 7: Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$E_{on}^{(1)}$	Turn-on switching energy	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $R_G = 10\ \Omega$, $V_{GE} = 15\text{ V}$ (see Figure 17: "Switching waveform")	-	81	-	μ J
$E_{off}^{(2)}$	Turn-off switching energy		-	125	-	μ J
E_{ts}	Total switching energy		-	206	-	μ J
$E_{on}^{(1)}$	Turn-on switching energy		-	161	-	μ J
$E_{off}^{(2)}$	Turn-off switching energy		-	255	-	μ J
E_{ts}	Total switching energy	$V_{CC} = 390\text{ V}$, $I_C = 12\text{ A}$, $R_G = 10\ \Omega$, $V_{GE} = 15\text{ V}$, $T_C = 125^\circ\text{C}$ (see Figure 17: "Switching waveform")	-	416	-	μ J

Notes:

⁽¹⁾Including the reverse recovery of the external diode. The diode is the same of the co-packed STGW19NC60WD.

⁽²⁾Including the tail of the collector current.

2.2 Electrical characteristics (curves)

Figure 2: Output characteristics




Figure 3: Transfer characteristics




Figure 4: Transconductance




Figure 5: Collector-emitter on voltage vs temperature




Figure 6: Gate charge vs gate-source voltage




Figure 7: Capacitance variations




Figure 8: Normalized gate threshold voltage vs temperature




Figure 9: Collector-emitter on voltage vs collector current




Figure 10: Normalized breakdown voltage vs temperature




Figure 11: Switching energy vs temperature




Figure 12: Switching energy vs gate resistance




Figure 13: Switching energy vs collector current






Figure 14: Turn-off SOA




3 Test circuits

Figure 15: Test circuit for inductive load switching




AM01504v1

Figure 16: Gate charge test circuit



AM01505v1

Figure 17: Switching waveform



AM01506v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 TO-247 package information

Figure 18: TO-247 package outline




Table 8: TO-247 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

5 Revision history

Table 9: Document revision history

Date	Revision	Changes
04-Oct-2006	1	Initial release.
08-May-2007	2	Modified value on <i>Table 2</i>
20-Nov-2008	3	Inserted packages: D2PAK and TO-247
07-Nov-2016	4	The part numbers STGB19NC60W and STGP19NC60W have been moved to a separate datasheet Modified: <i>Table 2: "Absolute maximum ratings"</i> , <i>Table 4: "Static"</i> and <i>Table 7: "Switching energy (inductive load)"</i> Minor text changes

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved