

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

## Product Type Features

PCB Connector Assembly Type : **PCB Mount Header**  
Connector System : **Wire-to-Board**  
Header Type : **Partially Shrouded**  
Sealable : **No**  
Connector & Contact Terminates To : **Printed Circuit Board**  
Wire/Cable Type : **Discrete Wire**

## Configuration Features

Connector Contact Load Condition : **Fully Loaded**  
PCB Mount Orientation : **Vertical**  
Number of Positions : **2**  
Number of Rows : **1**

## Electrical Characteristics

Operating Voltage (VAC): **100**

## Contact Features

Contact Base Material : **Phosphor Bronze**  
PCB Contact Termination Area Plating Material : **Tin**  
Contact Underplating Material : **Nickel**  
Contact Mating Area Plating Material : **Tin**  
Contact Mating Area Plating Material Finish : **Matte**  
Contact Type : **Pin**  
Contact Current Rating (Max) (A): **.8**  
PCB Contact Termination Area Plating Thickness : **3.08 µm [ 120 µin ]**  
PCB Contact Termination Area Plating Material Finish : **Matte**  
Contact Layout : **Inline**

## Termination Features

Termination Method to Printed Circuit Board : **Through Hole**  
Termination Post & Tail Length : **1.7 mm [ .067 in ]**

## Mechanical Attachment

Mating Alignment : **With**  
Mating Alignment Type : **Polarization**  
PCB Mount Alignment : **Without**  
Mating Retention : **Without**  
PCB Mount Retention : **Without**  
Connector Mounting Type : **Board Mount**  
Strain Relief : **Without**  
Contact Retention : **Without**

## Housing Features

Centerline (Pitch) : **1.25 mm [ .049 in ]**  
Housing Color : **Natural**  
Housing Material : **PA 9T GF**

## Dimensions

Length : **4.2 mm [ .165 in ]**  
Height : **4.7 mm [ .185 in ]**  
Width : **3.2 mm [ .126 in ]**

## Usage Conditions

Operating Temperature Range : **-25 – 85 °C [ -13 – 185 °F ]**



Industry Standards	UL Flammability Rating : <b>UL 94V-0</b>
Packaging Features	Packaging Quantity : <b>141</b> Packaging Method : <b>Tube, Tube/Box</b>
Statement of Compliance	<a href="#">Statement of Compliance pdf</a>

Products with Similar Specs

[View All Similar Products](#)


THIS PRODUCT

TOP RESULTS ?

WIRE-TO-BOARD HEADERS &...

1734598-2

1.25 WTB HDR DIP, 2 POS




In-Stock

PCB Connector Assembly Type : **PCB Mount Header**  
PCB Mount Orientation : **Vertical**  
Connector System : **Wire-to-Board**  
Number of Positions : **2**  
Centerline (Pitch) : **1.25 mm**

WIRE-TO-BOARD HEADERS &...

1-1734598-0

1.25 WTB HDR DIP, 10 POS




From In-Stock

PCB Connector Assembly Type : **PCB Mount Header**  
PCB Mount Orientation : **Vertical**  
Connector System : **Wire-to-Board**  
Number of Positions : **10**  
Centerline (Pitch) : **1.25 mm**

WIRE-TO-BOARD HEADERS &...

1734598-3

1.25 WTB HDR DIP, 3 POS




From In-Stock

PCB Connector Assembly Type : **PCB Mount Header**  
PCB Mount Orientation : **Vertical**  
Connector System : **Wire-to-Board**  
Number of Positions : **3**  
Centerline (Pitch) : **1.25 mm**

WIRE-TO-BOARD HEADERS &...

1734598-7

1.25 WTB HDR DIP, 7 POS



From In-Stock

PCB Connector Assembly Type : **PCB Mount Header**  
PCB Mount Orientation : **Vertical**  
Connector System : **Wire-to-Board**  
Number of Positions : **7**  
Centerline (Pitch) : **1.25 mm**