

TABLE OF CONTENTS

Features	1	ESD Caution.....	7
Applications.....	1	Pin Configurations and Function Descriptions	8
Functional Block Diagram	1	Truth Table	8
General Description	1	Typical Performance Characteristics	9
Product Highlights	1	Test Circuits.....	12
Revision History	2	Terminology	14
Specifications.....	3	Outline Dimensions	15
Dual Supply	3	Ordering Guide	15
Single Supply	5		
Absolute Maximum Ratings.....	7		

REVISION HISTORY

3/16—Rev. B to Rev. C

Changed LFCSP_VQ to LFCSP	Throughout
Changes to Figure 3.....	8
Updated Outline Dimensions	15
Changes to Ordering Guide	15

2/09—Rev. A to Rev. B

Changes to Power Requirements, I_{DD} , Digital Inputs = 5 V	
Parameter, Table 1.....	4
Changes to Power Requirements, I_{DD} , Digital Inputs = 5 V	
Parameter, Table 2.....	6
Updated Outline Dimensions	15

7/06—Rev. 0 to Rev. A

Updated Format.....	Universal
Changes to Table 1.....	3
Changes to Table 2.....	5
Changes to the Terminology Section.....	14

7/05—Revision 0: Initial Version

SPECIFICATIONS

DUAL SUPPLY

$V_{DD} = 15\text{ V} \pm 10\%$, $V_{SS} = -15\text{ V} \pm 10\%$, GND = 0 V, unless otherwise noted.

Table 1.

Parameter	Y Version ¹			Unit	Test Conditions/Comments
	25°C	–40°C to +85°C	–40°C to +125°C		
ANALOG SWITCH					
Analog Signal Range			V _{DD} to V _{SS}	V	
On Resistance (R _{ON})	120			Ω typ	V _S = ±10 V, I _S = –1 mA; see Figure 21
	190	230	260	Ω max	V _{DD} = +13.5 V, V _{SS} = –13.5 V
On Resistance Match Between Channels (ΔR _{ON})	3.5			Ω typ	V _S = ±10 V, I _S = –1 mA
	6	10	12	Ω max	
On Resistance Flatness (R _{FLAT(ON)})	20			Ω typ	V _S = –5 V, 0 V, +5 V; I _S = –1 mA
	57	72	79	Ω max	
LEAKAGE CURRENTS					
Source Off Leakage, I _S (OFF)	±0.02			nA typ	V _{DD} = +16.5 V, V _{SS} = –16.5 V
	±0.1	±0.6	±1	nA max	V _S = ±10 V, V _D = ∓10 V; see Figure 22
Drain Off Leakage, I _D (OFF)	±0.02			nA typ	V _S = ±10 V, V _D = ∓10 V; see Figure 22
	±0.1	±0.6	±1	nA max	
Channel On Leakage, I _D , I _S (ON)	±0.02			nA typ	V _S = V _D = ±10 V; see Figure 23
	±0.2	±0.6	±1	nA max	
DIGITAL INPUTS					
Input High Voltage, V _{INH}			2.0	V min	
Input Low Voltage, V _{INL}			0.8	V max	
Input Current, I _{INL} or I _{INH}	0.005			μA typ	V _{IN} = V _{INL} or V _{INH}
			±0.1	μA max	
Digital Input Capacitance, C _{IN}	2.5			pF typ	
DYNAMIC CHARACTERISTICS ²					
Transition Time, t _{TRANS}	120			ns typ	R _L = 300 Ω, C _L = 35 pF
	150	180	200	ns max	V _S = 10 V; see Figure 24
t _{ON} (EN)	70			ns typ	R _L = 300 Ω, C _L = 35 pF
	85	100	110	ns max	V _S = 10 V; see Figure 26
t _{OFF} (EN)	90			ns typ	R _L = 300 Ω, C _L = 35 pF
	110	135	155	ns max	V _S = 10 V; see Figure 26
Break-Before-Make Time Delay, t _D	25			ns typ	R _L = 300 Ω, C _L = 35 pF
			10	ns min	V _{S1} = V _{S2} = 10 V; see Figure 25
Charge Injection	–0.7			pC typ	V _S = 0 V, R _S = 0 Ω, C _L = 1 nF; see Figure 27
Off Isolation	85			dB typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz; see Figure 28
Channel-to-Channel Crosstalk	80			dB typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz; see Figure 30
Total Harmonic Distortion + Noise	0.15			% typ	R _L = 10 kΩ, 5 V rms, f = 20 Hz to 20 kHz; see Figure 31
Bandwidth –3 dB	800			MHz typ	R _L = 50 Ω, C _L = 5 pF; see Figure 29
C _S (OFF)	1.2			pF typ	f = 1 MHz, V _S = 0 V
	1.5			pF max	f = 1 MHz, V _S = 0 V
C _D (OFF)	3.6			pF typ	f = 1 MHz, V _S = 0 V
	4.2			pF max	f = 1 MHz, V _S = 0 V
C _D , C _S (ON)	5.5			pF typ	f = 1 MHz, V _S = 0 V
	6.5			pF max	f = 1 MHz, V _S = 0 V

Parameter	Y Version ¹			Unit	Test Conditions/Comments
	25°C	–40°C to +85°C	–40°C to +125°C		
POWER REQUIREMENTS					$V_{DD} = +16.5\text{ V}$, $V_{SS} = -16.5\text{ V}$
I_{DD}	0.001		1.0	$\mu\text{A typ}$ $\mu\text{A max}$	Digital inputs = 0 V or V_{DD}
I_{DD}	170		285	$\mu\text{A typ}$ $\mu\text{A max}$	Digital inputs = 5 V
I_{SS}	0.001		1.0	$\mu\text{A typ}$ $\mu\text{A max}$	Digital inputs = 0 V or V_{DD}
I_{SS}	0.001		1.0	$\mu\text{A typ}$ $\mu\text{A max}$	Digital inputs = 5 V

¹ Y version temperature range is –40°C to +125°C.

² Guaranteed by design, not subject to production test.

SINGLE SUPPLY

$V_{DD} = 12\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$, $GND = 0\text{ V}$, unless otherwise noted.

Table 2.

Parameter	Y Version ¹			Unit	Test Conditions/Comments
	25°C	–40°C to +85°C	–40°C to +125°C		
ANALOG SWITCH					
Analog Signal Range			0 V to V _{DD}	V	
On Resistance (R _{ON})	300			Ω typ	V _S = 0 V to 10 V, I _S = –1 mA; see Figure 21
	475	567	625	Ω max	V _{DD} = 10.8 V, V _{SS} = 0 V
On Resistance Match Between Channels (ΔR _{ON})	5			Ω typ	V _S = 0 V to 10 V, I _S = –1 mA
	16	26	27	Ω max	
On Resistance Flatness (R _{FLAT(ON)})	60			Ω typ	V _S = 3 V, 6 V, 9 V; I _S = –1 mA
LEAKAGE CURRENTS					
Source Off Leakage, I _S (OFF)	±0.02			nA typ	V _{DD} = 13.2 V
	±0.1	±0.6	±1	nA max	V _S = 1 V/10 V, V _D = 10 V/1 V; see Figure 22
Drain Off Leakage, I _D (OFF)	±0.02			nA typ	V _S = 1 V/10 V, V _D = 10 V/1 V; see Figure 22
	±0.1	±0.6	±1	nA max	
Channel On Leakage, I _D , I _S (ON)	±0.02			nA typ	V _S = V _D = 1 V or 10 V; see Figure 23
	±0.2	±0.6	±1	nA max	
DIGITAL INPUTS					
Input High Voltage, V _{INH}			2.0	V min	
Input Low Voltage, V _{INL}			0.8	V max	
Input Current, I _{INL} or I _{INH}	0.001			μA typ	V _{IN} = V _{INL} or V _{INH}
			±0.1	μA max	
Digital Input Capacitance, C _{IN}	2.5			pF typ	
DYNAMIC CHARACTERISTICS ²					
Transition Time, t _{TRANS}	150			ns typ	R _L = 300 Ω, C _L = 35 pF
	190	240	265	ns max	V _S = 8 V; see Figure 24
t _{ON} (EN)	95			ns typ	R _L = 300 Ω, C _L = 35 pF
	120	150	170	ns max	V _S = 8 V; see Figure 26
t _{OFF} (EN)	100			ns typ	R _L = 300 Ω, C _L = 35 pF
	125	155	170	ns max	V _S = 8 V; see Figure 26
Break-Before-Make Time Delay, t _D	50			ns typ	R _L = 300 Ω, C _L = 35 pF
			10	ns min	V _{S1} = V _{S2} = 8 V; see Figure 25
Charge Injection	–0.4			pC typ	V _S = 6 V, R _S = 0 Ω, C _L = 1 nF; see Figure 27
Off Isolation	85			dB typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz; see Figure 28
Channel-to-Channel Crosstalk	80			dB typ	R _L = 50 Ω, C _L = 5 pF, f = 1 MHz; see Figure 30
Bandwidth –3 db	550			MHz typ	R _L = 50 Ω, C _L = 5 pF; see Figure 29
C _S (OFF)	1.2			pF typ	f = 1 MHz; V _S = 6 V
	1.5			pF max	f = 1 MHz; V _S = 6 V
C _D (OFF)	3.6			pF typ	f = 1 MHz; V _S = 6 V
	4.2			pF max	f = 1 MHz; V _S = 6 V
C _D , C _S (ON)	5.5			pF typ	f = 1 MHz; V _S = 6 V
	6.5			pF max	f = 1 MHz; V _S = 6 V

Parameter	Y Version ¹			Unit	Test Conditions/Comments
	25°C	–40°C to +85°C	–40°C to +125°C		
POWER REQUIREMENTS					
I _{DD}	0.001		1.0	μA typ μA max	V _{DD} = 13.2 V Digital inputs = 0 V or V _{DD}
I _{DD}	170		285	μA typ μA max	Digital inputs = 5 V

¹ Y version temperature range is –40°C to +125°C.

² Guaranteed by design, not subject to production test.

ABSOLUTE MAXIMUM RATINGS

$T_A = 25^\circ\text{C}$, unless otherwise noted.

Table 3.

Parameter	Rating
V_{DD} to V_{SS}	35 V
V_{DD} to GND	-0.3 V to $+25\text{ V}$
V_{SS} to GND	$+0.3\text{ V}$ to -25 V
Analog Inputs ¹	$V_{SS} - 0.3\text{ V}$ to $V_{DD} + 0.3\text{ V}$ or 30 mA, whichever occurs first
Digital Inputs ¹	$\text{GND} - 0.3\text{ V}$ to $V_{DD} + 0.3\text{ V}$ or 30 mA, whichever occurs first
Peak Current, S or D	100 mA (pulsed at 1 ms, 10% duty cycle maximum)
Continuous Current	45 mA
Operating Temperature Range	
Automotive (Y Version)	-40°C to $+125^\circ\text{C}$
Storage Temperature Range	-65°C to $+150^\circ\text{C}$
Junction Temperature	150°C
14-Lead TSSOP, θ_{JA} Thermal Impedance (4-Layer Board)	112°C/W
12-Lead LFCSP, θ_{JA} Thermal Impedance	80°C/W
Reflow Soldering Peak Temperature, Pb Free	260°C

¹ Overvoltages at IN, S, or D are clamped by internal diodes. Current must be limited to the maximum ratings given.

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

Only one absolute maximum rating can be applied at any one time.

ESD CAUTION



ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATIONS AND FUNCTION DESCRIPTIONS




Figure 2. TSSOP Pin Configuration




Figure 3. LFCSP Pin Configuration

Table 4. Pin Function Descriptions

Pin No.		Mnemonic	Description
TSSOP	LFCSP		
1	11	A0	Logic Control Input.
2	12	EN	Active High Digital Input. When low, the device is disabled and all switches are off. When high, Ax logic inputs determine on switches.
3	1	V_{SS}	Most Negative Power Supply Potential.
4	2	S1	Source Terminal. Can be an input or an output.
5	3	S2	Source Terminal. Can be an input or an output.
6	4	D	Drain Terminal. Can be an input or an output.
7 to 9	5	NC	No Connection.
10	6	S4	Source Terminal. Can be an input or an output.
11	7	S3	Source Terminal. Can be an input or an output.
12	8	V_{DD}	Most Positive Power Supply Potential.
13	9	GND	Ground (0 V) Reference.
14	10	A1	Logic Control Input.

TRUTH TABLE

Table 5.

EN	A1	A0	S1	S2	S3	S4
0	X	X	Off	Off	Off	Off
1	0	0	On	Off	Off	Off
1	0	1	Off	On	Off	Off
1	1	0	Off	Off	On	Off
1	1	1	Off	Off	Off	On

TYPICAL PERFORMANCE CHARACTERISTICS







Figure 4. On Resistance as a Function of V_D (V_S), Dual SupplyFigure 7. On Resistance as a Function of V_D (V_S) for Different Temperatures, Dual SupplyFigure 5. On Resistance as a Function of V_D (V_S), Dual SupplyFigure 8. On Resistance as a Function of V_D (V_S) for Different Temperatures, Single SupplyFigure 6. On Resistance as a Function of V_D (V_S), Single Supply

Figure 9. Leakage Currents as a Function of Temperature, Dual Supply




Figure 10. Leakage Currents as a Function of Temperature, Single Supply




Figure 13. Transition Times vs. Temperature



Figure 11. I_{DD} vs. Logic Level

Figure 14. Off Isolation vs. Frequency




Figure 12. Charge Injection vs. Source Voltage




Figure 15. Crosstalk vs. Frequency




Figure 16. On Response vs. Frequency




Figure 19. On Capacitance vs. Source Voltage




Figure 17. THD + N vs. Frequency




Figure 20. Capacitance vs. Source Voltage, Single Supply




Figure 18. Off Capacitance vs. Source Voltage

TEST CIRCUITS




Figure 21. On Resistance




Figure 22. Off Leakage




Figure 23. On Leakage




Figure 24. Address to Output Switching Times




Figure 25. Break-Before-Make Time Delay




Figure 26. Enable-to-Output Switching Delay







Figure 27. Charge Injection



$$\text{OFF ISOLATION} = 20 \log \frac{V_{OUT}}{V_S}$$

04779-027


Figure 28. Off Isolation



$$\text{CHANNEL-TO-CHANNEL CROSSTALK} = 20 \log \frac{V_{OUT}}{V_S}$$

04779-029

Figure 30. Channel-to-Channel Crosstalk



$$\text{INSERTION LOSS} = 20 \log \frac{V_{OUT \text{ WITH SWITCH}}}{V_{OUT \text{ WITHOUT SWITCH}}}$$

04779-028

Figure 29. Bandwidth




Figure 31. THD + Noise

04779-030

TERMINOLOGY

I_{DD}

The positive supply current.

I_{SS}

The negative supply current.

V_D (V_S)

The analog voltage on Terminal D and Terminal S.

R_{ON}

The ohmic resistance between D and S.

R_{FLAT(ON)}

Flatness is defined as the difference between the maximum and minimum value of on resistance, as measured over the specified analog signal range.

I_S (OFF)

The source leakage current with the switch off.

I_D (OFF)

The drain leakage current with the switch off.

I_D, I_S (ON)

The channel leakage current with the switch on.

V_{INL}

The maximum input voltage for Logic 0.

V_{INH}

The minimum input voltage for Logic 1.

I_{INL} (I_{INH})

The input current of the digital input.

C_S (OFF)

The off switch source capacitance, which is measured with reference to ground.

C_D (OFF)

The off switch drain capacitance, which is measured with reference to ground.

C_D, C_S (On)

The on switch capacitance, measured with reference to ground.

C_{IN}

The digital input capacitance.

t_{ON} (EN)

The delay between applying the digital control input and the output switching on.

t_{OFF} (EN)

The delay between applying the digital control input and the output switching off.

t_{TRANS}

The delay time between the 50% and 90% points of the digital input and switch on condition when switching from one address state to another.

Charge Injection

A measure of the glitch impulse transferred from the digital input to the analog output during switching.

Off Isolation

A measure of unwanted signal coupling through an off switch.

Crosstalk

A measure of unwanted signal that is coupled through from one channel to another as a result of parasitic capacitance.

Bandwidth

The frequency at which the output is attenuated by –3 dB.

On Response

The frequency response of the on switch.


Insertion Loss

The loss due to the on resistance of the switch.

Total Harmonic Distortion + Noise (THD + N)

The ratio of the harmonic amplitude plus noise of the signal to the fundamental.


OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MO-153-AB-1

Figure 32. 14-Lead Thin Shrink Small Outline Package [TSSOP]
(RU-14)

Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MO-220-WEED.

Figure 33. 12-Lead Lead Frame Chip Scale Package [LFCSP]
3 mm × 3 mm Body and 0.75 mm Package Height
(CP-12-4)

Dimensions shown in millimeters

ORDERING GUIDE

Model ¹	Temperature Range	Package Description	Package Option
ADG1204YRUZ	−40°C to +125°C	14-Lead Thin Shrink Small Outline Package [TSSOP]	RU-14
ADG1204YRUZ-REEL	−40°C to +125°C	14-Lead Thin Shrink Small Outline Package [TSSOP]	RU-14
ADG1204YRUZ-REEL7	−40°C to +125°C	14-Lead Thin Shrink Small Outline Package [TSSOP]	RU-14
ADG1204YCPZ-500RL7	−40°C to +125°C	12-Lead Lead Frame Chip Scale Package [LFCSP]	CP-12-4
ADG1204YCPZ-REEL7	−40°C to +125°C	12-Lead Lead Frame Chip Scale Package [LFCSP]	CP-12-4

¹ Z = RoHS Compliant Part.

NOTES