

Dynamic Characteristics

$T_J = 25^{\circ}\text{C}$ unless otherwise specified

APT102GA60B2_L

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	Capacitance $V_{GE} = 0V, V_{CE} = 25V$ $f = 1\text{MHz}$		8170		pF
C_{oes}	Output Capacitance			630		
C_{res}	Reverse Transfer Capacitance			78		
Q_g^4	Total Gate Charge	Gate Charge $V_{GE} = 15V$ $V_{CE} = 300V$ $I_C = 62A$		294		nC
Q_{ge}	Gate-Emitter Charge			56		
Q_{gc}	Gate- Collector Charge			106		
SSOA	Switching Safe Operating Area	$T_J = 150^{\circ}\text{C}, R_G = 4.7\Omega^5, V_{GE} = 15V,$ $L = 100\mu\text{H}, V_{CE} = 600V$	307			A
$t_{d(on)}$	Turn-On Delay Time	Inductive Switching (25°C) IGBT and Diode $V_{CC} = 400V$ $V_{GE} = 15V$ $I_C = 62A$ $R_G = 4.7\Omega^5$ $T_J = +25^{\circ}\text{C}$		28		ns
t_r	Current Rise Time			37		
$t_{d(off)}$	Turn-Off Delay Time			212		
t_f	Current Fall Time			101		
E_{on2}	Turn-On Switching Energy			1354		μJ
E_{off}^7	Turn-Off Switching Energy			1614		
$t_{d(on)}$	Turn-On Delay Time	Inductive Switching (125°C) IGBT and Diode $V_{CC} = 400V$ $V_{GE} = 15V$ $I_C = 62A$ $R_G = 4.7\Omega^5$ $T_J = +125^{\circ}\text{C}$		27		ns
t_r	Current Rise Time			37		
$t_{d(off)}$	Turn-Off Delay Time			247		
t_f	Current Fall Time			142		
E_{on2}	Turn-On Switching Energy			2106		μJ
E_{off}^7	Turn-Off Switching Energy			1852		

1 Continuous current limited by package lead temperature.

2 Repetitive Rating: Pulse width and case temperature limited by maximum junction temperature.

3 Pulse test: Pulse Width $< 380\mu\text{s}$, duty cycle $< 2\%$.

4 See Mil-Std-750 Method 3471.

5 R_G is external gate resistance, not including internal gate resistance or gate driver impedance. (MIC4452)

6 E_{on2} is the clamped inductive turn on energy that includes a commutating diode reverse recovery current in the IGBT turn on energy loss. A combi device is used for the clamping diode.

7 E_{off} is the clamped inductive turn-off energy measured in accordance with JEDEC standard JESD24-1.

Microsemi reserves the right to change, without notice, the specifications and information contained herein.

Typical Performance Curves

APT102GA60B2_L




FIGURE 1, Output Characteristics ($T_J = 25^\circ\text{C}$)




FIGURE 2, Output Characteristics ($T_J = 25^\circ\text{C}$)




FIGURE 3, Transfer Characteristics




FIGURE 4, Gate charge




FIGURE 5, On State Voltage vs Gate-to-Emitter Voltage




FIGURE 6, On State Voltage vs Junction Temperature




FIGURE 7, Threshold Voltage vs Junction Temperature




FIGURE 8, DC Collector Current vs Case Temperature

Typical Performance Curves

APT102GA60B2_L




FIGURE 9, Turn-On Delay Time vs Collector Current




FIGURE 11, Current Rise Time vs Collector Current




FIGURE 13, Turn-On Energy Loss vs Collector Current




FIGURE 10, Turn-Off Delay Time vs Collector Current




FIGURE 12, Current Fall Time vs Collector Current




FIGURE 14, Turn-Off Energy Loss vs Collector Current




FIGURE 15, Switching Energy Losses vs Gate Resistance




FIGURE 16, Switching Energy Losses vs Junction Temperature

Typical Performance Curves

APT102GA60B2_L




FIGURE 17, Capacitance vs Collector-To-Emitter Voltage




FIGURE 18, Minimum Switching Safe Operating Area




Figure 19, Maximum Effective Transient Thermal Impedance, Junction-To-Case vs Pulse Duration




Figure 20, Inductive Switching Test Circuit




Figure 21, Turn-on Switching Waveforms and Definitions






Figure 22, Turn-off Switching Waveforms and Definitions

T-MAX™ (B2) Package Outline



These dimensions are equal to the TO-247 without the mounting hole.
Dimensions in Millimeters and (Inches)

TO-264 (L) Package Outline



Dimensions in Millimeters and (Inches)