



PROTECTION PRODUCTS
Pin Identification and Configuration

Pin	Symbol	Identification
1, 16	DAT1	Data line #1 input/output
2, 15	DAT0	Data line #0 Input/Output
3, 14	Clock	Clock line Input/Output
4	Rup	15K Pull-up resistors
5, 12	Vdd	Power Supply ESD Protection in/output
6, 11	CMD	Command Line Input/Output
7, 10	DAT3	Data line #3 input/output
8, 9	DAT2	Data line #2 input/output
13	NC	Not connected
Center tab	GND	Ground connection


Pin Configuration (Top View)
Schematics & Component Values


PROTECTION PRODUCTS
Absolute Maximum Rating

Parameter	Symbol	Value	Units
Junction Temperature	T_J	125	°C
Operating Temperature	T_{op}	-40 to +85	°C
Storage Temperature	T_{STG}	-55 to +150	°C
ESD per IEC 61000-4-2			
Input Pins 1, 2, 3, 5, 6, 7, 8, 12 (Contact) ¹ Input Pins 1, 2, 3, 5, 6, 7, 8, 12 (Air) ¹	V_{ESD}	+/- 12 +/- 15	kV
Output Pins 4, 9, 10, 11, 14, 15, 16 (Contact) ¹ Output Pins 4, 9, 10, 11, 14, 15, 16 (Air) ¹	V_{ESD}	+/- 10 +/- 10	kV

Electrical Characteristics (T = 25°C)





Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Units
TVS Reverse Stand-Off Voltage	V_{RWM}				5	V
TVS Reverse Breakdown Voltage	V_{BR}	$I_t = 1mA$	6	8	10	V
TVS Reverse Leakage Current	I_R	$V_{RWM} = 3.0V$			0.1	μA
Series Resistors	R	Each Line	38	45	52	Ohms
DAT Pull Up Resistor	R_{up}		12	15	18	k Ohms
Dynamic Resistance ^{2, 3}	R_{DYN}	$t_p = 100ns$, Measured from 4A to 16A		0.40		Ohms
Total Capacitance	C_{in}	Input to Gnd, Pins 1, 2, 6, 7, 8 $V_R = 0V$, $f = 1MHz$	10	22	25	pF
Total Capacitance	C_{in}	Input to Gnd, Pin 3, 5, 12 $V_R = 0V$, $f = 1MHz$	6	12	15	pF


Notes







1) Measured with a 20dB attenuator, 50 Ohm scope input impedance, 2GHz bandwidth. ESD gun return path connected to ESD ground plane.

2) Transmission Line Pulse Test (TLP) Settings: $t_p = 100ns$, $t_r = 0.2ns$, I_{TLP} and V_{TLP} averaging window: $t_1 = 70ns$ to $t_2 = 90ns$.

3) Dynamic resistance calculated from $I_{TLP} = 4A$ to $I_{TLP} = 16A$

PROTECTION PRODUCTS
Typical Characteristics
**Capacitance vs. Reverse Voltage
(CLK & VDD)**

**Capacitance vs. Reverse Voltage
(DAT & CMD Lines)**

Typical Insertion Loss S21 (CLK Line)

Typical Insertion Loss S21 (Each DAT Line)

Analog Crosstalk

TLP Characteristic


PROTECTION PRODUCTS
Typical Characteristics
**ESD Clamping (+8kV Contact per IEC 61000-4-2)
DAT Lines**

**ESD Clamping (-8kV Contact per IEC 61000-4-2)
DAT Lines**

**ESD Clamping +8kV Contact per IEC 61000-4-2)
CLK Line**

**ESD Clamping -8kV Contact per IEC 61000-4-2)
CLK Line**

**ESD Clamping +8kV Contact per IEC 61000-4-2)
VDD Line**

**ESD Clamping -8kV Contact per IEC 61000-4-2)
VDD Line**


PROTECTION PRODUCTS
Applications Information
Device Connection

The EClamp2515K is a microSD/T-Flash interface device designed for use in cell phones and other portable electronic devices. The EClamp2515K is comprised of series and pull up resistors required on the microSD interface. Each line also includes TVS diodes for ESD protection.

The EClamp2515K is in a 16-pin SLP package. Electrical connection is made to the 16 pins located at the bottom of the device. The device has a flow through design for easy layout. Pin connections are noted in Figure 1. A center tab serves as the ground connection. Recommendations for the ground connection are given below.


Ground Connection Recommendation


Parasitic inductance present in the board layout will affect the filtering and ESD performance of the device. Ground loop inductance can be reduced by using multiple vias to make the connection to the ground plane. Figure 2 shows the recommended device layout. The ground pad vias have a diameter of 0.008 inches (0.20 mm) while the two external vias have a diameter of 0.010 inches (0.250mm). The internal vias are spaced approximately evenly from the center of the pad. The designer may choose to use more vias with a smaller diameter (such as 0.005 inches or 0.125mm) since changing the diameter of the via will result in little change in inductance.

**Figure 1 - Pin Identification and Configuration
(Top Side View)**

DAT1 In	1	16	DAT1 Out
DAT0 In			DAT0 Out
CLK In			CLK Out
Rup			No Connect
Vdd In			Vdd (out)
CMD In			CMD Out
DAT3 In			DAT3 Out
DAT2 In			DAT2 Out

Figure 2 - Recommended Layout using Ground Vias




PROTECTION PRODUCTS
Outline Drawing - SLP3313P16T


DIM	INCHES			MILLIMETERS		
	MIN	NOM	MAX	MIN	NOM	MAX
A	.018	.020	.022	0.45	0.50	0.55
A1	.000	.001	.002	0.00	0.02	0.05
A2		(.005)			(0.13)	
b	.006	.008	.010	0.15	0.20	0.25
D	.128	.130	.133	3.25	3.30	3.375
D1	.110	.114	.118	2.80	2.90	3.00
E	.049	.051	.054	1.25	1.30	1.375
E1	.008	.012	.016	0.20	0.30	0.40
e		.016 BSC			0.40 BSC	
L	.008	.010	.012	0.20	0.25	0.30
N		16			16	
aaa		.003			0.08	
bbb		.004			0.10	

NOTES:


1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).
2. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

Land Pattern - SLP3313P16T


DIM	DIMENSIONS	
	INCHES	MILLIMETERS
C	(.050)	(1.27)
G	.027	0.69
H	.012	0.30
K	.118	3.00
P	.016	0.40
X	.008	0.20
Y	.023	0.58
Z	.073	1.85

NOTES:

1. CONTROLLING DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).
2. THIS LAND PATTERN IS FOR REFERENCE PURPOSES ONLY. CONSULT YOUR MANUFACTURING GROUP TO ENSURE YOUR COMPANY'S MANUFACTURING GUIDELINES ARE MET.



PROTECTION PRODUCTS
Marking Code


YYWW = Date Code

Ordering Information

Part Number	Qty per Reel	Reel Size
EClamp2515K.TCT	3000	7 Inch

EMIClamp and EClamp are trademarks of Semtech Corporation

Tape and Reel Specification


Pin 1 Location (Towards Sprocket Holes)

User Direction of feed

Device Orientation in Tape

A0	B0	K0
1.51 +/-0.10 mm	3.51 +/-0.10 mm	0.66 +/-0.10 mm

Tape Width	B, (Max)	D	D1	E	F	K (MAX)	P	P0	P2	T(MAX)	W
12 mm	8.2 mm (.476)	1.5 + 0.1 mm - 0.0 mm (0.59 +.005 - .000)	1.0 mm ±0.05 (.039)	1.750±.10 mm (.069±.004)	5.5±0.05 mm (.217±.002)	4.5 mm (.177)	4.0±0.1 mm (.157±.00- 4)	4.0±0.1 mm (.157±.00- 4)	2.0±0.05m- m (.079±.002)	0.4 mm (.016)	12.0 mm + 0.3 mm - 0.1 mm (.472±.012)

Contact Information

Semtech Corporation
Protection Products Division
200 Flynn Road, Camarillo, CA 93012
Phone: (805)498-2111 FAX (805)498-3804