

Thin-Film RF/Microwave Inductor Technology

Accu-L® Series

L0603 AND L0805 SMD High-Q RF Inductor – Accu-L®



HOW TO ORDER

L	0805	4R7	D	E	S	TR
Product Sn100	Size 0603 0805	Inductance Expressed in nH (2 significant digits + number of zeros) for values <10nH, letter R denotes decimal point. Example: 22nH = 220 4.7nH = 4R7	Tolerance for $L \leq 4.7\text{nH}$, B = $\pm 0.1\text{nH}$ C = $\pm 0.2\text{nH}$ D = $\pm 0.5\text{nH}$ $4.7\text{nH} < L < 10\text{nH}$, C = $\pm 0.2\text{nH}$ D = $\pm 0.5\text{nH}$ $L \geq 10\text{nH}$, G = $\pm 2\%$ J = $\pm 5\%$	Specification Code E = Accu-L® 0805 technology G = Accu-L® 0603 technology	Termination Code W = Nickel/ solder coated (Sn 63, Pb 37) **S= Nickel/Lead Free Solder coated (Sn100)	Packaging Code TR = Tape and Reel (3,000/reel)
Not RoHS Compliant LEAD-FREE LEAD-FREE COMPATIBLE COMPONENT RoHS COMPLIANT		**RoHS compliant Engineering Kits Available see pages 118-119				

For RoHS compliant products,
please select correct termination style.

ELECTRICAL SPECIFICATIONS TABLE FOR ACCU-L® 0603

450 MHz Test Frequency			900 MHz Test Frequency		1900 MHz Test Frequency		2400 MHz Test Frequency		SRF min. (MHz)	R _{DC} max. (Ω)	I _{DC} max. (mA) (1)
Inductance L (nH)	Available Inductance Tolerance	Q Typical	L (nH)	Q Typical	L (nH)	Q Typical	L (nH)	Q Typical			
1.2	$\pm 0.1, \pm 0.2\text{nH}$	49	1.2	70	1.2	134	1.2	170	10000	0.04	1000
1.5	$\pm 0.1, \pm 0.2\text{nH}$	26	1.54	39	1.52	63	1.52	76	10000	0.06	1000
1.8	$\pm 0.1, \pm 0.2\text{nH}$	20	1.74	30	1.73	50	1.72	59	10000	0.07	1000
2.2	$\pm 0.1, \pm 0.2\text{nH}$	20	2.2	30	2.24	49	2.24	56	10000	0.08	1000
2.7	$\pm 0.1, \pm 0.2\text{nH}$	21	2.7	30	2.75	48	2.79	54	9000	0.08	750
3.3	$\pm 0.1, \pm 0.2, \pm 0.5\text{nH}$	24	3.33	35	3.39	56	3.47	64	8400	0.08	750
3.9	$\pm 0.1, \pm 0.2, \pm 0.5\text{nH}$	25	3.9	57	4.06	60	4.21	69	6500	0.12	500
4.7	$\pm 0.1, \pm 0.2, \pm 0.5\text{nH}$	23	4.68	32	4.92	46	5.2	49	5500	0.15	500
5.6	$\pm 0.2, \pm 0.5\text{nH}$	26	5.65	36	5.94	54	6.23	60	5000	0.25	300
6.8	$\pm 0.2, \pm 0.5\text{nH}$	23	6.9	33	7.3	47	8.1	39	4500	0.30	300
8.2	$\pm 0.2, \pm 0.5\text{nH}$	23	8.4	31	10	35	12.1	31	3800	0.35	300
10.0	$\pm 2\%, \pm 5\%$	28	10	39	11.8	47	14.1	41	3500	0.45	300
12.0	$\pm 2\%, \pm 5\%$	28	13.2	38	14.1	30	17.2	20	3000	0.50	300
15.0	$\pm 2\%, \pm 5\%$	28	16.2	38	25.9	30	49.8	15	2500	0.60	300

(1) IDC measured for 15°C rise at 25°C ambient temperature when soldered to FR-4 board.
Inductance and Q measured on Agilent 4291B / 4287 using the 16196A test fixture.

ELECTRICAL SPECIFICATIONS TABLE FOR ACCU-L® 0805

450 MHz Test Frequency			900 MHz Test Frequency		1900 MHz Test Frequency		2400 MHz Test Frequency		SRF min. (MHz)	R _{DC} max. (Ω)	I _{DC} max. (mA)	
Inductance L (nH)	Available Inductance Tolerance	Q Typical	L (nH)	Q Typical	L (nH)	Q Typical	L (nH)	Q Typical			T = 15°C (1)	T = 70°C (2)
1.2	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	60	1.2	92	1.2	122	1.2	92	10000	0.05	1000	2000
1.5	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	50	1.5	74	1.5	102	1.5	84	10000	0.05	1000	2000
1.8	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	50	1.8	72	1.8	88	1.9	73	10000	0.06	1000	2000
2.2	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	42	2.2	62	2.2	82	2.3	72	10000	0.07	1000	2000
2.7	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	42	2.7	62	2.8	80	2.9	70	10000	0.08	1000	2000
3.3	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	38	3.3	46	3.4	48	3.5	57	10000	0.11	750	1500
3.9	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	27	3.9	36	4.0	38	4.1	42	10000	0.20	750	1500
4.7	$\pm 0.1\text{nH}, \pm 0.2\text{nH}, \pm 0.5\text{nH}$	43	4.8	62	5.3	76	5.8	60	5500	0.10	750	1500
5.6	$\pm 0.5\text{nH}$	50	5.7	68	6.3	73	7.6	62	4600	0.10	750	1500
6.8	$\pm 0.5\text{nH}$	43	7.0	62	7.7	71	9.4	50	4500	0.11	750	1500
8.2	$\pm 0.5\text{nH}$	43	8.5	56	10.0	55	15.2	32	3500	0.12	750	1500
10	$\pm 2\%, \pm 5\%$	46	10.6	60	13.4	52	–	–	2500	0.13	750	1500
12	$\pm 2\%, \pm 5\%$	40	12.9	50	17.3	40	–	–	2400	0.20	750	1500
15	$\pm 2\%, \pm 5\%$	36	16.7	46	27	23	–	–	2200	0.20	750	1000
18	$\pm 2\%, \pm 5\%$	30	21.9	27	–	–	–	–	1700	0.35	500	1000
22	$\pm 2\%, \pm 5\%$	36	27.5	33	–	–	–	–	1400	0.40	500	1000

(1) I_{DC} measured for 15°C rise at 25°C ambient temperature
(2) I_{DC} measured for 70°C rise at 25°C ambient temperature

L, Q, SRF measured on HP 4291A, Boonton 34A and Wilitron 360 Vector Analyzer, RDC measured on Keithley 580 micro-ohmmeter.

Thin-Film RF/Microwave Inductor Technology


Accu-L® Series

L0603 AND L0805 SMD High-Q RF Inductor – Accu-L®




L0603

Typical Q vs. Frequency
L0603



Measured on AGILENT 4291B/4287
using the 16196A test fixture


Typical Inductance vs. Frequency
L0603



Measured on AGILENT 4291B/4287
using the 16196A test fixture


L0805

Typical Q vs. Frequency
L0805




Measured on HP4291A and
Boonton 34A Coaxial Line

Typical Inductance vs. Frequency
L0805



Measured on HP4291A and
Wiltron 360 Vector Analyzer

Maximum Temperature Rise
at 25°C ambient temperature (on FR-4)
L0805



Temperature rise will typically be no higher than shown by the graph



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.