




Typical Application Circuit



Function Block Diagram



Functional Pin Description

| Pin Name | Pin Function              |
|----------|---------------------------|
| VIN      | Power Input               |
| VOUT     | Output Voltage            |
| GND      | Ground                    |
| EN/EN    | Chip Enable Control Input |

Absolute Maximum Ratings (Note 1)

- Input Voltage ----- 7V
- Power Dissipation,  $P_D$  @  $T_A = 25^{\circ}C$ 
  - SOT-23-3 ----- 0.4W
  - SOT-23-5 ----- 0.4W
  - SOT-89 ----- 0.571W
  - TO-92 ----- 0.625W
- Junction Temperature -----  $150^{\circ}C$
- Lead Temperature (Soldering, 10 sec.) -----  $260^{\circ}C$
- Storage Temperature Range -----  $-65^{\circ}C$  to  $150^{\circ}C$
- Package Thermal Resistance (Note 2)
  - SOT-23-3,  $\theta_{JA}$  -----  $250^{\circ}C/W$
  - SOT-23-5,  $\theta_{JA}$  -----  $250^{\circ}C/W$
  - SOT-89,  $\theta_{JA}$  -----  $175^{\circ}C/W$
  - TO-92,  $\theta_{JA}$  -----  $160^{\circ}C/W$
- ESD Susceptibility (Note 3)
  - HBM (Human Body Mode) ----- 2kV
  - MM (Machine Mode) ----- 200V

Recommended Operating Conditions (Note 4)

- Junction Temperature Range -----  $-40^{\circ}C$  to  $125^{\circ}C$
- Ambient Temperature Range -----  $-40^{\circ}C$  to  $85^{\circ}C$

## Electrical Characteristics

( $V_{IN} = 5.5V$ ,  $C_{IN} = 1\mu F$ ,  $C_{OUT} = 1\mu F$ ,  $T_A = 25^\circ C$ , unless otherwise specified)

| Parameter                   | Symbol              | Test Conditions                                                               | Min  | Typ  | Max  | Unit       |
|-----------------------------|---------------------|-------------------------------------------------------------------------------|------|------|------|------------|
| Input Voltage Range         | $V_{IN}$            |                                                                               | 2    | --   | 6    | V          |
| Output Voltage Accuracy     | $\Delta V_{OUT}$    | $I_L = 1mA$                                                                   | -2   | --   | +2   | %          |
| Maximum Output Current      | $I_{MAX}$           | $V_{IN} = V_{OUT} + 0.6V$ , $V_{IN} \geq 3.6V$                                | 100  | --   | --   | mA         |
| Current Limit               | $I_{LIM}$           | $I_L = 100mA$                                                                 | 150  | 250  | --   | mA         |
| GND Pin Current             | $I_G$               | No Load                                                                       | --   | 4    | 7    | $\mu A$    |
|                             |                     | $I_{OUT} = 100mA$                                                             |      | 4    | 10   | $\mu A$    |
| Dropout Voltage             | $V_{DROP}$          | $I_{OUT} = 1mA$ , $V_{IN} \geq 3.6V$                                          | --   | 4    | 10   | mV         |
|                             |                     | $I_{OUT} = 50mA$ , $V_{IN} \geq 3.6V$                                         | --   | 200  | 300  |            |
|                             |                     | $I_{OUT} = 100mA$ , $V_{IN} \geq 3.6V$                                        | --   | 450  | 600  |            |
| Line Regulation             | $\Delta V_{LINE}$   | $V_{IN} = (V_{OUT} + 0.3V)$ to $6V$ ,<br>$V_{IN} \geq 3.6V$ , $I_{OUT} = 1mA$ | -0.2 | --   | +0.2 | %/V        |
| Load Regulation             | $\Delta V_{LOAD}$   | $I_{LOAD} = 0mA$ to $100mA$                                                   | --   | 0.01 | 0.04 | %/mA       |
| Output Noise                | $e_{NO}$            | BW = 100Hz to 50kHz<br>$C_{OUT} = 10\mu F$                                    | --   | 250  | --   | $\mu V$    |
| Ripple Rejection            | PSRR                | $F = 1kHz$ , $C_{OUT} = 1\mu F$                                               | --   | 30   | --   | dB         |
| Standby Current             | RT9169/H (SOT-23-5) | $\overline{EN} = V_{IN}$ or $EN = 0$                                          | --   | 0.1  | 1    | $\mu A$    |
| EN/EN Threshold             | Logic High          | $V_{IL}$                                                                      | 0.6  | --   | --   | V          |
|                             | Logic Low           | $V_{IH}$                                                                      | --   | --   | 2    |            |
| Thermal Shutdown Protection |                     |                                                                               | 125  | --   | --   | $^\circ C$ |

**Note 1.** Stresses listed as the above "Absolute Maximum Ratings" may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.

**Note 2.**  $\theta_{JA}$  is measured in the natural convection at  $T_A = 25^\circ C$  on a low effective thermal conductivity test board of JEDEC 51-3 thermal measurement standard.

**Note 3.** Devices are ESD sensitive. Handling precaution is highly recommended.

**Note 4.** The device is not guaranteed to function outside its operating conditions.


## Application Information

A  $1\mu F$  (or larger) capacitor is recommended between  $V_{OUT}$  and GND for stability. The part may oscillate without the capacitor. Any type of capacitor can be used, but not Aluminum electrolytes when operating below  $-25^\circ C$ . The capacitance may be increased without limit.


A  $1\mu F$  capacitor (or larger) should be placed between  $V_{IN}$  to GND.

## Typical Operating Characteristics


### Temperature Stability




### Quiescent Current vs. Temperature




### Dropout Voltage ( $V_{IN} - V_{OUT}$ )




### Short Circuit Current




### PSRR




### PSRR




Line Transient Response




Line Transient Response




Load Transient Response




Load Transient Response




Load Transient Response



Load Transient Response




## Outline Dimension




| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 0.889                     | 1.295 | 0.035                | 0.051 |
| A1     | 0.000                     | 0.152 | 0.000                | 0.006 |
| B      | 1.397                     | 1.803 | 0.055                | 0.071 |
| b      | 0.356                     | 0.508 | 0.014                | 0.020 |
| C      | 2.591                     | 2.997 | 0.102                | 0.118 |
| D      | 2.692                     | 3.099 | 0.106                | 0.122 |
| e      | 1.803                     | 2.007 | 0.071                | 0.079 |
| H      | 0.080                     | 0.254 | 0.003                | 0.010 |
| L      | 0.300                     | 0.610 | 0.012                | 0.024 |

SOT-23-3 Surface Mount Package




| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 0.889                     | 1.295 | 0.035                | 0.051 |
| A1     | 0.000                     | 0.152 | 0.000                | 0.006 |
| B      | 1.397                     | 1.803 | 0.055                | 0.071 |
| b      | 0.356                     | 0.559 | 0.014                | 0.022 |
| C      | 2.591                     | 2.997 | 0.102                | 0.118 |
| D      | 2.692                     | 3.099 | 0.106                | 0.122 |
| e      | 0.838                     | 1.041 | 0.033                | 0.041 |
| H      | 0.080                     | 0.254 | 0.003                | 0.010 |
| L      | 0.300                     | 0.610 | 0.012                | 0.024 |

**SOT-23-5 Surface Mount Package**



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 1.397                     | 1.600 | 0.055                | 0.063 |
| b      | 0.356                     | 0.483 | 0.014                | 0.019 |
| B      | 2.388                     | 2.591 | 0.094                | 0.102 |
| b1     | 0.406                     | 0.533 | 0.016                | 0.021 |
| C      | 3.937                     | 4.242 | 0.155                | 0.167 |
| C1     | 0.787                     | 1.194 | 0.031                | 0.047 |
| D      | 4.394                     | 4.597 | 0.173                | 0.181 |
| D1     | 1.397                     | 1.753 | 0.055                | 0.069 |
| e      | 1.448                     | 1.549 | 0.057                | 0.061 |
| H      | 0.356                     | 0.432 | 0.014                | 0.017 |

### 3-Lead SOT-89 Surface Mount Package



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min                       | Max   | Min                  | Max   |
| A      | 3.175                     | 4.191 | 0.125                | 0.165 |
| A1     | 1.143                     | 1.372 | 0.045                | 0.054 |
| b      | 0.406                     | 0.533 | 0.016                | 0.021 |
| C      | 0.406                     | 0.533 | 0.016                | 0.021 |
| D      | 4.445                     | 5.207 | 0.175                | 0.205 |
| D1     | 3.429                     | 5.029 | 0.135                | 0.198 |
| E      | 4.318                     | 5.334 | 0.170                | 0.210 |
| e      | 1.143                     | 1.397 | 0.045                | 0.055 |
| L      | 12.700                    |       | 0.500                |       |

### 3-Lead TO-92 Plastic Package

#### Richtek Technology Corporation

Headquarter

5F, No. 20, Taiyuen Street, Chupei City

Hsinchu, Taiwan, R.O.C.

Tel: (8863)5526789 Fax: (8863)5526611

#### Richtek Technology Corporation

Taipei Office (Marketing)

5F, No. 95, Minchiuan Road, Hsintien City

Taipei County, Taiwan, R.O.C.

Tel: (8862)86672399 Fax: (8862)86672377

Email: marketing@richtek.com

Information that is provided by Richtek Technology Corporation is believed to be accurate and reliable. Richtek reserves the right to make any change in circuit design, specification or other related things if necessary without notice at any time. No third party intellectual property infringement of the applications should be guaranteed by users when integrating Richtek products into any application. No legal responsibility for any said applications is assumed by Richtek.