

2N5681, 2N5682 JAN SERIES

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
-----------------	--------	------	------	------

ON CHARACTERISTICS ⁽³⁾

Forward Current Transfer Ratio $I_C = 250 \text{ mAdc}, V_{CE} = 2.0 \text{ Vdc}$ $I_C = 500 \text{ mAdc}, V_{CE} = 2.0 \text{ Vdc}$ $I_C = 1.0 \text{ Adc}, V_{CE} = 2.0 \text{ Vdc}$	h_{FE}	40 20 5	150	
Collector-Emitter Saturation Voltage $I_C = 250 \text{ mAdc}, I_B = 25 \text{ mAdc}$ $I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$	$V_{CE(sat)}$		0.6 1.0	Vdc
Base-Emitter Saturation Voltage $I_C = 250 \text{ mAdc}, I_B = 25 \text{ mAdc}$ $I_C = 500 \text{ mAdc}, I_B = 50 \text{ mAdc}$	$V_{BE(sat)}$		1.1 1.3	Vdc

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short Circuit Forward-Current Transfer Ratio $I_C = 0.1 \text{ Adc}, V_{CE} = 10 \text{ Vdc}, f = 10 \text{ kHz}$	$ h_{fe} $	3.0		
Small Signal Short Circuit Forward-Current Transfer Ratio $I_C = 0.2 \text{ Adc}, V_{CE} = 1.5 \text{ Vdc}, f = 1.0 \text{ kHz}$	h_{fe}	40		
Output Capacitance $V_{CB} = 20 \text{ Vdc}, I_E = 0, f = 1 \text{ MHz}$	C_{obo}		50	pF

SAFE OPERATING AREA

DC Tests

$T_C = +25^\circ\text{C}$, 1 Cycle, $t \geq 0.5 \text{ s}$

Test 1

$V_{CE} = 2 \text{ Vdc}, I_C = 1.0 \text{ Adc}$

Test 2

$V_{CE} = 10 \text{ Vdc}, I_C = 1.0 \text{ Adc}$

Test 3

$V_{CE} = 90 \text{ Vdc}, I_C = 50 \text{ mAdc}$