

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Environmental Compliance

TE Material Declaration

MD_5-147292-3_02102012130

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Connector & Contact Terminates To Printed Circuit Board
- Connector Style Plug
- Header Type Breakaway
- PCB Mounting Orientation Vertical
- Connector Type Header
- Row-to-Row Spacing 2.54 mm [.1 in]
- Gasket Without
- Product Type Connector
- Stabilizers Without
- Board Standoff Without
- Strain Relief Without

Configuration Features

- Selectively Loaded No
- Number of Positions 4
- Number of Rows 2
- Keyed No

Electrical Characteristics

- Dielectric Withstanding Voltage 750 V

Body Features

- Post Size .64 mm [.025 in]

Contact Features

Solder Tail Contact Plating Material Tin-Lead over Nickel

Contact Protection Without

Contact Shape Square

Contact Base Material Copper Alloy

Contact Mating Area Plating Thickness (μin) 100 – 200

Contact Type Pin

Contact Mating Area Plating Material Tin

Termination Features

Termination Method to PC Board Surface Mount

Termination Post Length (in) .05

Termination End Plating Thickness (μin) 100 – 200

Termination End Plating Material Tin

Mechanical Attachment

Panel Mount Feature Without

Mating Connector Lock Without

PCB Mounting Style Surface Mount

PCB Mount Retention Without

Mating Alignment Without

Housing Features

Centerline (Pitch) 2.54 mm [.1 in]

Housing Material LCP (Liquid Crystal Polymer), LCP-GF (Liquid Crystal Polymer)

Housing Color Black

Dimensions

Mating Post Length 5.84 mm [.23 in]

Usage Conditions

Operating Temperature Range (°C) -65 – 105

High Temperature Compatible Yes

High Temperature Housing Yes

Operation/Application

High Speed Serial Data Connector No

Industry Standards

Approved Standards CSA LR7189, UL E28476

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity 250

Packaging Reel Diameter (mm) 24

Packaging Method Tape & Reel

Other

Comment Includes Pick & Place Cap



Statement of Compliance

Statement of Compliance

PDF

