

TABLE OF CONTENTS

| | |
|--------------------------------|---|
| Features | 1 |
| Applications | 1 |
| General Description | 1 |
| Functional Block Diagram | 1 |
| Revision History | 2 |
| Specifications | 3 |
| Absolute Maximum Ratings | 4 |
| Thermal Resistance | 4 |
| ESD Caution | 4 |

REVISION HISTORY

11/2019—Rev. B to Rev. C

| | |
|----------------------------|---|
| Changes to Figure 12 | 9 |
|----------------------------|---|

11/2016—Rev. A to Rev. B

| | |
|---|----|
| Change to Serial Port Timing Section and Time From BCLK Falling Parameter; Table 7 | 10 |
| Changes to Figure 19 Caption and Figure 21 Caption | 12 |

| | |
|---|----|
| Pin Configuration and Function Descriptions | 5 |
| Typical Performance Characteristics | 6 |
| Typical Application Circuit | 8 |
| Applications Information | 9 |
| Overview | 9 |
| Clocking | 9 |
| Serial Audio Output Interface | 9 |
| Outline Dimensions | 13 |
| Ordering Guide | 13 |

7/2013—Rev. 0 to Rev. A

| | |
|--|----|
| Changes to Supply Current Test Conditions/Comments | 3 |
| Changes to Figure 5 | 6 |
| Added Figure 6; Renumbered Sequentially | 6 |
| Changes to Figure 14 and Figure 15 | 10 |
| Changes to Figure 16, Figure 17, and Figure 18 | 11 |
| Changes to Figure 19, Figure 20, and Figure 21 | 12 |

1/2013—Revision 0: Initial Version

SPECIFICATIONS

IOVDD = 1.8 V, T_A = 25°C, BCLK = 3.072 MHz, output = 48 kHz, I²S format, unless otherwise noted.

Table 1.

| Parameter | Test Conditions/Comments | Min | Typ | Max | Unit |
|---|---------------------------------------|-------|-------------|--------|----------------|
| DIGITAL INPUT/OUTPUT | | | | | |
| High Level Input Voltage (V _{IH}) | | | 0.7 × IOVDD | | V |
| Low Level Input Voltage (V _{IL}) | | | 0.3 × IOVDD | | V |
| Input Leakage, High (I _{IH}) | BCLK and LRCLK pins | | | 1 | μA |
| Input Leakage, Low (I _{IL}) | BCLK and LRCLK pins | | | 1 | μA |
| Input Capacitance | | | | 5 | pF |
| SDATA | | | 4.5 | | mA |
| PDM_CLK | | | 9 | | mA |
| PERFORMANCE | | | | | |
| Dynamic Range | 20 Hz to 20 kHz, –60 dB input | | 110 | | dB |
| With A-Weighted Filter (RMS) | | | 110 | | dB |
| Signal-to-Noise-Ratio | A-weighted, fourth-order input | | 64× | | |
| Decimation Ratio | | | | | |
| Frequency Response | DC to 0.45 output f _s | –0.1 | | +0.01 | dB |
| Stop Band | | | 0.566 | | f _s |
| Stop-Band Attenuation | | 60 | | | dB |
| Group Delay | 0.02 f _s input signal | | 3.31 | | LRCLK cycles |
| Gain | PDM to PCM | | 0 | | dB |
| Start-Up Time | | | 48 | | LRCLK cycles |
| Bit Width | Internal and output | | 20 | | Bits |
| Interchannel Phase | | | 0 | | Degrees |
| CLOCKING | | | | | |
| Output Sampling Rate | f _s LRCLK pulse rate | 4 | 48 | 96 | kHz |
| BCLK Frequency | f _{BCLK} | 0.256 | 3.072 | 24.576 | MHz |
| POWER SUPPLIES | | | | | |
| Supply Voltage Range | IOVDD | 1.62 | | 3.6 | V |
| Supply Current | IOVDD = 1.8 V | | 0.67 | | mA |
| | IOVDD = 3.3 V | | 1.33 | | mA |
| | IOVDD = 1.8 V, 16 kHz output | | 0.21 | | mA |
| | IOVDD = 3.3 V, 16 kHz output | | 0.41 | | mA |
| Shutdown Current | IOVDD _{SD} , no input clocks | | 1 | | μA |

ABSOLUTE MAXIMUM RATINGS

Absolute maximum ratings apply at 25°C, unless otherwise noted.

Table 2.

| Parameter | Rating |
|--------------------------------------|-----------------|
| IOVDD Supply Voltage | 3.6 V |
| Input Voltage | 3.6 V |
| ESD Susceptibility | 4 kV |
| Storage Temperature Range | –65°C to +150°C |
| Operating Temperature Range | –40°C to +85°C |
| Junction Temperature Range | –65°C to +165°C |
| Lead Temperature (Soldering, 60 sec) | 300°C |

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

THERMAL RESISTANCE

θ_{JA} (junction to air) is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages. θ_{JA} is determined according to JESD51-9 on a 4-layer printed circuit board (PCB) with natural convection cooling.

Table 3. Thermal Resistance

| Package Type | θ_{JA} | Unit |
|---------------------------------|---------------|------|
| 8-ball, 1.56 mm × 0.76 mm WLCSP | 90 | °C/W |

ESD CAUTION



ESD (electrostatic discharge) sensitive device.

Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 2. Pin Configuration (Top Side View)

Table 4. Pin Function Descriptions

| Pin No. | Mnemonic | Type | Description |
|---------|----------|--------|--|
| A1 | PDM_DAT | Input | PDM Data Input |
| A2 | PDM_CLK | Output | PDM Clock Output |
| B1 | SDATA | Output | Serial Data Output for I ² S/TDM |
| B2 | BCLK | Input | Bit Clock for I ² S/TDM |
| C1 | GND | Ground | Ground |
| C2 | LRCLK | Input | Left/Right Clock for I ² S/Frame Sync for TDM |
| D1 | IOVDD | Supply | Input/Output and Digital Supply |
| D2 | CONFIG | Input | Configuration Pin |

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 3. FFT, $f_s = 48$ kHz, -60 dBFS Input




Figure 6. Group Delay vs. Frequency, $f_s = 48$ kHz




Figure 4. Frequency Response




Figure 7. Total Harmonic Distortion + Noise (THD + N) vs. Normalized Frequency (Relative to f_s)




Figure 5. Group Delay vs. Normalized Frequency (Relative to f_s)




Figure 8. THD + N Level vs. Generator Level




Figure 9. Supply Current vs. Supply Voltage




Figure 10. Out-of-Band Frequency Response (48 kHz Output)

TYPICAL APPLICATION CIRCUIT




Figure 11. Typical Application Circuit

11265-011

APPLICATIONS INFORMATION

OVERVIEW

The [ADAU7002](#) provides stereo decimation from a 1-bit PDM source to a 20-bit PCM audio. The downsampling ratio is fixed at 64×. The 20-bit downsampled PCM audio is output via standard I²S or TDM formats.

The input source for the [ADAU7002](#) can be any device that has a PDM output, such as a digital microphone. The output pins of these microphones can connect directly to the input pins of the [ADAU7002](#).

CLOCKING

The [ADAU7002](#) requires a BCLK rate that is a minimum of 64× the LRCLK sample rate. BCLK rates of 128×, 192×, 256×, 384×, and 512× the LRCLK rate are also supported. The [ADAU7002](#) automatically detects the ratio between BCLK and LRCLK and generates a PDM clock output at 64× the LRCLK rate. The minimum sample rate is 4 kHz, and the maximum is 96 kHz, which correspond to a PDM clock range of 256 kHz to 6.144 MHz. Internally, all processing is done at the PDM_CLK rate.

When BCLK is removed, the [ADAU7002](#) powers down automatically. When BCLK is not present, the PDM_CLK output stops.

Table 5. PDM Timing Parameters

| Parameter | t _{MIN} | t _{MAX} | Unit |
|-------------------------------------|------------------|------------------|------|
| Data Setup Time, t _{SETUP} | 10 | | ns |
| Data Hold Time, t _{HOLD} | 7 | | ns |

PDM data is latched on both edges of the clock.




Figure 12. PDM Timing Diagram

SERIAL AUDIO OUTPUT INTERFACE

The [ADAU7002](#) supports I²S and TDM serial output formats. Format selection and TDM slot placement is set with the CONFIG pin. The SDATA pin is in tristate mode, except when the port is driving serial data based on the CONFIG pin configuration.

Table 6. TDM Slot Selection

| Device Setting | CONFIG Pin Configuration |
|--|---------------------------------------|
| I ² S Format | Tie to IOVDD |
| TDM Slot 1 to Slot 2 Used/Driven, 32-Bit Slots | Tie to GND |
| TDM Slot 3 to Slot 4 Used/Driven, 32-Bit Slots | Open |
| TDM Slot 5 to Slot 6 Used/Driven, 32-Bit Slots | Tie to IOVDD through a 47 kΩ resistor |
| TDM Slot 7 to Slot 8 Used/Driven, 32-Bit Slots | Tie to GND through a 47 kΩ resistor |

Serial Port Timing




Figure 13. Serial Port Timing Diagram

IOVDD = 1.62 V to 3.63 V, load capacitance = 25 pF, unless otherwise noted.

Table 7. I²S/TDM Timing Parameters

| Parameter | Symbol | t _{MIN} | t _{MAX} | Unit |
|------------------------|-------------------|------------------|------------------|------|
| BCLK Pulse Width High | t _{BIH} | 10 | | ns |
| BCLK Pulse Width Low | t _{BIL} | 10 | | ns |
| LRCLK Setup Time | t _{LIS} | 10 | | ns |
| LRCLK Hold Time | t _{LIH} | 10 | | ns |
| Time from BCLK Falling | t _{SODM} | | 18 | ns |




Figure 14. I²S, CONFIG Pin Tied to IOVDD




Figure 15. TDM8 Channel 1 and Channel 2, CONFIG Pin Tied to GND




Figure 16. TDM8 Channel 3 and Channel 4, CONFIG Pin Open

11265-016




Figure 17. TDM8 Channel 5 to Channel 6, CONFIG Pin Tied to IOVDD Through a 47 kΩ Resistor

11265-017




Figure 18. TDM8 Channel 7 and Channel 8, CONFIG Pin Tied to GND Through a 47 kΩ Resistor

11265-018




Figure 19. TDM4 Channel 1 and Channel 2, CONFIG Pin Tied to GND




Figure 20. TDM4 Channel 3 and Channel 4, CONFIG Pin Open




Figure 21. TDM2 Channel 1 and Channel 2, CONFIG Pin Tied to GND

OUTLINE DIMENSIONS




Figure 22. 8-Ball Wafer Level Chip Scale Package [WLCSP]
(CB-8-6)

Dimensions shown in millimeters

10-18-2016-A

ORDERING GUIDE

| Model ¹ | Temperature Range | Package Description | Package Option | Marking Code |
|--------------------|-------------------|--|----------------|--------------|
| ADAU7002ACBZ-R7 | −40°C to +85°C | 8-Ball Wafer Level Chip Scale Package [WLCSP], 7" Tape and Reel | CB-8-6 | BE |
| ADAU7002ACBZ-RL | −40°C to +85°C | 8-Ball Wafer Level Chip Scale Package [WLCSP], 13" Tape and Reel | CB-8-6 | BE |
| EVAL-ADAU7002Z | | Evaluation Board | | |

¹ Z = RoHS Compliant Part.

NOTES

NOTES

NOTES