



1825027-8 Product Details

Share

Print

Email

1825027-8

TE Internal Number: 1825027-8

Active

View 3D PDF

Pushbutton Switches

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

• Switch

• Tactile

• Single Pole - Single Throw Configuration (Pole-Throw)

• Contact Rating = 50mA

• Operating Function = Off [On]

View all Features

Quick Links

▶ Pricing & Availability

▶ Search for Tooling

▶ Product Feature Selector

▶ Contact Us About This Product

Add to My Part List

Request Sample

Find Similar Products

Buy Product

Documentation & Additional Information

- Product Drawings:

• MICRO-MINIATURE PUSHBUTTON SWITCH (PDF, English)
- Catalog Pages/Data Sheets:

• SWITCHES\_CORE\_PROGRAM\_CATALOG (PDF, English)
- Product Specifications:

• None Available
- Application Specifications:

• None Available
- Instruction Sheets:

• None Available
- CAD Files: (CAD Format & Compression Information)

• 2D Drawing (DXF, Version G1)

• 3D Model (IGES, Version G1)

• 3D Model (STEP, Version G1)

- Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

- Product Type Features:

• Product Type = Switch

• Mount Angle = Right Angle

• Actuator Style = Round

Electrical Characteristics:

• Contact Rating = 50mA

Termination Features:

• Termination Type = Printed Circuit

Dimensions:

• Actuator Length (mm [in]) = 3.25 [0.128]

• Switch Height (mm [in]) = 7.00 [0.276]

Body Features:

• Mount Style = Through-Hole

• Actuator Profile = Extended

• Actuator Color = Blue

• Case Material = Nylon

• Actuator Material = PBT

Contact Features:

• Contact Plating = Silver

• Contact Base Material = Copper Alloy

Housing Features:

• Process Sealed = No

• Low Profile = No
- Configuration Features:

• Tactile = Yes

• Configuration (Pole-Throw) = Single Pole - Single Throw

• Operating Function = Off [On]

• Ganged = No

• ESD Grounding Terminal = Without

• Number of Actuators = Single

• Illuminated = No

• Dust Proof = No

• Support Bracket = With

• Snap Action = Without

• Tactile Feel = With

Industry Standards:

• RoHS/ELV Compliance = RoHS compliant, ELV compliant

• Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

• RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Temperature Rating = Standard

Operation/Application:

• Actuator Force (g [oz]) = 160.00 [5.648]

Packaging Features:

• Packaging Method = Loose Piece/Bulk

Other:

• Series = FSMRAJ

• Brand = TE Connectivity

• Comment = (On) indicates momentary position.

Corporate Information

About TE

Investors

News Room

Supplier Portal

Careers

Terms & Conditions

Privacy Policy

Quick Links

Distributor Inventory

Product Cross Reference

Documents & Drawings

Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us

Find a Phone Number

Knowledge Base

Manage Your Account

Keep Me Informed

