



## PIN CONFIGURATION

36-pin mini BGA (B) (6mm x 8mm)




32-pin TSOP (TYPE I) (T),  
32-pin sTSOP (TYPE I) (H)



## PIN DESCRIPTIONS

|                  |                     |
|------------------|---------------------|
| A0-A16           | Address Inputs      |
| $\overline{CS1}$ | Chip Enable 1 Input |
| CS2              | Chip Enable 2 Input |
| $\overline{OE}$  | Output Enable Input |
| $\overline{WE}$  | Write Enable Input  |
| I/O0-I/O7        | Input/Output        |
| NC               | No Connection       |
| V <sub>DD</sub>  | Power               |
| GND              | Ground              |

32-pin SOP (Q)



# IS62WV1288DALL/DBLL IS65WV1288DALL/DBLL

## TRUTH TABLE

| Mode            | $\overline{WE}$ | $\overline{CS1}$ | CS2 | $\overline{OE}$ | I/O Operation    | V <sub>DD</sub> Current             |
|-----------------|-----------------|------------------|-----|-----------------|------------------|-------------------------------------|
| Not Selected    | X               | H                | X   | X               | High-Z           | I <sub>SB1</sub> , I <sub>SB2</sub> |
| (Power-down)    | X               | X                | L   | X               | High-Z           | I <sub>SB1</sub> , I <sub>SB2</sub> |
| Output Disabled | H               | L                | H   | H               | High-Z           | I <sub>CC</sub>                     |
| Read            | H               | L                | H   | L               | D <sub>OUT</sub> | I <sub>CC</sub>                     |
| Write           | L               | L                | H   | X               | D <sub>IN</sub>  | I <sub>CC</sub>                     |

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

| Symbol            | Parameter                            | Value                         | Unit |
|-------------------|--------------------------------------|-------------------------------|------|
| V <sub>TERM</sub> | Terminal Voltage with Respect to GND | −0.5 to V <sub>DD</sub> + 0.5 | V    |
| V <sub>DD</sub>   | V <sub>DD</sub> Relates to GND       | −0.3 to 4.0                   | V    |
| T <sub>STG</sub>  | Storage Temperature                  | −65 to +150                   | °C   |
| P <sub>T</sub>    | Power Dissipation                    | 1.0                           | W    |

### Notes:

1. Stress greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

## CAPACITANCE<sup>(1,2)</sup>

| Symbol           | Parameter                | Conditions            | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|
| C <sub>IN</sub>  | Input Capacitance        | V <sub>IN</sub> = 0V  | 6    | pF   |
| C <sub>I/O</sub> | Input/Output Capacitance | V <sub>OUT</sub> = 0V | 8    | pF   |

### Notes:

1. Tested initially and after any design or process changes that may affect these parameters.
2. Test conditions: T<sub>A</sub> = 25°C, f = 1 MHz, V<sub>DD</sub> = 3.3V.



AC TEST CONDITIONS

| Parameter  | Unit<br>(2.3V-3.6V)            | Unit<br>(3.3V ± 5%)            | Unit<br>(1.65V-2.2V)           |
|--|--------------------------------|--------------------------------|--------------------------------|
| Input Pulse Level  | 0.4V to V <sub>DD</sub> - 0.3V | 0.4V to V <sub>DD</sub> - 0.3V | 0.4V to V <sub>DD</sub> - 0.3V |
| Input Rise and Fall Times  | 1V/ ns                         | 1V/ ns                         | 1V/ ns                         |
| Input and Output Timing<br>and Reference Level (V <sub>Ref</sub> ) | V <sub>DD</sub> /2             | $\frac{V_{DD}}{2} + 0.05$      | 0.9V                           |
| Output Load  | See Figures 1 and 2            | See Figures 1 and 2            | See Figures 1 and 2            |
| R1 ( $\Omega$ )  | 317                            | 317                            | 13500                          |
| R2 ( $\Omega$ )  | 351                            | 351                            | 10800                          |
| V <sub>TM</sub> (V)  | 3.3V                           | 3.3V                           | 1.8V                           |

AC TEST LOADS




Figure 1.




Figure 2.

# IS62WV1288DALL/DBLL

# IS65WV1288DALL/DBLL

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

**V<sub>DD</sub> = 3.3V ± 5%**

| Symbol          | Parameter                        | Test Conditions   | Min. | Max.                  | Unit |
|-----------------|----------------------------------|---|------|-----------------------|------|
| V <sub>OH</sub> | Output HIGH Voltage              | V <sub>DD</sub> = Min., I <sub>OH</sub> = -1 mA             | 2.4  | —                     | V    |
| V <sub>OL</sub> | Output LOW Voltage               | V <sub>DD</sub> = Min., I <sub>OL</sub> = 2.1 mA            | —    | 0.4                   | V    |
| V <sub>IH</sub> | Input HIGH Voltage               |   | 2    | V <sub>DD</sub> + 0.3 | V    |
| V <sub>IL</sub> | Input LOW Voltage <sup>(1)</sup> |   | -0.3 | 0.8                   | V    |
| I <sub>LI</sub> | Input Leakage                    | GND ≤ V <sub>IN</sub> ≤ V <sub>DD</sub>                     | -1   | 1                     | μA   |
| I <sub>LO</sub> | Output Leakage                   | GND ≤ V <sub>OUT</sub> ≤ V <sub>DD</sub> , Outputs Disabled | -1   | 1                     | μA   |

**Note:**

- V<sub>IL</sub> (min.) = -0.3V DC; V<sub>IL</sub> (min.) = -2.0V AC (pulse width < 10 ns). Not 100% tested.  
V<sub>IH</sub> (max.) = V<sub>DD</sub> + 0.3V DC; V<sub>IH</sub> (max.) = V<sub>DD</sub> + 2.0V AC (pulse width < 10 ns). Not 100% tested.

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

**V<sub>DD</sub> = 2.3V-3.6V**

| Symbol          | Parameter                        | Test Conditions   | Min. | Max.                  | Unit |
|-----------------|----------------------------------|---|------|-----------------------|------|
| V <sub>OH</sub> | Output HIGH Voltage              | V <sub>DD</sub> = Min., I <sub>OH</sub> = -1.0 mA           | 1.8  | —                     | V    |
| V <sub>OL</sub> | Output LOW Voltage               | V <sub>DD</sub> = Min., I <sub>OL</sub> = 2.1 mA            | —    | 0.4                   | V    |
| V <sub>IH</sub> | Input HIGH Voltage               |   | 2.0  | V <sub>DD</sub> + 0.3 | V    |
| V <sub>IL</sub> | Input LOW Voltage <sup>(1)</sup> |   | -0.3 | 0.8                   | V    |
| I <sub>LI</sub> | Input Leakage                    | GND ≤ V <sub>IN</sub> ≤ V <sub>DD</sub>                     | -1   | 1                     | μA   |
| I <sub>LO</sub> | Output Leakage                   | GND ≤ V <sub>OUT</sub> ≤ V <sub>DD</sub> , Outputs Disabled | -1   | 1                     | μA   |

**Note:**

- V<sub>IL</sub> (min.) = -0.3V DC; V<sub>IL</sub> (min.) = -2.0V AC (pulse width < 10 ns). Not 100% tested.  
V<sub>IH</sub> (max.) = V<sub>DD</sub> + 0.3V DC; V<sub>IH</sub> (max.) = V<sub>DD</sub> + 2.0V AC (pulse width < 10 ns). Not 100% tested.

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

**V<sub>DD</sub> = 1.65V-2.2V**

| Symbol                         | Parameter           | Test Conditions   | V <sub>DD</sub> | Min. | Max.                  | Unit |
|--------------------------------|---------------------|---|-----------------|------|-----------------------|------|
| V <sub>OH</sub>                | Output HIGH Voltage | I <sub>OH</sub> = -0.1 mA                                   | 1.65-2.2V       | 1.4  | —                     | V    |
| V <sub>OL</sub>                | Output LOW Voltage  | I <sub>OL</sub> = 0.1 mA                                    | 1.65-2.2V       | —    | 0.2                   | V    |
| V <sub>IH</sub>                | Input HIGH Voltage  |   | 1.65-2.2V       | 1.4  | V <sub>DD</sub> + 0.2 | V    |
| V <sub>IL</sub> <sup>(1)</sup> | Input LOW Voltage   |   | 1.65-2.2V       | -0.2 | 0.4                   | V    |
| I <sub>LI</sub>                | Input Leakage       | GND ≤ V <sub>IN</sub> ≤ V <sub>DD</sub>                     |                 | -1   | 1                     | μA   |
| I <sub>LO</sub>                | Output Leakage      | GND ≤ V <sub>OUT</sub> ≤ V <sub>DD</sub> , Outputs Disabled |                 | -1   | 1                     | μA   |

**Note:**

- V<sub>IL</sub> (min.) = -0.3V DC; V<sub>IL</sub> (min.) = -2.0V AC (pulse width < 10 ns). Not 100% tested.  
V<sub>IH</sub> (max.) = V<sub>DD</sub> + 0.3V DC; V<sub>IH</sub> (max.) = V<sub>DD</sub> + 2.0V AC (pulse width < 10 ns). Not 100% tested.

### OPERATING RANGE (V<sub>DD</sub>)

| Range      | Ambient Temperature | V <sub>DD</sub> | Speed |
|------------|---------------------|-----------------|-------|
| Commercial | 0°C to +70°C        | 1.65V-2.2V      | 45ns  |
| Industrial | -40°C to +85°C      | 1.65V-2.2V      | 55ns  |
| Automotive | -40°C to +125°C     | 1.65V-2.2V      | 55ns  |

### OPERATING RANGE (V<sub>DD</sub>)

| Range      | Ambient Temperature | V <sub>DD</sub> (45 ns) | V <sub>DD</sub> (35 ns) |
|------------|---------------------|-------------------------|-------------------------|
| Commercial | 0°C to +70°C        | 2.3V-3.6V               | 3.3V±5%                 |
| Industrial | -40°C to +85°C      | 2.3V-3.6V               | 3.3V±5%                 |

### OPERATING RANGE (V<sub>DD</sub>)

| Range      | Ambient Temperature | V <sub>DD</sub> (45 ns) |
|------------|---------------------|-------------------------|
| Automotive | -40°C to +125°C     | 2.3V-3.6V               |

### POWER SUPPLY CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)

| Symbol           | Parameter  | Test Conditions  |                     | -35  |      | -45  |      | -55  |      | Unit |
|------------------|--|--|---------------------|------|------|------|------|------|------|------|
|                  |  |  |                     | Min. | Max. | Min. | Max. | Min. | Max. |      |
| I <sub>CC</sub>  | V <sub>DD</sub> Dynamic Operating Supply Current | V <sub>DD</sub> = Max.,  | Com.                | —    | 8    | —    | 6    | —    | 5    | mA   |
|                  |  | I <sub>OUT</sub> = 0 mA, f = f <sub>MAX</sub>                          | Ind.                | —    | 12   | —    | 8    | —    | 7    |      |
|                  |  | $\overline{CS1} = V_{IL}$  | Auto.               | —    | 15   | —    | 12   | —    | 12   |      |
|                  |  | V <sub>IN</sub> ≥ V <sub>DD</sub> - 0.3V, or<br>V <sub>IN</sub> ≤ 0.4V | typ. <sup>(2)</sup> |      | 4    |      |      |      |      |      |
| I <sub>CC1</sub> | Operating Supply Current                         | V <sub>DD</sub> = Max.,  | Com.                | —    | 2.5  | —    | 2.5  | —    | 2.5  | mA   |
|                  |  | I <sub>OUT</sub> = 0 mA, f = 0   | Ind.                | —    | 2.5  | —    | 2.5  | —    | 2.5  |      |
|                  |  | $\overline{CS1} = V_{IL}$  | Auto.               | —    | 3    | —    | 3    | —    | 3    |      |
|                  |  | V <sub>IN</sub> ≥ V <sub>DD</sub> - 0.3V, or<br>V <sub>IN</sub> ≤ 0.4V |                     |      |      |      |      |      |      |      |
| I <sub>SB2</sub> | CMOS Standby Current (CMOS Inputs)               | V <sub>DD</sub> = Max.,  | Com.                | —    | 2    | —    | 2    | —    | 2    | μA   |
|                  |  | $\overline{CS1} \geq V_{DD} - 0.2V$ ,                                  | Ind.                | —    | 4    | —    | 4    | —    | 4    |      |
|                  |  | V <sub>IN</sub> ≥ V <sub>DD</sub> - 0.2V, or                           | Auto.               | —    | 18   | —    | 18   | —    | 18   |      |
|                  |  | V <sub>IN</sub> ≤ 0.2V, f = 0  | typ. <sup>(2)</sup> |      | 0.6  |      |      |      |      |      |

#### Note:

- At f = f<sub>MAX</sub>, address and data inputs are cycling at the maximum frequency, f = 0 means no input lines change.
- Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

# IS62WV1288DALL/DBLL

## IS65WV1288DALL/DBLL

### READ CYCLE SWITCHING CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)


| Symbol  | Parameter                                     | 35 ns |      | 45 ns |      | 55 ns |      | Unit |
|---|---|-------|------|-------|------|-------|------|------|
|   |   | Min.  | Max. | Min.  | Max. | Min.  | Max. |      |
| t <sub>RC</sub>                                       | Read Cycle Time                               | 35    | —    | 45    | —    | 55    | —    | ns   |
| t <sub>AA</sub>                                       | Address Access Time                           | —     | 35   | —     | 45   | —     | 55   | ns   |
| t <sub>OHA</sub>                                      | Output Hold Time                              | 10    | —    | 10    | —    | 10    | —    | ns   |
| t <sub>ACS1</sub> /t <sub>ACS2</sub>                  | $\overline{\text{CS1}}$ /CS2 Access Time      | —     | 35   | —     | 45   | —     | 55   | ns   |
| t <sub>DOE</sub>                                      | $\overline{\text{OE}}$ Access Time            | —     | 10   | —     | 20   | —     | 25   | ns   |
| t <sub>HZOE</sub> <sup>(2)</sup>                      | $\overline{\text{OE}}$ to High-Z Output       | —     | 10   | —     | 15   | —     | 20   | ns   |
| t <sub>LZOE</sub> <sup>(2)</sup>                      | $\overline{\text{OE}}$ to Low-Z Output        | 3     | —    | 5     | —    | 5     | —    | ns   |
| t <sub>HZCS1</sub> /t <sub>HZCS2</sub> <sup>(2)</sup> | $\overline{\text{CS1}}$ /CS2 to High-Z Output | 0     | 10   | 0     | 15   | 0     | 20   | ns   |
| t <sub>LZCS1</sub> /t <sub>LZCS2</sub> <sup>(2)</sup> | $\overline{\text{CS1}}$ /CS2 to Low-Z Output  | 5     | —    | 10    | —    | 10    | —    | ns   |

#### Notes:

1. Test conditions assume signal transition times of 5 ns or less, timing reference levels of 0.9V/1.5V, input pulse levels of 0.4 to V<sub>DD</sub>-0.2V/V<sub>DD</sub>-0.3V and output loading specified in Figure 1.
2. Tested with the load in Figure 2. Transition is measured  $\pm 500$  mV from steady-state voltage. Not 100% tested.


## AC WAVEFORMS

### READ CYCLE NO. 1<sup>(1,2)</sup> (Address Controlled) ( $\overline{CS1} = \overline{OE} = V_{IL}$ , $CS2 = \overline{WE} = V_{IH}$ )



## AC WAVEFORMS

### READ CYCLE NO. 2<sup>(1,3)</sup> ( $\overline{CS1}$ , $CS2$ , $\overline{OE}$ Controlled)



#### Notes:

1.  $\overline{WE}$  is HIGH for a Read Cycle.
2. The device is continuously selected.  $\overline{OE}$ ,  $\overline{CS1} = V_{IL}$ .  $CS2 = \overline{WE} = V_{IH}$ .
3. Address is valid prior to or coincident with  $\overline{CS1}$  LOW and  $CS2$  HIGH transition.

# IS62WV1288DALL/DBLL IS65WV1288DALL/DBLL

## WRITE CYCLE SWITCHING CHARACTERISTICS<sup>(1,2)</sup> (Over Operating Range)


| Symbol                               | Parameter                            | 35ns |      | 45ns |      | 55 ns |      | Unit |
|--------------------------------------|--------------------------------------|------|------|------|------|-------|------|------|
|                                      |                                      | Min. | Max. | Min. | Max. | Min.  | Max. |      |
| t <sub>WC</sub>                      | Write Cycle Time                     | 35   | —    | 45   | —    | 55    | —    | ns   |
| t <sub>SCS1</sub> /t <sub>SCS2</sub> | $\overline{CS1}/CS2$ to Write End    | 25   | —    | 35   | —    | 45    | —    | ns   |
| t <sub>AW</sub>                      | Address Setup Time to Write End      | 25   | —    | 35   | —    | 45    | —    | ns   |
| t <sub>HA</sub>                      | Address Hold from Write End          | 0    | —    | 0    | —    | 0     | —    | ns   |
| t <sub>SA</sub>                      | Address Setup Time                   | 0    | —    | 0    | —    | 0     | —    | ns   |
| t <sub>PWE</sub>                     | $\overline{WE}$ Pulse Width          | 25   | —    | 35   | —    | 40    | —    | ns   |
| t <sub>SD</sub>                      | Data Setup to Write End              | 20   | —    | 20   | —    | 25    | —    | ns   |
| t <sub>HD</sub>                      | Data Hold from Write End             | 0    | —    | 0    | —    | 0     | —    | ns   |
| t <sub>HZWE</sub> <sup>(3)</sup>     | $\overline{WE}$ LOW to High-Z Output | —    | 10   | —    | 20   | —     | 20   | ns   |
| t <sub>LZWE</sub> <sup>(3)</sup>     | $\overline{WE}$ HIGH to Low-Z Output | 3    | —    | 5    | —    | 5     | —    | ns   |

### Notes:

1. Test conditions assume signal transition times of 5 ns or less, timing reference levels of 0.9V/1.5V, input pulse levels of 0.4V to V<sub>DD</sub>-0.2V/V<sub>DD</sub>-0.3V and output loading specified in Figure 1.
2. The internal write time is defined by the overlap of  $\overline{CS1}$  LOW, CS2 HIGH and  $\overline{UB}$  or  $\overline{LB}$ , and  $\overline{WE}$  LOW. All signals must be in valid states to initiate a Write, but any one can go inactive to terminate the Write. The Data Input Setup and Hold timing are referenced to the rising or falling edge of the signal that terminates the write.
3. Tested with the load in Figure 2. Transition is measured  $\pm 500$  mV from steady-state voltage. Not 100% tested.

## AC WAVEFORMS


### WRITE CYCLE NO. 1 ( $\overline{CS1}/CS2$ Controlled, $\overline{OE}$ = HIGH or LOW)






## AC WAVEFORMS

### WRITE CYCLE NO. 2 ( $\overline{WE}$ Controlled: $\overline{OE}$ is HIGH During Write Cycle)



### WRITE CYCLE NO. 3 ( $\overline{WE}$ Controlled: $\overline{OE}$ is LOW During Write Cycle)




## DATA RETENTION SWITCHING CHARACTERISTICS


| Symbol           | Parameter                          | Test Condition                                       | Min.            | typ. <sup>(1)</sup> | Max.         | Unit |
|------------------|------------------------------------|--|-----------------|---------------------|--------------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                          | 1.2             |                     | 3.6          | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 1.2V, CS1 ≥ V <sub>DD</sub> - 0.2V | —               | 0.5                 | 2<br>4<br>18 | μA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                          | 0               |                     | —            | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                          | t <sub>RC</sub> |                     | —            | ns   |

Note: 1. Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

### DATA RETENTION WAVEFORM (CS1 Controlled)



### DATA RETENTION WAVEFORM (CS2 Controlled)



## ORDERING INFORMATION

### IS62WV1288DALL (1.65V - 2.2V)

Industrial Range: -40°C to +85°C

| Speed (ns) | Order Part No.       | Package                         |
|------------|----------------------|---------------------------------|
| 55         | IS62WV1288DALL-55TI  | TSOP-I (8mmx20mm)               |
|            | IS62WV1288DALL-55TLI | TSOP-I, Lead-free (8mmx20mm)    |
|            | IS62WV1288DALL-55HI  | sTSOP-I (8mmx13.4mm)            |
|            | IS62WV1288DALL-55HLI | sTSOP-I, Lead-free (8mmx13.4mm) |
|            | IS62WV1288DALL-55BI  | mini BGA (6mm x 8mm)            |
|            | IS62WV1288DALL-55BLI | mini BGA (6mm x 8mm), Lead-free |

## ORDERING INFORMATION

### IS62WV1288DBLL (2.3V - 3.6V)

Industrial Range: -40°C to +85°C<sup>1</sup>


| Speed (ns) | Order Part No.       | Package                         |
|------------|----------------------|---------------------------------|
| 45         | IS62WV1288DBLL-45TI  | TSOP-I (8mmx20mm)               |
|            | IS62WV1288DBLL-45TLI | TSOP-I, Lead-free (8mmx20mm)    |
|            | IS62WV1288DBLL-45HI  | sTSOP-I (8mmx13.4mm)            |
|            | IS62WV1288DBLL-45HLI | sTSOP-I, Lead-free (8mmx13.4mm) |
|            | IS62WV1288DBLL-45QI  | SOP                             |
|            | IS62WV1288DBLL-45QLI | SOP, Lead-free                  |
|            | IS62WV1288DBLL-45BI  | mini BGA (6mm x 8mm)            |
|            | IS62WV1288DBLL-45BLI | mini BGA (6mm x 8mm), Lead-free |




### Automotive Range: -40°C to +125°C

| Speed (ns) | Order Part No.        | Package                         |
|------------|-----------------------|---------------------------------|
| 45         | IS65WV1288DBLL-45TLA3 | TSOP-I, Lead-free (8mmx20mm)    |
|            | IS65WV1288DBLL-45HLA3 | sTSOP-I, Lead-free (8mmx13.4mm) |
|            | IS65WV1288DBLL-45QLA3 | SOP, Lead-free                  |

#### Notes:

1. Speed = 35ns for temperature range of 0°C to +70°C or for  $V_{DD} = 3.3V \pm 5\%$ .





**NOTE :**

1. Controlling dimension : mm
2. Dimension D1 adn E do not include mold protrusion .
3. Dimension b does not include dambar protrusion/intrusion.
4. Formed leads shall be planar with respect to one another within 0.1mm at the seating plane after final test.

| SYMBOL | DIMENSION IN MM |           |       |
|--------|-----------------|-----------|-------|
|        | MIN             | NDM       | MAX   |
| A      | 1.00            |           | 1.20  |
| A1     | 0.05            |           | 0.20  |
| A2     | 0.95            | 1.00      | 1.05  |
| b      | 0.17            |           | 0.27  |
| D      | 19.80           | 20.00     | 20.20 |
| D1     | 18.30           | 18.40     | 18.50 |
| E      | 7.80            | 8.00      | 8.20  |
| e      |                 | 0.50 BSC. |       |
| L      | 0.40            |           | 0.70  |
| L1     |                 | 0.25 BSC. |       |
| ZD     |                 | 0.25 REF. |       |
| Θ      | 0               | 5°        | 8°    |

ISSI®

TITLE


32L 8x20mm TSOP-1  
Package Outline

REV.


E

DATE

06/08/2006



TOP VIEW



| SYMBOL   | DIMENSION IN MM |      |      | DIMENSION IN INCH |       |       |
|----------|-----------------|------|------|-------------------|-------|-------|
|          | MIN.            | NOM. | MAX. | MIN.              | NOM.  | MAX.  |
| A        |                 |      | 1.20 |                   |       | 0.047 |
| A1       | 0.20            |      | 0.30 | 0.008             |       | 0.012 |
| $\phi b$ | 0.30            | 0.35 | 0.40 | 0.012             | 0.014 | 0.016 |
| D        | 7.90            | 8.00 | 8.10 | 0.311             | 0.315 | 0.319 |
| D1       | 5.25            | BSC. |      | 0.207             | BSC.  |       |
| E        | 5.90            | 6.00 | 6.10 | 0.232             | 0.236 | 0.240 |
| E1       | 3.75            | BSC. |      | 0.148             | BSC.  |       |
| e        | 0.75            | BSC. |      | 0.030             | BSC.  |       |
| ZD       | 1.375           | REF. |      | 0.054             | REF.  |       |
| ZE       | 1.125           | REF. |      | 0.044             | REF.  |       |

**NOTE :**

1. CONTROLLING DIMENSION : MM .
2. Reference document : JEDEC MO-207



TITLE

36/48L 6x8mm TF-BGA  
Package Outline

REV.

E

DATE

08/12/2008