


Ordering Information




Reference Voltage Tolerance	Package Type	Pin-out Version	Lead	Packing
O : $\pm 0.4\%$ N : $\pm 1.0\%$	H : TO92-3L C : SOT23-3L	Blank (TO92-3L) 1. REF 2. ANODE 3. CATHODE A (SOT23-3L) 1. CATHODE 2. REF 3. ANODE R (SOT23-3L) 1. REF 2. CATHODE 3. ANODE	P : RoHS & Halogen Free (ref. IEC 61249-2-21)	A : Tape & Reel

Product Number	Output Voltage Tolerance	Package	Lead	Packing
LT431OHPA	0.4 %	TO92-3L	RoHS& Halogen Free	Taping
LT431NHPA	1.0 %	TO92-3L	RoHS& Halogen Free	Taping
LT431OCAPA	0.4 %	SOT23-3L	RoHS& Halogen Free	Taping & Reel
LT431NCAPA	1.0 %	SOT23-3L	RoHS& Halogen Free	Taping & Reel
LT431OCRPA	0.4 %	SOT23-3L	RoHS& Halogen Free	Taping & Reel
LT431NCRPA	1.0 %	SOT23-3L	RoHS& Halogen Free	Taping & Reel

Pin Assignment


TO92-3L
(Top View)



LT431OHPA
LT431NHPA

1.R
2.A
3.C


SOT23-3L
(Top View)



LT431OCAPA
LT431NCAPA

1.C
2.R
3.A

SOT23-3L
(Top View)



LT431OCRPA
LT431NCRPA

1.R
2.C
3.A

Pin Descriptions

Pin Name	Pin Description
R	Ref
A	Anode
C	Cathode

Absolute Maximum Ratings(at $T_A=25^{\circ}\text{C}$)

Note: Operate over the “Absolute Maximum Ratings” may cause permanent damage to the device.
Exposure to such conditions for extended time may still affect the reliability of the device.

Characteristics		Symbol	Rating	Unit
Cathode Voltage		V _{KA}	40	V
Continuous Cathode Current		I _{KA}	250	mA
Reference Input Current		I _{REF}	10	mA
Junction Temperature		T _J	160	°C
Storage Temperature		T _{STG}	-40~150	°C
Thermal Resistance (Junction to Case)	SOT23-3L	θ _{jc}	110	°C/W
	TO92-3L		80	
Thermal Resistance (Junction to Ambient)	SOT23-3L	θ _{ja}	350	°C/W
	TO92-3L		150	
Power dissipation	SOT23-3L	P _D	285	mW
	TO92-3L		625	
Moisture Sensitivity		MSL	Please refer the MSL label on the IC package bag/carton for detail	

Note1 : Ratings apply to ambient temperature at 25°C

Recommended Operating Conditions

Characteristics	Symbol	Min	Max	Unit
Cathode Voltage	V_{KA}	V_{REF}	36	V
Cathode Current	I_{KA}	0.5	200	mA
Operating Temperature (Operating free-air temperature)	T_A	-20	85	$^{\circ}\text{C}$

Electrical Characteristics

(T_A=25°C, unless otherwise specified)

Characteristics	Symbol	Conditions	Min	Typ	Max	Unit
Reference Voltage	V _{REF}	V _{KA} = V _{REF} , I _{KA} = 10mA (Fig.1)	0.4 %	2.485	2.495	V
			1.0 %	2.470	2.520	
Deviation of Reference Input Voltage over full temperature Range(*Note 2)	V _{REF(DEV)}	V _{KA} = V _{REF} , I _{KA} = 10mA, T _A = -20~85°C (Fig.1)		6.0	20	mV
Reference Input Current	I _{REF}	R1 = 10KΩ, R2 = ∞ I _{KA} = 10mA (Fig.2)		1.5	3.5	uA
Deviation of Reference Input Current over Temperature	I _{REF(DEV)}	R1 = 10KΩ, R2 = ∞ I _{KA} = 10mA T _A = -20~85°C (Fig.2)		0.4	1.2	uA
Ratio of the Change in Reference V _{KA} = 10V ~V _{REF} - -1.2 -2.0 Voltage to the Change in Cathode Voltage	ΔV _{REF} ΔV _{KA}	I _{KA} = 10mA (Fig.2)	V _{KA} = 10V ~V _{REF}	-1.2	-2.0	mV/V
			V _{KA} = 36V ~10V	-1	-2.0	
Minimum Cathode Current for Regulation	I _{KA(min)}	V _{KA} = V _{REF} (Fig.1)		0.2	0.5	mA
Off-state Cathode Current	I _{KA(OFF)}	V _{KA} = 36V, V _{REF} = 0V (Fig.3)		0.1	1	uA
Dynamic Output Impedance	Z _{KA}	V _{KA} = V _{REF} Frequency ≤ 1KHz (Fig.1)		0.2	0.5	Ω

Note 2 : These specifications are guaranteed by design and are not tested when in mass-production.

Application Circuit

Fig1: $V_{KA} = V_{REF}$




Fig2: $V_{KA} > V_{REF}$










Fig3: Off state current





Typical Characteristics





Typical Characteristics(Continued)

(1) Small Signal Voltage Amplification Vs Frequency



TEST CIRCUIT FOR VOLTAGE AMPLIFICATION



(2) Reference Impedance VS Frequency






TEST CIRCUIT FOR REFERENCE IMPEDANCE

Typical Characteristics (Continued)

(3) Pulse Response




(4) Stability boundary conditions



The areas under the curves represent conditions that may cause the device to oscillate. For curves B, C, and D, R_2 and V_I were adjusted to establish the initial V_{KA} and I_{KA} conditions with $C_L = 0$. V_{BATT} and C_L were then adjusted to determine the ranges of stability.

Marking Information

(1) TO92-3L



1) YM = Date Code,


Y: Year, M: Month

2) 431xxx = Marking Code

LT431OHPA: 431OHP

LT431NHPA: 431NHP

(2) SOT23-3L



1) YM = Date Code,

Y: Year, M: Month

2) xxx = Marking Code

LT431OCAPA: OCA


LT431NCAPA: NCA

LT431OCRPA: OCR

LT431NCRPA: NCR

Mechanical Information


(1) Package type: TO92-3L



Symbol	Min	Max
A	4.30	4.70
b	0.38	0.55
c	0.36	0.51
D	4.30	4.70
E	3.30	3.70
e	2.44	2.64
e1	1.27 TYP	
e2	2.20	2.80
L	13.00	14.00
L1	2.50	4.50

Mechanical Information (Continued)

(2) Package type: SOT23-3L



Unit: mm

Symbol	Min	Max
A	0.90	1.15
A1	-	0.10
A2	0.89	1.05
b	0.30	0.50
c	0.07	0.18
D	2.80	3.04
E	2.10	2.64
E1	1.20	1.40
e	0.95 REF	
e1	1.80	2.00
L	0.30	0.50
L1	0.55 REF	
Gauge Plane	0.25 BSC	
θ	0°	8°

MSL (Moisture Sensitive Level) Information

IPC/JEDEC J-STD-020D.1 Moisture Sensitivity Levels Table

LEVEL	FLOOR LIFE		SOAK REQUIREMENTS				
			Standard		Accelerated Equivalent ¹		
					eV 0.40-0.48	eV 0.30-0.39	CONDITION
	TIME	CONDITION	TIME (hours)	CONDITION	TIME (hours)	TIME (hours)	
1	Unlimited	≤30 °C /85% RH	168 +5/-0	85 °C /85% RH	NA	NA	NA
2	1 year	≤30 °C /60% RH	168 +5/-0	85 °C /60% RH	NA	NA	NA
2a	4 weeks	≤30 °C /60% RH	696 ² +5/-0	30 °C /60% RH	120 -1/+0	168 -1/+0	60 °C/ 60% RH
3	168 hours	≤30 °C /60% RH	192 ² +5/-0	30 °C /60% RH	40 -1/+0	52 -1/+0	60 °C/ 60% RH
4	72 hours	≤30 °C /60% RH	96 ² +2/-0	30 °C /60% RH	20 +0.5/-0	24 +0.5/-0	60 °C/ 60% RH
5	48 hours	≤30 °C /60% RH	72 ² +2/-0	30 °C /60% RH	15 +0.5/-0	20 +0.5/-0	60 °C/ 60% RH
a	24 hours	≤30 °C /60% RH	48 ² +2/-0	30 °C /60% RH	10 +0.5/-0	13 +0.5/-0	60 °C/ 60% RH
6	Time on Label (TOL)	≤30 °C /60% RH	TOL	30 °C /60% RH	NA	NA	NA

Note 1: CAUTION - To use the "accelerated equivalent" soak conditions, correlation of damage response (including electrical, after soak and reflow), should be established with the "standard" soak conditions. Alternatively, if the known activation energy for moisture diffusion of the package materials is in the range of 0.40 - 0.48 eV or 0.30 - 0.39 eV, the "accelerated equivalent" may be used. Accelerated soak times may vary due to material properties (e.g. mold compound, encapsulant, etc.). JEDEC document JESD22-A120 provides a method for determining the diffusion coefficient.

Note 2: The standard soak time includes a default value of 24 hours for semiconductor manufacturer's exposure time (MET) between bake and bag and includes the maximum time allowed out of the bag at the distributor's facility. If the actual MET is less than 24 hours the soak time may be reduced. For soak conditions of 30 °C/60% RH, the soak time is reduced by 1 hour for each hour the MET is less than 24 hours. For soak conditions of 60 °C/60% RH, the soak time is reduced by 1 hour for each 5 hours the MET is less than 24 hours. If the actual MET is greater than 24 hours the soak time must be increased. If soak conditions are 30 °C/60% RH, the soak time is increased 1 hour for each hour that the actual MET exceeds 24 hours. If soak conditions are 60 °C/60% RH, the soak time is increased 1 hour for each 5 hours that the actual MET exceeds 24 hours.

Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.