

## 1 Characteristics


**Table 1. Absolute maximum ratings ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ )**

| Symbol    | Parameter                                          |                                        | Value       | Unit               |
|-----------|----------------------------------------------------|----------------------------------------|-------------|--------------------|
| $P_{PP}$  | Peak pulse power dissipation                       | $T_j \text{ initial} = T_{amb}$        | 600         | W                  |
| $P$       | Power dissipation on infinite heatsink             | $T_{amb} = 55\text{ }^{\circ}\text{C}$ | 4           | W                  |
| $T_{stg}$ | Storage temperature range                          |                                        | -65 to +175 | $^{\circ}\text{C}$ |
| $T_j$     | Operating junction temperature range               |                                        | -55 to +175 | $^{\circ}\text{C}$ |
| $T_L$     | Maximum lead temperature for soldering during 10 s |                                        | 260         | $^{\circ}\text{C}$ |


**Table 2. Thermal resistance**

| Symbol        | Parameter                                                        | Value | Unit                 |
|---------------|------------------------------------------------------------------|-------|----------------------|
| $R_{th(j-l)}$ | Junction to leads                                                | 30    | $^{\circ}\text{C/W}$ |
| $R_{th(j-a)}$ | Junction to ambient on printed circuit on recommended pad layout | 120   | $^{\circ}\text{C/W}$ |

**Figure 1. Electrical characteristics - parameter definitions**



**Figure 2. Pulse definition for electrical characteristics**




**Table 3. Electrical characteristics parameter values ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)**

| Order code   | $I_{RM}$ max at $V_{RM}$ |       |     | $V_{BR}$ at $I_R^{(1)}$ |      |      |    | 10 / 1000 $\mu s$ |                  |          | 8 / 20 $\mu s$ |          |          | $\alpha T^{(2)}$    |
|--------------|--------------------------|-------|-----|-------------------------|------|------|----|-------------------|------------------|----------|----------------|----------|----------|---------------------|
|              |                          |       |     |                         |      |      |    | $V_{CL}$          | $I_{PP}$         | $R_D$    | $V_{CL}$       | $I_{PP}$ | $R_D$    |                     |
|              | 25 °C                    | 85 °C |     | Min.                    | Typ. | Max. |    | Max.              |                  | Max.     | Max.           |          |          | Max.                |
|              | $\mu A$                  |       | V   | V                       |      |      | mA | V <sup>(3)</sup>  | A <sup>(4)</sup> | $\Omega$ | V              | A        | $\Omega$ | $10^{-4}/^{\circ}C$ |
| SMA6J5.0A/CA | 20                       | 50    | 5.0 | 6.40                    | 6.74 | 7.07 | 10 | 9.1               | 68               | 0.029    | 14.4           | 275      | 0.027    | 5.7                 |
| SMA6J6.0A/CA | 20                       | 50    | 6.0 | 6.70                    | 7.05 | 7.41 | 10 | 9.5               | 61               | 0.034    | 14.8           | 270      | 0.027    | 5.9                 |
| SMA6J6.5A/CA | 20                       | 50    | 6.5 | 7.20                    | 7.58 | 7.96 | 10 | 10.2              | 56               | 0.040    | 15.2           | 266      | 0.027    | 6.1                 |
| SMA6J8.5A/CA | 20                       | 50    | 8.5 | 9.4                     | 9.9  | 10.4 | 1  | 13.3              | 41.7             | 0.070    | 19.5           | 205      | 0.044    | 7.3                 |
| SMA6J10A/CA  | 0.2                      | 1     | 10  | 11.1                    | 11.7 | 12.3 | 1  | 15.7              | 37               | 0.093    | 21.7           | 184      | 0.051    | 7.8                 |
| SMA6J12A/CA  | 0.2                      | 1     | 12  | 13.3                    | 14.0 | 14.7 | 1  | 18.8              | 31               | 0.133    | 25.3           | 157      | 0.068    | 8.3                 |
| SMA6J13A/CA  | 0.2                      | 1     | 13  | 14.4                    | 15.2 | 15.9 | 1  | 20.4              | 29               | 0.154    | 27.2           | 147      | 0.076    | 8.4                 |
| SMA6J15A/CA  | 0.2                      | 1     | 15  | 16.7                    | 17.6 | 18.5 | 1  | 23.6              | 25.1             | 0.206    | 32.5           | 123      | 0.114    | 8.8                 |
| SMA6J18A/CA  | 0.2                      | 1     | 18  | 20.0                    | 21.1 | 22.1 | 1  | 28.3              | 21.5             | 0.288    | 39.3           | 102      | 0.168    | 9.2                 |
| SMA6J20A/CA  | 0.2                      | 1     | 20  | 22.2                    | 23.4 | 24.5 | 1  | 31.4              | 19.4             | 0.354    | 42.8           | 93       | 0.196    | 9.4                 |
| SMA6J24A/CA  | 0.2                      | 1     | 24  | 26.7                    | 28.1 | 29.5 | 1  | 37.8              | 16               | 0.516    | 50             | 80       | 0.256    | 9.6                 |
| SMA6J26A/CA  | 0.2                      | 1     | 26  | 28.9                    | 30.4 | 31.9 | 1  | 40.9              | 14.9             | 0.600    | 53.5           | 75       | 0.288    | 9.7                 |
| SMA6J28A/CA  | 0.2                      | 1     | 28  | 31.1                    | 32.7 | 34.4 | 1  | 44.0              | 13.8             | 0.697    | 59             | 68       | 0.363    | 9.8                 |
| SMA6J33A/CA  | 0.2                      | 1     | 33  | 36.7                    | 38.6 | 40.6 | 1  | 51.9              | 11.8             | 0.963    | 69             | 57       | 0.512    | 10.0                |
| SMA6J40A/CA  | 0.2                      | 1     | 40  | 44.4                    | 46.7 | 49.1 | 1  | 62.8              | 9.7              | 1.42     | 84             | 48       | 0.728    | 10.1                |
| SMA6J48A/CA  | 0.2                      | 1     | 48  | 53.3                    | 56.1 | 58.9 | 1  | 75.4              | 8.1              | 2.04     | 100            | 40       | 1.03     | 10.3                |
| SMA6J58A/CA  | 0.2                      | 1     | 58  | 64.4                    | 67.8 | 71.2 | 1  | 91.1              | 6.7              | 2.97     | 121            | 33       | 1.51     | 10.4                |
| SMA6J70A/CA  | 0.2                      | 1     | 70  | 77.8                    | 81.9 | 86.0 | 1  | 110               | 5.5              | 4.38     | 146            | 27       | 2.22     | 10.5                |
| SMA6J85A/CA  | 0.2                      | 1     | 85  | 94                      | 99   | 104  | 1  | 134               | 4.6              | 6.45     | 178            | 22.5     | 3.29     | 10.6                |
| SMA6J100A/CA | 0.2                      | 1     | 100 | 111                     | 117  | 123  | 1  | 157               | 3.8              | 9.03     | 212            | 19       | 4.69     | 10.7                |
| SMA6J130A/CA | 0.2                      | 1     | 130 | 144                     | 152  | 159  | 1  | 204               | 3                | 14.9     | 265            | 15       | 7.03     | 10.8                |
| SMA6J154A/CA | 0.2                      | 1     | 154 | 171                     | 180  | 189  | 1  | 242               | 2.4              | 22.1     | 317            | 12.6     | 10.2     | 10.8                |
| SMA6J170A/CA | 0.2                      | 1     | 170 | 189                     | 199  | 209  | 1  | 275               | 2.2              | 30.0     | 353            | 11.3     | 12.7     | 10.8                |
| SMA6J188A/CA | 0.2                      | 1     | 188 | 209                     | 220  | 231  | 1  | 328               | 2                | 48.5     | 388            | 10.3     | 15.2     | 10.8                |


- Pulse test:  $t_p < 50\text{ ms}$
- To calculate  $V_{BR}$  or  $V_{CL}$  versus junction temperature, use the following formulas:
  - $V_{BR}$  at  $T_J = V_{BR}$  at  $25\text{ °C} \times (1 + \alpha T \times (T_J - 25))$
  - $V_{CL}$  at  $T_J = V_{CL}$  at  $25\text{ °C} \times (1 + \alpha T \times (T_J - 25))$
- To calculate maximum clamping voltage at other surge level, use the following formula:
  - $V_{CLmax} = V_{BRmax} + R_D \times I_{PPappli}$  where  $I_{PPappli}$  is the surge current in the application
- Surge capability given for both directions for unidirectional and bidirectional types.

## 1.1 Characteristics (curves)


**Figure 3. Peak power dissipation versus initial junction temperature**







**Figure 4. Peak pulse power versus exponential pulse duration ( $T_{amb} = 25^\circ\text{C}$ )**




**Figure 5. Clamping voltage versus peak pulse current (exponential waveform, maximum values)**




**Figure 6. Junction capacitance versus reverse applied voltage (typical values) (SMA6JxxA)**

**Figure 7. Junction capacitance versus reverse applied voltage (typical values) (SMA6JxxCA)**

**Figure 8. Peak forward voltage drop versus peak forward current (typical values)**

**Figure 9. Relative variation of thermal impedance junction to ambient versus pulse duration (printed circuit board FR4,  $S_{Cu} = 1\text{ cm}^2$ )**


**Figure 10. Thermal resistance junction to ambient versus copper surface under each lead (printed circuit board FR4,  $e_{Cu} = 35 \mu m$ )**



**Figure 11. Leakage current versus junction temperature (typical values)**



## 2 Package information


---

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

## 2.1 SMA package information



- Case: JEDEC DO214-AA molded plastic over planar junction
- Terminals: solder plated, solderable per MIL-STD-750, method 2026
- Polarity: for unidirectional types the band indicates cathode
- Flammability: epoxy is rated UL94V-0
- RoHS package

**Figure 12. SMA package outline**



**Table 4. SMA package mechanical data**


| Ref. | Dimensions  |      |        |        |
|------|-------------|------|--------|--------|
|      | Millimeters |      | Inches |        |
|      | Min.        | Max. | Min.   | Max.   |
| A1   | 1.90        | 2.45 | 0.0748 | 0.0964 |
| A2   | 0.05        | 0.20 | 0.0020 | 0.0079 |
| b    | 1.25        | 1.65 | 0.0492 | 0.0649 |
| c    | 0.15        | 0.40 | 0.0059 | 0.0157 |
| D    | 2.25        | 2.90 | 0.0885 | 0.1141 |
| E    | 4.80        | 5.35 | 0.1889 | 0.2106 |
| E1   | 3.95        | 4.60 | 0.1555 | 0.1811 |
| L    | 0.75        | 1.50 | 0.0295 | 0.0591 |

**Figure 13. SMA recommended footprint**

**Figure 14. Marking layout**


Note: Marking layout can vary according to assembly location.

### 3 Ordering information

**Figure 15. Ordering information scheme**



**Table 5. Ordering information**

| Order code <sup>(1)</sup> | Marking                | Package | Weight  | Base qty. | Delivery mode |
|---------------------------|------------------------|---------|---------|-----------|---------------|
| SMA6JxxA-TR               | See Table 6. Marking . | SMA     | 0.072 g | 5000      | Tape and reel |
| SMA6JxxCA-TR              |                        |         |         |           |               |

1. xx indicates stand-off voltage

**Table 6. Marking**

| Type         | Marking | Type          | Marking |
|--------------|---------|---------------|---------|
| SMA6J5.0A-TR | 6UA     | SMA6J5.0CA-TR | 6BA     |
| SMA6J6.0A-TR | 6UB     | SMA6J6.0CA-TR | 6BB     |
| SMA6J6.5A-TR | 6UC     | SMA6J6.5CA-TR | 6BC     |
| SMA6J8.5A-TR | 6UD     | SMA6J8.5CA-TR | 6BD     |
| SMA6J10A-TR  | 6UE     | SMA6J10CA-TR  | 6BE     |
| SMA6J12A-TR  | 6UF     | SMA6J12CA-TR  | 6BF     |
| SMA6J13A-TR  | 6UG     | SMA6J13CA-TR  | 6BG     |
| SMA6J15A-TR  | 6UH     | SMA6J15CA-TR  | 6BH     |
| SMA6J18A-TR  | 6UJ     | SMA6J18CA-TR  | 6BJ     |
| SMA6J20A-TR  | 6UK     | SMA6J20CA-TR  | 6BK     |

| Type         | Marking | Type          | Marking |
|--------------|---------|---------------|---------|
| SMA6J24A-TR  | 6UM     | SMA6J24CA-TR  | 6BM     |
| SMA6J26A-TR  | 6UN     | SMA6J26CA-TR  | 6BN     |
| SMA6J28A-TR  | 6UO     | SMA6J28CA-TR  | 6BO     |
| SMA6J33A-TR  | 6UQ     | SMA6J33CA-TR  | 6BQ     |
| SMA6J40A-TR  | 6UR     | SMA6J40CA-TR  | 6BR     |
| SMA6J48A-TR  | 6US     | SMA6J48CA-TR  | 6BS     |
| SMA6J58A-TR  | 6UT     | SMA6J58CA-TR  | 6BT     |
| SMA6J70A-TR  | 6UU     | SMA6J70CA-TR  | 6BU     |
| SMA6J85A-TR  | 6UV     | SMA6J85CA-TR  | 6BV     |
| SMA6J100A-TR | 6UW     | SMA6J100CA-TR | 6BW     |
| SMA6J130A-TR | 6UX     | SMA6J130CA-TR | 6BX     |
| SMA6J154A-TR | 6UY     | SMA6J154CA-TR | 6BY     |
| SMA6J170A-TR | 6UZ     | SMA6J170CA-TR | 6BZ     |
| SMA6J188A-TR | 6UAA    | SMA6J188CA-TR | 6BAA    |

## Revision history

**Table 7. Document revision history**

| Date        | Revision | Changes                                                                                                     |
|-------------|----------|-------------------------------------------------------------------------------------------------------------|
| 21-Feb-2007 | 1        | First issue.                                                                                                |
| 7-Nov-2007  | 2        | Updated Description. Improved readability of Ordering information scheme. Reformatted to current standards. |
| 04-Aug-2014 | 3        | Updated weight in Table 7.                                                                                  |
| 28-Oct-2015 | 4        | Updated Table 4 and Figure 3.                                                                               |
| 04-Jul-2017 | 5        | Updated Table 4.                                                                                            |
| 22-Jan-2018 | 6        | Updated Table3.                                                                                             |
| 30-Aug-2018 | 7        | Updated <a href="#">Table 6. Marking</a> .                                                                  |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved