



My Cart



My Part Lists

Sign In/Register



English (Change)

Have a Question?

Chat with a Product  
Information Specialist



What can we help you find?



Products

Industries

Resources

About TE

My Account

Innovation

Support Center

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details

## 5406298-1 Product Details

Share

Print

Email



5406298-1

TE Internal Number: 5406298-1

Active

View 3D PDF

### PCB Mounted Jacks - Single Port, Multi-port and Stacked



Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ45

View all Features

#### Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

#### Documentation & Additional Information

##### Product Drawings:

- MODULAR JACK ASSEMBLY, SINGLE PORT, 8 POSITION, SHIE... (PDF, English)

##### Catalog Pages/Data Sheets:

- 1-1773464-9\_MODULAR\_JACKS\_SINGLE\_PORT\_PCB\_MOUNT (PDF, English)

##### Product Specifications:

- High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English)

##### Application Specifications:

- Modular Jacks (PDF, English)

##### Instruction Sheets:

- None Available

##### CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version A)
- 3D Model (IGES, Version A)
- 3D Model (STEP, Version A)

##### Additional Information:

- Product Line Information

##### Related Products:

- Tooling

List all Documents

#### Product Features (Please use the Product Drawing for all design activity)

##### Product Type Features:

- Product Type = Connector
- Jack Type = RJ45
- PCB Mounting Orientation = Side Entry (Right Angle)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3
- LED = Without
- Grounding Options = Panel Ground and PCB Ground
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black
- Shield Material = Copper Alloy
- Latch Style = Standard

##### Mechanical Attachment:

- Panel Mount Retention = With
- Flanged = No

##### Electrical Characteristics:

- Shielded = Yes

##### Termination Features:

- Solder Tail Contact Plating = Tin over Nickel

##### Dimensions:

- Height (mm [in]) = 13.72 [0.540]
- PCB Tail Length (mm [in]) = 3.56 [0.140]
- PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]

##### Body Features:

- Inverted Jack Face = No
- Shield Plating = Bright Tin
- PCB Ground Tab Location (mm [in]) = -3.05 [-0.120]

##### Contact Features:

- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze

##### Housing Features:

- Housing Material = High Temperature Nylon
- UL Flammability Rating = UL 94V-0

##### Configuration Features:

- Preloaded = Yes
- Port Configuration = Single
- Jack Configuration = 1 x 1
- Number of Positions = 8
- Number of Contacts Loaded = 8
- Number of PCB Ground Tabs = 2
- Panel Ground Location = Top and Side, Top

##### Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

##### Packaging Features:

- Packaging Method = Tray

##### Product Availability:

- Region = Asia, North America

##### Other:

- Brand = AMP

#### Corporate Information

About TE

Investors

News Room

Supplier Portal

Careers

Terms & Conditions

Privacy Policy

#### Quick Links

Distributor Inventory

Product Cross Reference

Documents & Drawings

Product Compliance Support Center

Site Map

#### Customer Support

Email or Chat With Us

Find a Phone Number

Knowledge Base

Manage Your Account

#### Keep Me Informed

