

Honeywell Sensing and Control

Search



narrow your search

Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6165)
- Switches (9781)
- Wireless (45)

Technology

- Control and Instrumentation (890)
- Electromechanical (9307)
- Magnetic (541)
- Platinum thin film (56)
- Thick Film (1372)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™

[find out more](#)

white papers

- Wireless Switches Offer Unlimited Benefit
- Basic Switches Are Not Created Equal
- Applying Precision Switches
- Sensors for Medical Devices
- New Ways to Measure Torque
- Choosing Safety Switches
- Specifying Hour Meters

Need help?

[Click here to contact us](#)

CSNE151-104

(Home : Products : Sensors » Current Sensors » Closed Loop » CSN)



Actual product
appearance may
vary.

CSN Series closed loop current sensor, measures ac, dc or impulse current, 25 amp-turns nominal, ±56 amp-turns range, miniature housing, 2000 turn

[Sales & Service](#)[Distributor Inventory](#)
[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Product Type	Closed Loop Linear
Sensed Current Type	ac or dc
Sensed Current Range	±56 A
Package Type	Series Connect PCB Mount
Output Type	Current
Continuous Current	±40 A
Operate Current	25 A RMS @ 25 °C
Supply Current	±12 mA + Output
Supply Voltage	±15.0 Vdc
Offset Current	< ±0.3 mA
Offset Current Drift	< ±0.6 mA
Coil Resistance	190 Ohm
Response Time	< 1 µs
Coil Turns	2000
Output Nominal	12.5 mA
Operating Temperature	-40 °C to 75 °C [-40 °F to 167 °F]
Storage Temperature	-40 °C to 90 °C [-40 °F to 194 °F]
Measuring Resistance	193 Ohm min., 722 Ohm max.
Housing Material	Glass-filled PBT (UL94-V0)
Mounting	PCB on 9 Pins
Pinout Style	3 Pin
Accuracy	±1.0 %
Availability	Global
Comment	Low cost miniature 25 A sensor.
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Series Name	CSN

contacts

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

my links

[Login to iCOM](#)
[Login to Rep/AD Portal](#)
[Login to Digital University](#)

News Center

Honeywell Introduces
TruStability® NSC Series,
Uncompensated / Unamplified
Board Mount Pressure Sensors

HONEYWELL EXPANDS ITS
LIMITLESS™ PLATFORM WITH
THE LAUNCH OF ITS
GLOBALLY AVAILABLE
INDUSTRIAL WIRELESS
RECEIVER

HONEYWELL INTRODUCES
ITS HAWK™ RESOLVERS 1-
INCH SERIES, FULLY HOUSED
CONFIGURATION

HONEYWELL INTRODUCES
MICROPOWER OMNIPOLAR
DIGITAL HALL-EFFECT
SENSOR ICS WITH LOW
SUPPLY VOLTAGE AND ULTRA
LOW TYPICAL CURRENT

HONEYWELL EXTENDS ITS
TRUSTABILITY® PRESSURE
SENSOR PRODUCT LINE WITH
A SINGLE SIDE LIQUID MEDIA
OPTION

HONEYWELL ADDS NEW 100°
AND 180° ARC
CONFIGURATIONS TO ITS
SMART POSITION SENSOR
PORTFOLIO

MICRO SWITCH
Anniversary site