

Moisture Sensitivity Level (MSL)	3
Floor Life	168 HOURS
Peak Package Body Temperature (PPT)(°C)	260
Maximum Time at Peak Temperature (s)	40
Number of Reflow Cycles	3
REACH SVHC	NXP REACH Statement
UL94 (plastics flammability test)	V0;Burning stops within 10 seconds on a vertical specimen;no drips allowed

Manufacturing Information

Micron Size(μm)	.18
-----------------	-----

Ordering Information

Minimum Package Quantity (MPQ)	800
MPQ Container	BRICK
Exempt from Minimum Delivery Value	Yes
Preferred Order Quantity (POQ)	1600
POQ Container	BOX
Export Control Classification Number (US)	3A991A2
Harmonized Tariff (
CCATS Document	-
ENC Status	-
Other Trade Compliance Documents	-
Budgetary Price excluding tax(US Currency)	1 @ USeach
Order	

Operating Characteristics

Sample Exception Availability	N
-------------------------------	---

Reliability Data Lookup

[Investors](#)

[Partners](#)

[Careers](#)

[Mobile Apps](#)

[Press, News, Blogs](#)

[Contact Us](#)



[NXP News](#)

[Read More](#)

[Privacy](#) | [Terms of Use](#) | [Terms of Sale](#) | [Feedback](#)

©2006-2017 NXP Semiconductors. All rights reserved.